

# Adaptive Server<sup>®</sup> Anywhere Error Messages

Last modified: October 2002 Part Number: 38131-01-0802-01 Copyright © 1989-2002 Sybase, Inc. Portions copyright © 2001-2002 iAnywhere Solutions, Inc. All rights reserved.

No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of iAnywhere Solutions, Inc. iAnywhere Solutions, Inc. is a subsidiary of Sybase, Inc.

Sybase, SYBASE (logo), AccelaTrade, ADA Workbench, Adaptable Windowing Environment, Adaptive Component Architecture, Adaptive Server, Adaptive Server Anywhere, Adaptive Server Enterprise, Adaptive Server Enterprise Monitor, Adaptive Server Enterprise Replication, Adaptive Server Everywhere, Adaptive Server IQ, Adaptive Warehouse, AnswerBase, Anywhere Studio, Application Manager, AppModeler, APT Workbench, APT-Build, APT-Edit, APT-Execute, APT-FORMS, APT-Library, APT-Translator, ASEP, Backup Server, BavCam, Bit-Wise, BizTracker, Certified PowerBuilder Developer, Certified SYBASE Professional, Certified SYBASE Professional (logo), ClearConnect, Client Services, Client-Library, CodeBank, Column Design, ComponentPack, Connection Manager, Convoy/DM, Copernicus, CSP, Data Pipeline, Data Workbench, DataArchitect, Database Analyzer, DataExpress, DataServer, DataWindow, DB-Library, dbQueue, Developers Workbench, Direct Connect Anywhere, DirectConnect, Distribution Director, Dynamo, e-ADK, E-Anywhere, e-Biz Integrator, E-Whatever, EC-GATEWAY, ECMAP, ECRTP, eFulfillment Accelerator, Electronic Case Management, Embedded SOL, EMS, Enterprise Application Studio, Enterprise Client/Server, Enterprise Connect, Enterprise Data Studio, Enterprise Manager, Enterprise SQL Server Manager, Enterprise Work Architecture, Enterprise Work Designer, Enterprise Work Modeler, eProcurement Accelerator, eremote, Everything Works Better When Everything Works Together, EWA, Financial Fusion, Financial Fusion Server, First Impression, Formula One, Gateway Manager, GeoPoint, iAnywhere, iAnywhere Solutions, ImpactNow, Industry Warehouse Studio, InfoMaker, Information Anywhere, Information Everywhere, InformationConnect, InstaHelp, Intellidex, InternetBuilder, iremote, iScript, Jaguar CTS, jConnect for JDBC, KnowledgeBase, Logical Memory Manager, MainframeConnect, Maintenance Express, MAP, MDI Access Server, MDI Database Gateway, media.splash, MetaWorks, MethodSet, ML Ouery, MobiCATS, MySupport, Net-Gateway, Net-Library, New Era of Networks, Next Generation Learning, Next Generation Learning Studio, O DEVICE, OASIS, OASIS (logo), ObjectConnect, ObjectCycle, OmniConnect, OmniSQL Access Module, OmniSQL Toolkit, Open Biz, Open Business Interchange, Open Client, Open Client/Server, Open Client/Server Interfaces, Open ClientConnect, Open Gateway, Open Server, Open ServerConnect, Open Solutions, Optima++, Partnerships that Work, PB-Gen, PC APT Execute, PC DB-Net, PC Net Library, PhysicalArchitect, Pocket PowerBuilder, PocketBuilder, Power Through Knowledge, Power++, power.stop, PowerAMC, PowerBuilder, PowerBuilder Foundation Class Library, PowerDesigner, PowerDimensions, PowerDynamo, Powering the New Economy, PowerJ, PowerScript, PowerSite, PowerSocket, Powersoft, Powersoft Portfolio, Powersoft Professional, PowerStage, PowerStudio, PowerTips, PowerWare Desktop, PowerWare Enterprise, ProcessAnalyst, Rapport, Relational Beans, Replication Agent, Replication Driver, Replication Server, Replication Server Manager, Replication Toolkit, Report Workbench, Report-Execute, Resource Manager, RW-DisplayLib, RW-Library, S Designor, S-Designor, S.W.I.F.T. Message Format Libraries, SAFE, SAFE/PRO, SDF, Secure SQL Server, Secure SQL Toolset, Security Guardian, SKILS, smart.partners, smart.parts, smart.script, SOL Advantage, SOL Anywhere, SOL Anywhere Studio, SOL Code Checker, SOL Debug, SOL Edit, SOL Edit/TPU, SOL Everywhere, SQL Modeler, SQL Remote, SQL Server, SQL Server Manager, SQL Server SNMP SubAgent, SQL Server/CFT, SQL Server/DBM, SQL SMART, SQL Station, SQL Toolset, SQLJ, Stage III Engineering, Startup.Com, STEP, SupportNow, Sybase Central, Sybase Client/Server Interfaces, Sybase Development Framework, Sybase Financial Server, Sybase Gateways, Sybase Learning Connection, Sybase MPP, Sybase SQL Desktop, Sybase SQL Lifecycle, Sybase SQL Workgroup, Sybase Synergy Program, Sybase User Workbench, Sybase Virtual Server Architecture, SybaseWare, Syber Financial, SyberAssist, SybMD, SyBooks, System 10, System 11, System XI (logo), SystemTools, Tabular Data Stream, The Enterprise Client/Server Company, The Extensible Software Platform, The Future Is Wide Open, The Learning Connection, The Model For Client/Server Solutions. The Online Information Center, The Power of One. TradeForce, Transact-SOL, Translation Toolkit, Turning Imagination Into Reality, UltraLite, UNIBOM, Unilib, Uninull, Unisep, Unistring, URK Runtime Kit for UniCode, Viewer, Visual Components, VisualSpeller, VisualWriter, VQL, Warehouse Control Center, Warehouse Studio, Warehouse WORKS, WarehouseArchitect, Watcom, Watcom SQL, Watcom SQL Server, Web Deployment Kit, Web.PB, Web.SQL, WebSights, WebViewer, WorkGroup SQL Server, XA-Library, XA-Server, and XP Server are trademarks of Sybase, Inc. or its subsidiaries.

All other trademarks are property of their respective owners.

Last modified October 2002. Part number 38131-01-0802-01.

## Contents

1

| About This Manual                           | v   |
|---|-----|
| SQL Anywhere Studio documentation           |     |
| Finding out more and providing feedback     |     |
| Database Error Messages                     | 1   |
| Error messages indexed by Adaptive Server   |     |
| Anywhere SQLCODE                            | 2   |
| Error messages indexed by SQLSTATE          |     |
| Error messages indexed by Sybase error code |     |
| Alphabetic list of error messages           |     |
| Internal errors (assertion failed)          |     |
| Index                                       | 319 |

## **About This Manual**

| Subject  | This book provides a complete listing of Adaptive Server Anywhere error messages together with diagnostic information.                |
|----------|---|
| Audience | This manual is for all users of Adaptive Server Anywhere. It is to be used in conjunction with other manuals in the documentation set |

#### **SQL Anywhere Studio documentation**

This book is part of the SQL Anywhere documentation set. This section describes the books in the documentation set and how you can use them.

#### The SQL Anywhere Studio documentation set

The SQL Anywhere Studio documentation set consists of the following books:

- Introducing SQL Anywhere Studio This book provides an overview of the SQL Anywhere Studio database management and synchronization technologies. It includes tutorials to introduce you to each of the pieces that make up SQL Anywhere Studio.
- What's New in SQL Anywhere Studio This book is for users of previous versions of the software. It lists new features in this and previous releases of the product and describes upgrade procedures.
- ◆ Adaptive Server Anywhere Getting Started This book is for people new to relational databases or new to Adaptive Server Anywhere. It provides a quick start to using the Adaptive Server Anywhere databasemanagement system and introductory material on designing, building, and working with databases.
- Adaptive Server Anywhere Database Administration Guide This book covers material related to running, managing, and configuring databases.
- Adaptive Server Anywhere SQL User's Guide This book describes how to design and create databases; how to import, export, and modify data; how to retrieve data; and how to build stored procedures and triggers.
- Adaptive Server Anywhere SQL Reference Manual This book provides a complete reference for the SQL language used by Adaptive Server Anywhere. It also describes the Adaptive Server Anywhere system tables and procedures.
- ♦ Adaptive Server Anywhere Programming Guide This book describes how to build and deploy database applications using the C, C++, and Java programming languages. Users of tools such as Visual Basic and PowerBuilder can use the programming interfaces provided by those tools.

- ♦ Adaptive Server Anywhere Error Messages This book provides a complete listing of Adaptive Server Anywhere error messages together with diagnostic information.
- ♦ Adaptive Server Anywhere C2 Security Supplement Adaptive Server Anywhere 7.0 was awarded a TCSEC (Trusted Computer System Evaluation Criteria) C2 security rating from the U.S. Government. This book may be of interest to those who wish to run the current version of Adaptive Server Anywhere in a manner equivalent to the C2-certified environment. The book does *not* include the security features added to the product since certification.
- MobiLink Synchronization User's Guide This book describes all aspects of the MobiLink data synchronization system for mobile computing, which enables sharing of data between a single Oracle, Sybase, Microsoft or IBM database and many Adaptive Server Anywhere or UltraLite databases.
- ◆ SQL Remote User's Guide This book describes all aspects of the SQL Remote data replication system for mobile computing, which enables sharing of data between a single Adaptive Server Anywhere or Adaptive Server Enterprise database and many Adaptive Server Anywhere databases using an indirect link such as e-mail or file transfer.
- UltraLite User's Guide This book describes how to build database applications for small devices such as handheld organizers using the UltraLite deployment technology for Adaptive Server Anywhere databases.
- ♦ UltraLite User's Guide for PenRight! MobileBuilder This book is for users of the PenRight! MobileBuilder development tool. It describes how to use UltraLite technology in the MobileBuilder programming environment.
- SQL Anywhere Studio Help This book is provided online only. It includes the context-sensitive help for Sybase Central, Interactive SQL, and other graphical tools.

In addition to this documentation set, SQL Modeler and InfoMaker include their own online documentation.

#### **Documentation formats**

SQL Anywhere Studio provides documentation in the following formats:

• Online books The online books include the complete SQL Anywhere Studio documentation, including both the printed books and the context-sensitive help for SQL Anywhere tools. The online books are updated with each maintenance release of the product, and are the most complete and up-to-date source of documentation.

To access the online books on Windows operating systems, choose Start > Programs > Sybase SQL Anywhere 8> Online Books. You can navigate the online books using the HTML Help table of contents, index, and search facility in the left pane, and using the links and menus in the right pane.

To access the online books on UNIX operating systems, run the following command at a command prompt:

dbbooks

• **Printable books** The SQL Anywhere books are provided as a set of PDF files, viewable with Adobe Acrobat Reader.

The PDF files are available on the CD ROM in the *pdf\_docs* directory. You can choose to install them when running the setup program.

- **Printed books** The following books are included in the SQL Anywhere Studio box:
  - Introducing SQL Anywhere Studio.
  - Adaptive Server Anywhere Getting Started.
  - *SQL Anywhere Studio Quick Reference*. This book is available only in printed form.

The complete set of books is available as the SQL Anywhere Documentation set from Sybase sales or from e-Shop, the Sybase online store, at http://e-shop.sybase.com/cgi-bin/eshop.storefront/.

### Finding out more and providing feedback

We would like to receive your opinions, suggestions, and feedback on this documentation.

You can provide feedback on this documentation and on the software through newsgroups set up to discuss SQL Anywhere technologies. These newsgroups can be found on the *forums.sybase.com* news server.

The newsgroups include the following:

- sybase.public.sqlanywhere.general.
- ♦ sybase.public.sqlanywhere.linux.
- sybase.public.sqlanywhere.mobilink.
- sybase.public.sqlanywhere.product\_futures\_discussion.
- sybase.public.sqlanywhere.replication.
- sybase.public.sqlanywhere.ultralite.

#### Newsgroup disclaimer

iAnywhere Solutions has no obligation to provide solutions, information or ideas on its newsgroups, nor is iAnywhere Solutions obliged to provide anything other than a systems operator to monitor the service and insure its operation and availability.

iAnywhere Solutions Technical Advisors as well as other staff assist on the newsgroup service when they have time available. They offer their help on a volunteer basis and may not be available on a regular basis to provide solutions and information. Their ability to help is based on their workload.

## CHAPTER 1 Database Error Messages

| About this chapter | This chapter lists all database error messages reported by Adaptiv<br>Anywhere. Many of the errors contain the characters %1, %2 and<br>These are replaced by the parameters to the error message. |      |
|--------------------|--|------|
|                    | Each error has a numeric error code, called the SQLCODE. Nega<br>are considered errors; positive codes are warnings. The SQLCOD<br>indicates successful completion.                                |      |
|                    | The full listing of the error messages is ordered by SQLCODE va<br>an error message description if you do not have the SQLCODE va<br>up the SQLCODE in the alphabetic or SQLSTATE listing.         |      |
| Contents           | Торіс  | Page |
|                    | Error messages indexed by Adaptive Server Anywhere SQLCODE   | 2    |
|                    | Error messages indexed by SQLSTATE   | 24   |
|                    | Error messages indexed by Sybase error code  | 45   |
|                    | Alphabetic list of error messages  | 72   |
|                    | Internal errors (assertion failed)   | 317  |

# Error messages indexed by Adaptive Server Anywhere SQLCODE

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -895                                      | "Encryption error: %1" on page 158  |
| -894                                      | "Plan can not be generated for this type of statement" on page 228                                      |
| -891                                      | "Cannot convert between requested character sets %1' and %2"<br>on page 98                              |
| -889                                      | "Statement contains an illegal usage of the non-deterministic<br>function %1" on page 256               |
| -883                                      | "Character conversion reporting is not available when the single<br>byte converter is used" on page 121 |
| -882                                      | "An output character could not be converted to the application character set" on page 88                |
| -881                                      | "An input character could not be converted to database character set" on page 84                        |
| -880                                      | "An invalid multi-byte output character was encountered" on page 87                                     |
| -879                                      | "An invalid multi-byte input character was encountered" on page 86                                      |
| -878                                      | "Index '%1' can not be clustered" on page 175   |
| -877                                      | "SETUSER not allowed in procedures, triggers, events or batches" on page 251                            |
| -876                                      | "Client out of memory" on page 123  |
| -875                                      | "There is no way to join to %1" on page 288   |
| -871                                      | "The database needs to be restarted for this Java related command" on page 277                          |
| -870                                      | "Cannot convert between requested character set '%1' and database character set '%2" on page 97         |
| -869                                      | "Database server cannot convert data from/to character set '%1"<br>on page 146                          |
| -868                                      | "%1' is an unknown character set label" on page 75  |
| -867                                      | "Cannot change synchronization user_name when status of the   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
|   | last upload is unknown." on page 96   |
| -865                                      | "Key constraint between temporary tables requires a primary<br>key (not unique constraint)" on page 208                               |
| -864                                      | "Statement contains an illegal usage of the NUMBER(*)<br>function" on page 256  |
| -863                                      | "Grouped query contains more than one distinct aggregate function" on page 170  |
| -862                                      | "The aggregate expression <sup>%</sup> 1' must appear in either the select<br>list or a HAVING clause subquery" on page 273           |
| -861                                      | "Aggregated expression '%1' contains multiple columns of<br>which one or more are outer references" on page 81                        |
| -860                                      | "At least one of the specified dbspaces was not calibrated." on page 90   |
| -859                                      | "%1" on page 75   |
| -858                                      | "CREATE/DROP STATISTICS statement cannot refer to virtual tables" on page 136   |
| -857                                      | "Synchronization failed due to an unspecified error on the server." on page 261   |
| -856                                      | "Invalid sqllen field in SQLDA" on page 197   |
| -855                                      | "Trigger name %1' is ambiguous" on page 293   |
| -854                                      | "Function or column reference to %1' in the ORDER BY clause<br>is invalid" on page 168  |
| -853                                      | "Cursor not in a valid state" on page 139   |
| -852                                      | "Table name %1' is ambiguous" on page 271   |
| -851                                      | "Decryption error: %1" on page 153  |
| -850                                      | "Tables related by key constraint must both be permanent or<br>both be temporary created with ON COMMIT PRESERVE<br>ROWS" on page 272 |
| -849                                      | "Referential integrity actions other than RESTRICT not allowed for temporary tables" on page 235                                      |
| -848                                      | "Exception occurred while loading Java SecurityManager" on page 163   |
| -847                                      | "Java SecurityManager class not found: %1" on page 205  |
| -846                                      | "Set clause for column %1' used incorrectly" on page 251  |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -845                                      | "Owner %1' used in a qualified column reference does not<br>match correlation name %2" on page 224 |
| -844                                      | "Cannot find synchronization definition with the name %1" on page 105                              |
| -843                                      | "Cannot find synchronization user with the name '%1" on page 106                                   |
| -842                                      | "JDK %1' is not a supported JDK" on page 207   |
| -841                                      | "The JDK version in %1' does not match %2" on page 279   |
| -840                                      | "Incorrect or missing encryption key" on page 174  |
| -839                                      | "Download failed because of conflicts with existing rows." on page 156                             |
| -838                                      | "Certicom initialization on server failed" on page 120   |
| -837                                      | "Trigger or foreign key for table %1' is no longer valid" on page 293                              |
| -836                                      | "Procedure %1' is no longer valid" on page 230   |
| -835                                      | "Event %1' in use" on page 162   |
| -834                                      | "Column %1' not found in table %2" on page 126   |
| -833                                      | "Row in table %1' was modified or deleted in BEFORE trigger"<br>on page 244                        |
| -832                                      | "Connection error: %1" on page 128   |
| -831                                      | "Definition for alias '%1' must appear before its first reference"<br>on page 153                  |
| -830                                      | "Alias '%1' is not unique" on page 82  |
| -829                                      | "Certicom handshake failure" on page 120   |
| -828                                      | "A conflict with the DBMLSync download phase was detected"<br>on page 79                           |
| -827                                      | "Database upgrade not possible; user tables have table ids in system table range" on page 150      |
| -826                                      | "Database upgrade not possible; RowGenerator table not owned<br>by user dbo" on page 150           |
| -825                                      | "Previous error lost prior to RESIGNAL" on page 228  |
| -824                                      | "Illegal reference to correlation name '%1' in ON condition" on<br>page 173                        |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -823                                      | "OMNI cannot handle expressions involving remote tables<br>inside stored procedures" on page 222   |
| -822                                      | "Table '%1' is already included" on page 267   |
| -821                                      | "Dbspace for table %1' not found" on page 152  |
| -820                                      | "Invalid scroll position '%1" on page 196  |
| -819                                      | "Table '%1' is part of a synchronization definition" on page 268                                   |
| -818                                      | "The external function call is incompatible" on page 277   |
| -817                                      | "too many temporary tables in connection" on page 290  |
| -816                                      | "Specified database file already in use." on page 252  |
| -815                                      | "Cannot update column <sup>3</sup> %1' since it does not appear in the SELECT clause." on page 118 |
| -814                                      | "Cannot update column <sup>3</sup> %1' since it appears in the ORDER BY clause." on page 117       |
| -813                                      | "FOR UPDATE has been incorrectly specified for a READ ONLY cursor." on page 166                    |
| -812                                      | "The Select list for the derived table '%1' has no expression to match '%2" on page 283            |
| -811                                      | "Jar %1' not found" on page 204  |
| -810                                      | "Java class %1' not found" on page 204   |
| -809                                      | "Synchronization option is too long" on page 263   |
| -808                                      | "An internal error was generated by the test harness" on page 86                                   |
| -807                                      | "Host variables may not be used within a batch" on page 170  |
| -806                                      | "System event type '%1' not found" on page 265   |
| -805                                      | "Synchronization option %1' not found" on page 262   |
| -804                                      | "Unable to reenlist transaction; DTC may be down" on page 298                                      |
| -803                                      | "Unable to enlist transaction; DTC may be down" on page 296  |
| -802                                      | "Cannot enlist in a transaction with uncommitted data pending"<br>on page 104                      |
| -801                                      | "Cannot enlist in a transaction while already enlisted in a transaction" on page 104               |
| -800                                      | "Cannot commit or rollback while enlisted in a transaction" on page 96                             |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -799                                      | "DTC transactions are not supported on this platform" on page 157                       |
| -797                                      | "Synchronization option %1' contains semi-colon, equal sign or curly brace" on page 262 |
| -796                                      | "Synchronization site %1' is already defined" on page 264                               |
| -795                                      | "Undefined synchronization template %1" on page 299                                     |
| -794                                      | "Synchronization server failed to commit the upload" on page 263                        |
| -793                                      | "Invalid start date/time for event %1" on page 198                                      |
| -792                                      | "Invalid time '%1' for event '%2" on page 199   |
| -791                                      | "Invalid day of week or month %1' for event %2" on page 186                             |
| -790                                      | "Cannot register connection to %1' since automatic label<br>exhausted" on page 112      |
| -789                                      | "Cannot register %1' since registration cookie exhausted" on page 111                   |
| -788                                      | "Another connection has already registered as '%1" on page 89                           |
| -787                                      | "Current connection is already registered to %1' as %2" on page 137                     |
| -786                                      | "Cannot deregister '%1' since active registered connection<br>exists" on page 100       |
| -785                                      | "Cannot deregister application because of invalid cookie" on page 101                   |
| -784                                      | "Cannot register connection because of invalid application cookie" on page 112          |
| -783                                      | "Cannot register another '%1' as an exclusive application" on page 111                  |
| -782                                      | "Cannot register %1' since another exclusive instance is<br>running" on page 110        |
| -780                                      | "Cannot update primary key for table %1' involved in a publication" on page 119         |
| -779                                      | "Cannot create synchronization entry for table %1' with BLOB<br>primary key" on page 99 |
| -778                                      | "Must include primary key for table %1' in the synchronization"<br>on page 214          |
| -777                                      | "Cannot synchronize table %1' since it does not have a primary                          |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
|   | key" on page 115   |
| -774                                      | "Schedule %1' for event %2' already exists" on page 247  |
| -773                                      | "Schedule %1' for event %2' not found" on page 247   |
| -772                                      | "Event '%1' already exists" on page 162  |
| -771                                      | "Event '%1' not found" on page 163   |
| -770                                      | "Cannot modify publication entry using ALTER<br>SYNCHRONIZATION" on page 109                                   |
| -769                                      | "Cannot modify synchronization entry using ALTER<br>PUBLICATION" on page 109                                   |
| -768                                      | "Cannot subscribe to '%1" on page 115  |
| -767                                      | "Cannot find synchronization subscription with the name '%1""<br>on page 106                                   |
| -766                                      | "View references '%1', which is a temporary object. Views can<br>only refer to permanent objects." on page 313 |
| -765                                      | "Synchronization message type %1' not found" on page 261   |
| -764                                      | "Server not found and unable to autostart" on page 250   |
| -763                                      | "%1' is not a public Java reference, and cannot be referenced from SQL" on page 77                             |
| -762                                      | "%1' is not a public Java class, and cannot be referenced from SQL" on page 77                                 |
| -761                                      | "Server capability name '%1' could not be found in the SYS.SYSCAPABILITYNAME table." on page 250               |
| -760                                      | "Invalid SQL identifier" on page 197   |
| -759                                      | "SQLDA data type invalid" on page 254  |
| -758                                      | "The database does not support the Java virtual machine" on page 276   |
| -757                                      | "Modifications not permitted for read-only database" on page 212   |
| -756                                      | "Cannot uniquely identify column %2' of table %1' in the current JDBC resultset" on page 116                   |
| -755                                      | "You cannot synchronize with uncommitted transactions" on page 316   |
| -754                                      | "Parse error: %1" on page 226  |
| -753                                      | "The JDBC resultset must be positioned on an insert row in   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
|   | order to use the %1' function" on page 278   |
| -752                                      | "Cannot call the '%1' function on a JDBC resultset when it is<br>positioned on an insert row" on page 95 |
| -751                                      | "User owns tables in use" on page 309  |
| -750                                      | "User owns procedures in use" on page 308  |
| -749                                      | "Feature not available with UltraLite" on page 165   |
| -748                                      | "Invalid JDBC resultset concurrency" on page 191   |
| -747                                      | "Invalid JDBC resultset type" on page 191  |
| -746                                      | "Cannot allocate System V resources" on page 94  |
| -745                                      | "Cannot initialize IQ memory manager: %1" on page 107  |
| -744                                      | "Invalid IQ database command line option or parameter value: %1" on page 190                             |
| -743                                      | "Seek absolute 0 was attempted on a JDBC SAResultSet" on page 248  |
| -742                                      | "JDBC SAStatement batch execute abandoned" on page 207   |
| -741                                      | "%1' is not a write file for %2" on page 78  |
| -740                                      | "The communications environment could not be created" on page 274  |
| -739                                      | "db_init has not been called or the call to db_init failed" on page 151                                  |
| -738                                      | "Password must be at least %1 characters" on page 227  |
| -737                                      | "Signature %1' does not match procedure parameters" on page 252  |
| -736                                      | "The data type of column '%1' is not supported" on page 275  |
| -735                                      | "Invalid parameter" on page 194  |
| -734                                      | "Cannot update or delete an all-NULL row from table <sup>3</sup> %1" or page 119                         |
| -733                                      | "Number of columns allowing NULLs exceeds limit" on page 221   |
| -732                                      | "Creating remote tables with computed columns is not supported" on page 137                              |
| -731                                      | "Cannot drop a user that owns objects involved in replication"<br>on page 102                            |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -730                                      | "Invalid jar file" on page 190  |
| -729                                      | "The specified foreign key (%1) can not be enforced" on<br>page 285                               |
| -728                                      | "Update operation attempted on non-updatable remote query"<br>on page 303                         |
| -727                                      | "The optimizer was unable to construct a valid access plan" on page 280                           |
| -726                                      | "The table specification %1' identifies more than one remote table" on page 286                   |
| -725                                      | "Identity attribute mismatch for column '%1" on page 172  |
| -724                                      | "Null attribute mismatch for column %1" on page 220   |
| -723                                      | "The length specified for column '%1' is different than the actual length" on page 279            |
| -722                                      | "The column '%1' does not exist in the remote table" on page 273                                  |
| -721                                      | "The data type specified for column '%1' is not compatible with the actual data type" on page 276 |
| -720                                      | "VALIDATE TABLE statement must refer to a base table" on page 311                                 |
| -719                                      | "RESTORE unable to start database '%1" on page 240  |
| -718                                      | "RESTORE unable to write to file %1" on page 240  |
| -717                                      | "RESTORE unable to open file %1" on page 239  |
| -716                                      | "Backup file format is invalid" on page 92  |
| -715                                      | "Contents of backup files are inconsistent" on page 130   |
| -714                                      | "Invalid operation on a closed %1" on page 193  |
| -713                                      | "An internal error occurred in a %1" on page 85   |
| -712                                      | "External login for server '% 1' could not be found" on page 164                                  |
| -711                                      | "Incorrect store DLL (%1) version." on page 175   |
| -710                                      | "Invalid comparison" on page 183  |
| -709                                      | "Computed columns are not supported in this database" on page 128                                 |
| -708                                      | "READTEXT or WRITETEXT statement cannot refer to a view" on page 234                              |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -707                                      | "Statement is not allowed in passthrough mode" on page 257                                |
| -706                                      | "Remote server does not have the ability to support this statement" on page 237           |
| -705                                      | "Return type of void from procedure '%1' cannot be used in any expression" on page 241    |
| -704                                      | "Cannot create an index on Java class %1" on page 98                                      |
| -703                                      | "Cannot insert or update computed column '%1"" on page 107                                |
| -702                                      | "TRUNCATE TABLE statement cannot refer to a view" on page 294                             |
| -701                                      | "Cannot access instance member through a class" on page 94                                |
| -700                                      | "SQLDA fields inconsistent for a multi-row SQLDA" on page 254                             |
| -699                                      | "Cannot update member fields qualified with "final" modifier"<br>on page 118              |
| -698                                      | "The remote server does not support an auto-incrementing data type" on page 282           |
| -697                                      | "Error during backup: %1" on page 159   |
| -696                                      | "Invalid operation on a closed %1" on page 192  |
| -695                                      | "An internal error occurred in a %1" on page 85   |
| -694                                      | "Could not change an opened prepared statement or callable<br>statement" on page 132      |
| -693                                      | "JDBC feature '%1' not supported" on page 206   |
| -692                                      | "Could not execute backup/restore DLL (%1) entry point." on page 133                      |
| -691                                      | "Could not load the backup/restore DLL "%1"" on page 135                                  |
| -690                                      | "Return value cannot be set" on page 242  |
| -689                                      | "Input parameter index out of range" on page 178  |
| -688                                      | "Strongly-encrypted database files are not supported in the runtime server" on page 258   |
| -687                                      | "Syntax error, cannot specify IQ specific options without specifying IQ PATH" on page 265 |
| -686                                      | "Insufficient cache to start Java virtual machine" on page 179                            |
| -685                                      | "Resource governor for %1' exceeded" on page 239  |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -684                                      | "Rollback occurred due to deadlock during prefetch" on page 242                               |
| -683                                      | "The cursor name %1' already exists" on page 275  |
| -682                                      | "%1" on page 74   |
| -681                                      | "Invalid join type used with Transact-SQL outer join" on page 191                             |
| -680                                      | "Invalid expression in WHERE clause of Transact-SQL outer<br>join" on page 188                |
| -679                                      | "Not enough memory is allocated to the Java virtual machine<br>for remote access" on page 219 |
| -678                                      | "Index name %1' is ambiguous" on page 176   |
| -677                                      | "Table %1' has a foreign key with a referential action" on page 266                           |
| -676                                      | "The specified transaction isolation is invalid" on page 285                                  |
| -675                                      | "Java virtual machine could not be started" on page 205                                       |
| -674                                      | "statement's size limit is invalid." on page 258  |
| -673                                      | "Database upgrade not possible" on page 149   |
| -672                                      | "Database upgrade failed" on page 149   |
| -671                                      | "Parameter not registered as output parameter" on page 226                                    |
| -670                                      | "Invalid class byte code" on page 182   |
| -669                                      | "Method %1' cannot be called at this time" on page 211  |
| -668                                      | "Cursor is restricted to FETCH NEXT operations" on page 138                                   |
| -667                                      | "Could not access column information for the table %1" on<br>page 131                         |
| -666                                      | "The remote table '%1' could not be found" on page 283  |
| -665                                      | "Database "%1" needs recovery" on page 141  |
| -664                                      | "Database is active" on page 143  |
| -663                                      | "Cannot deserialize Java object" on page 101  |
| -662                                      | "Cannot serialize Java object with class %1" on page 113                                      |
| -661                                      | "Backwards scrolling cursors are not supported for remote objects" on page 92                 |
| -660                                      | "Server '%1': %2" on page 249   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -659                                      | "Remote server '%1' could not be found; Add the server using CREATE SERVER" on page 236 |
| -658                                      | "Remote server '%1' is currently configured as read only" on page 236                   |
| -657                                      | "Unable to connect to server %1': server definition is circular"<br>on page 295         |
| -656                                      | "Unable to connect to server %1': %2" on page 295                                       |
| -655                                      | "Error parsing connection parameter string" on page 161                                 |
| -654                                      | "The connection parameters file could not be found" on page 274                         |
| -653                                      | "Cannot remove class %1': member of Jar" on page 113                                    |
| -652                                      | "Could not decompress class %1' from Jar." on page 133                                  |
| -651                                      | "An attempt to delete database '%1' failed" on page 83                                  |
| -650                                      | "Index type specification of %1' is invalid" on page 177                                |
| -649                                      | "Field %1' of class %2' cannot be null" on page 166                                     |
| -648                                      | "Cannot create item (%1) in the specified dbspace." on page 99                          |
| -647                                      | "Could not execute store DLL (%1) entry point." on page 134                             |
| -646                                      | "Could not load the store DLL "%1"" on page 136   |
| -645                                      | "Database creation failed: %1" on page 143  |
| -644                                      | "Invalid database page size" on page 185  |
| -643                                      | "UNLOAD TABLE cannot be used to unload a view" on page 301                              |
| -642                                      | "Invalid SQL descriptor name" on page 197   |
| -641                                      | "Error in assignment" on page 159   |
| -640                                      | "Invalid descriptor index" on page 187  |
| -639                                      | "Parameter name missing in call to procedure %1" on page 225                            |
| -638                                      | "Right truncation of string data" on page 242   |
| -637                                      | "Duplicate insert column" on page 157   |
| -636                                      | "Duplicate referencing column" on page 157  |
| -635                                      | "GRANT of column permission on view not allowed" on page 169                            |
| -634                                      | "Unterminated C string" on page 302   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -633                                      | "Update operation attempted on a read-only cursor" on page 302                                      |
| -632                                      | "WITH CHECK OPTION violated for insert/update on base table %1" on page 314                         |
| -631                                      | "RAISERROR executed: %1" on page 234  |
| -630                                      | "Invalid escape sequence '%1" on page 188   |
| -629                                      | "Invalid escape character '%1" on page 187  |
| -628                                      | "Division by zero" on page 156  |
| -627                                      | "Disallowed language extension detected in syntax near '%1""<br>on page 154                         |
| -626                                      | "A thread used internally could not be started" on page 81  |
| -625                                      | "Too many parameters to this external procedure call" on page 289                                   |
| -624                                      | "Expression has unsupported data type" on page 164  |
| -623                                      | "Data definition statements not allowed in procedures or triggers" on page 140                      |
| -622                                      | "Could not allocate resources to call external function" on<br>page 132                             |
| -621                                      | "Could not find %1' in dynamic library %2" on page 134  |
| -620                                      | "Could not load dynamic library %1" on page 135   |
| -619                                      | "Need a dynamic library name" on page 215   |
| -618                                      | "Mismatch between external function platform specifier and<br>current operating system" on page 211 |
| -617                                      | "Calling functions outside the database server is not supported"<br>on page 92                      |
| -616                                      | "Too many columns in table" on page 289   |
| -615                                      | "Parameter %1' not found in procedure %2" on page 225   |
| -614                                      | "Cannot drop a user that owns messages or data types" on page 102                                   |
| -613                                      | "User-defined type '%1' not found" on page 310  |
| -612                                      | "User message %1 not found" on page 308   |
| -611                                      | "Transact-SQL feature not supported" on page 290  |
| -610                                      | "User message %1 already exists" on page 307  |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -609                                      | "Invalid data type for column in WRITETEXT or READTEXT"<br>on page 185  |
| -608                                      | "Invalid TEXTPTR value used with WRITETEXT or READTEXT" on page 199   |
| -607                                      | "Cannot stop the database server" on page 114   |
| -606                                      | "The pattern is too long" on page 282   |
| -605                                      | "The server attempted to access a page beyond the end of the maximum allowable dbspace file size" on page 284 |
| -604                                      | "A dbspace has reached its maximum file size" on page 80  |
| -602                                      | "Cannot access file %1' %2" on page 93  |
| -601                                      | " <sup>3</sup> %1' is not a known file format for loading or unloading tables"<br>on page 76                  |
| -504                                      | "(no message)" on page 73   |
| -503                                      | "(no message)" on page 72   |
| -313                                      | "The login ID %1' has not been mapped to any database user ID" on page 280                                    |
| -312                                      | "User %1' already has membership in group %2" on page 304   |
| -311                                      | "Internal rollback log corrupted" on page 182   |
| -310                                      | "Attempt to read beyond end-of-file in a compressed database"<br>on page 90                                   |
| -309                                      | "Memory error transaction rolled back" on page 210  |
| -308                                      | "Connection was terminated" on page 129   |
| -307                                      | "All threads are blocked" on page 82  |
| -306                                      | "Deadlock detected" on page 152   |
| -305                                      | "I/O error %1 transaction rolled back" on page 171  |
| -304                                      | "Disk full '%1' transaction rolled back" on page 155  |
| -303                                      | "Disk write failure '%1' transaction rolled back" on page 155   |
| -302                                      | "Terminated by user transaction rolled back" on page 272  |
| -301                                      | "Internal database error %1 transaction rolled back" on page 181  |
| -300                                      | "Run time SQL error %1" on page 245   |
| -299                                      | "Statement interrupted by user" on page 257   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -298                                      | "Attempted two active database requests" on page 90                          |
| -297                                      | "User-defined exception signaled" on page 309                                |
| -296                                      | "Error number %1 for RAISERROR may not be less than 17000" on page 160       |
| -295                                      | "Cannot uniquely identify rows in cursor" on page 116                        |
| -294                                      | "Format string argument number %1 is invalid" on page 168                    |
| -289                                      | "A consolidated user already exists" on page 79                              |
| -288                                      | "Remote statement failed" on page 237  |
| -287                                      | "Passthrough statement inconsistent with current passthrough"<br>on page 227 |
| -286                                      | "Remote message type '%1' not found" on page 235                             |
| -285                                      | "User %1' is not a remote user for this database" on page 306                |
| -284                                      | "User '%1' is already the publisher for this database" on page 305           |
| -283                                      | "Subscription to %1' for %2' not found" on page 260                          |
| -282                                      | "Subscription to %1' for %2' already exists" on page 260                     |
| -281                                      | "Table '%1' has publications" on page 267                                    |
| -280                                      | "Publication '%1' not found" on page 233                                     |
| -275                                      | "Triggers and procedures not supported in runtime server" on page 294        |
| -274                                      | "Procedure or trigger calls have nested too deeply" on page 233              |
| -273                                      | "COMMIT/ROLLBACK not allowed within trigger actions" on page 127             |
| -272                                      | "Invalid REFERENCES clause in trigger definition" on page 195                |
| -271                                      | "Trigger definition conflicts with existing triggers" on page 292            |
| -270                                      | "Cannot drop a user that owns procedures in runtime server" on page 103      |
| -269                                      | "Cannot delete a column referenced in a trigger definition" on page 100      |
| -268                                      | "Trigger <sup>*</sup> %1' not found" on page 292                             |
| -267                                      | "COMMIT/ROLLBACK not allowed within atomic operation"<br>on page 126         |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -266                                      | "%1" on page 74  |
| -265                                      | "Procedure %1' not found" on page 231  |
| -264                                      | "Wrong number of variables in FETCH" on page 316   |
| -263                                      | "Invalid absolute or relative offset in FETCH" on page 182                                   |
| -262                                      | "Label '%1' not found" on page 208   |
| -261                                      | "There is already a variable named %1" on page 287   |
| -260                                      | "Variable %1' not found" on page 313   |
| -251                                      | "Foreign key '%1' for table '%2' duplicates an existing foreign key" on page 167             |
| -250                                      | "Identifier '%1' too long" on page 171   |
| -249                                      | "The login ID %1' is already mapped to user ID %2" on page 280                               |
| -248                                      | "Cannot map a login ID to the sys or public user ID" on page 108                             |
| -247                                      | "The integrated login ID guest can only be mapped to the guest database user ID" on page 278 |
| -246                                      | "Integrated logins are not supported for this database" on page 180                          |
| -245                                      | "Integrated login failed" on page 179  |
| -244                                      | "Transaction log was truncated" on page 291  |
| -243                                      | "Unable to delete database file" on page 296   |
| -242                                      | "Incomplete transactions prevent transaction log renaming" on page 174                       |
| -241                                      | "Database backup not started" on page 141  |
| -240                                      | "Unknown backup operation" on page 300   |
| -231                                      | "Client/database server version mismatch" on page 123  |
| -230                                      | "Sqlpp/dblib version mismatch" on page 255   |
| -222                                      | "Result set not allowed from within an atomic compound statement" on page 241                |
| -221                                      | "ROLLBACK TO SAVEPOINT not allowed" on page 243  |
| -220                                      | "Savepoint '%1' not found" on page 246   |
| -218                                      | "Authentication failed" on page 91   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -217                                      | "The option %1' cannot be set from within a procedure" on page 281                          |
| -216                                      | "The option %1' can only be set as a temporary option" on page 281                          |
| -215                                      | "Procedure in use by %1" on page 232  |
| -214                                      | "Table in use" on page 270  |
| -213                                      | "Savepoints require a rollback log" on page 246   |
| -212                                      | "CHECKPOINT statement requires a rollback log" on page 122                                  |
| -211                                      | "Not allowed while <sup>3</sup> %1' is using the database" on page 217                      |
| -210                                      | "User %1' has the row in %2' locked" on page 305  |
| -209                                      | "Invalid value for column '%1' in table '%2" on page 203                                    |
| -208                                      | "Row has changed since last read operation cancelled" on page 244                           |
| -207                                      | "Wrong number of values for INSERT" on page 315   |
| -206                                      | "Integrated logins are required, standard logins are not permitted" on page 181             |
| -205                                      | "Integrated logins are not permitted" on page 180   |
| -204                                      | "Only the DBA can set the option '%1" on page 223   |
| -203                                      | "Cannot set a temporary option for user '%1"" on page 114                                   |
| -202                                      | "Only PUBLIC settings are allowed for option '%1" on page 223                               |
| -201                                      | "Invalid setting for option %1" on page 196   |
| -200                                      | "Invalid option '%1' no PUBLIC setting exists" on page 193                                  |
| -199                                      | "INSERT/DELETE on cursor can modify only one table" on page 178                             |
| -198                                      | "Primary key for row in table %1' is referenced by foreign key %2' in table %3" on page 229 |
| -197                                      | "No current row of cursor" on page 215  |
| -196                                      | "Index '%1' for table '%2' would not be unique" on page 176                                 |
| -195                                      | "Column %1' in table %2' cannot be NULL" on page 125  |
| -194                                      | "No primary key value for foreign key %1' in table %2" on page 217                          |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| -193                                      | "Primary key for table %1' is not unique" on page 230           |
| -192                                      | "Update operation attempted on non-updatable query" on page 303 |
| -191                                      | "Cannot modify column '%1' in table '%2" on page 108            |
| -190                                      | "Cannot update an expression" on page 117                       |
| -189                                      | "Unable to find in index %1' for table %2" on page 297          |
| -188                                      | "Not enough values for host variables" on page 220              |
| -187                                      | "Illegal cursor operation attempt" on page 172                  |
| -186                                      | "Subquery cannot return more than one row" on page 259          |
| -185                                      | "SELECT returns more than one row" on page 249                  |
| -183                                      | "Cannot find index named '%1"" on page 105                      |
| -182                                      | "Not enough fields allocated in SQLDA" on page 218              |
| -181                                      | "No indicator variable provided for NULL result" on page 216    |
| -180                                      | "Cursor not open" on page 139                                   |
| -172                                      | "Cursor already open" on page 138                               |
| -171                                      | "Error opening cursor" on page 160                              |
| -170                                      | "Cursor has not been declared" on page 138                      |
| -165                                      | "Java VM heap exhausted at internal function: %1" on page 206   |
| -164                                      | "Namespace heap exhausted at internal function: %1" on page 214 |
| -163                                      | "Derived table %1' has no name for column %2" on page 154       |
| -161                                      | "Invalid type on DESCRIBE statement" on page 200                |
| -160                                      | "Can only describe a SELECT statement" on page 93               |
| -159                                      | "Invalid column number" on page 183                             |
| -158                                      | "Value %1 out of range for destination" on page 311             |
| -157                                      | "Cannot convert %1 to a %2" on page 97                          |
| -156                                      | "Invalid expression near '%1" on page 189                       |
| -155                                      | "Invalid host variable" on page 189                             |
| -154                                      | "Wrong number of parameters to function %1" on page 315         |
| -153                                      | "SELECT lists in UNION do not match in length" on page 248      |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -152                                      | "Invalid ORDER BY specification" on page 194                                     |
| -151                                      | "Subquery allowed only one select list item" on page 259                         |
| -150                                      | "Invalid use of an aggregate function" on page 201                               |
| -149                                      | "Function or column reference to %1' must also appear in a GROUP BY" on page 169 |
| -148                                      | "Unknown function %1" on page 300  |
| -147                                      | "There is more than one way to join '%1' to '%2" on page 287                     |
| -146                                      | "There is no way to join '%1' to '%2" on page 288                                |
| -145                                      | "Foreign key name '%1' not found" on page 167                                    |
| -144                                      | "Column %1' found in more than one table need a correlation<br>name" on page 124 |
| -143                                      | "Column '%1' not found" on page 125  |
| -142                                      | "Correlation name %1' not found" on page 131                                     |
| -141                                      | "Table '%1' not found" on page 269   |
| -140                                      | "User ID '%1' does not exist" on page 307  |
| -139                                      | "More than one table is identified as %1" on page 213                            |
| -138                                      | "Dbspace '%1' not found" on page 151   |
| -137                                      | "Table '%1' requires a unique correlation name" on page 269                      |
| -136                                      | "Table '%1' is in an outer join cycle" on page 268                               |
| -135                                      | "Language extension" on page 209   |
| -134                                      | "Feature %1' not implemented" on page 165  |
| -133                                      | "Invalid prepared statement type" on page 195                                    |
| -132                                      | "SQL statement error" on page 254  |
| -131                                      | "Syntax error near '%1' %2" on page 264  |
| -130                                      | "Invalid statement" on page 198  |
| -128                                      | "Cannot drop a user that owns tables in runtime system" on page 103              |
| -127                                      | "Cannot alter a column in an index" on page 95                                   |
| -126                                      | "Table cannot have two primary keys" on page 270                                 |
| -125                                      | "ALTER clause conflict" on page 83   |
| -124                                      | "More columns are being dropped from table %1' than are                          |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
|   | defined" on page 212  |
| -123                                      | "User '%1' is not a user group" on page 306   |
| -122                                      | "Operation would cause a group cycle" on page 224                                       |
| -121                                      | "%1" on page 73   |
| -120                                      | "User '%1' already has GRANT permission" on page 304                                    |
| -119                                      | "Primary key column % 1' already defined" on page 229                                   |
| -118                                      | "Table %1' has no primary key" on page 266  |
| -116                                      | "Table must be empty" on page 271   |
| -114                                      | "Number of columns defined for the view does not match<br>SELECT statement" on page 222 |
| -113                                      | "Column %1' in foreign key has a different definition than<br>primary key" on page 124  |
| -112                                      | "Table already has a primary key" on page 270   |
| -111                                      | "Index name %1' not unique" on page 177   |
| -110                                      | "Item '%1' already exists" on page 203  |
| -109                                      | "There are still active database connections" on page 286                               |
| -108                                      | "Connection not found" on page 129  |
| -107                                      | "Error writing to transaction log file" on page 161                                     |
| -106                                      | "Cannot open transaction log file %1" on page 110                                       |
| -105                                      | "Database cannot be started %1" on page 142   |
| -104                                      | "Invalid user ID or password on preprocessed module" on page 202                        |
| -103                                      | "Invalid user ID or password" on page 202   |
| -103                                      | "Invalid user ID or password" on page 202   |
| -102                                      | "Database server connection limit exceeded" on page 147                                 |
| -101                                      | "Not connected to a database" on page 218   |
| -100                                      | "Database server not found" on page 148   |
| -99                                       | "Connections to database have been disabled" on page 130                                |
| -98                                       | "Authentication violation" on page 91   |
| -97                                       | "Database page size too big" on page 145  |
| -96                                       | "Database server already running" on page 146   |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message  |
|---|--|
| -95                                       | "Parse error: %1" on page 226  |
| -94                                       | "Invalid type for field reference" on page 200                       |
| -93                                       | "Class %1' has no public field %2" on page 122                       |
| -92                                       | "%1' is not a valid class file" on page 78                           |
| -91                                       | "Procedure '%1' terminated with unhandled exception '%2" on page 231 |
| -90                                       | "Argument %1 of procedure '%2' cannot be null" on page 89            |
| -89                                       | "Database server not running in multi-user mode" on page 148         |
| -88                                       | "Client/server communications protocol version mismatch" on page 123 |
| -87                                       | "Database name required to start server" on page 144                 |
| -86                                       | "Not enough memory to start" on page 219                             |
| -85                                       | "Communication error" on page 127                                    |
| -84                                       | "Specified database is invalid" on page 253                          |
| -83                                       | "Specified database not found" on page 253                           |
| -82                                       | "Unable to start specified database: %1" on page 299                 |
| -81                                       | "Invalid database server command line" on page 186                   |
| -80                                       | "Unable to start database server" on page 298                        |
| -79                                       | "Invalid local database switch" on page 192                          |
| -78                                       | "Dynamic memory exhausted" on page 158                               |
| -77                                       | "Database name not unique" on page 144                               |
| -76                                       | "Request denied no active databases" on page 238                     |
| -75                                       | "Request to start/stop database denied" on page 238                  |
| -74                                       | "The selected database is currently inactive" on page 284            |
| -72                                       | "No database file specified" on page 216                             |
| 0   | "(no message)" on page 72  |
| 100                                       | "Row not found" on page 245  |
| 101                                       | "Value truncated" on page 312  |
| 102                                       | "Using temporary table" on page 310                                  |
| 103                                       | "Invalid data conversion" on page 184                                |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| 104                                       | "Row has been updated since last time read" on page 243   |
| 105                                       | "Procedure has completed" on page 232   |
| 106                                       | "Value for column %1' in table %2' has changed" on page 312   |
| 107                                       | "Language extension detected in syntax" on page 210   |
| 109                                       | "Null value eliminated in aggregate function" on page 221   |
| 110                                       | "Transaction log backup page only partially full" on page 291   |
| 111                                       | "Statement cannot be executed" on page 255  |
| 112                                       | "More information required" on page 213   |
| 113                                       | "Database option %1' for user %2' has an invalid setting" on page 145   |
| 114                                       | "Character set translation to %1' cannot be performed; %2' is used instead" on page 121   |
| 115                                       | "Database server cannot convert data from/to character set '%1', conversion may not be correct" on page 147                                   |
| 116                                       | "Language %1' is not supported, %2' will be used" on page 209   |
| 117                                       | "Unsupported character set <sup>%</sup> 1' and unsupported language <sup>%</sup> 2';<br>language used is <sup>%</sup> 3' instead" on page 301 |
| 118                                       | "Illegal user selectivity estimate specified" on page 173   |
| 119                                       | "Unable to open backup log %1" on page 297  |
| 120                                       | "%1' is an unknown option" on page 76   |
| 121                                       | "Cursor option values changed" on page 140  |
| 123                                       | "Database created without any schema" on page 142   |
| 124                                       | "Invalid data conversion: NULL was inserted for column <sup>3</sup> %1' on line %2." on page 184  |
| 125                                       | "An invalid multi-byte input character was encountered" on page 86  |

| Adaptive<br>Server<br>Anywhere<br>SQLCODE | Error message   |
|---|---|
| 126                                       | "An invalid multi-byte output character was encountered" on page 87   |
| 127                                       | "An input character could not be converted to database character<br>set and simple substitution took place" on page 84      |
| 128                                       | "An output character could not be converted to the application character set and simple substitution took place" on page 88 |
| 130                                       | "A row could not be converted to the new schema format" on page 80  |
| 200                                       | "Warning" on page 314   |

### **Error messages indexed by SQLSTATE**

Adaptive Server Anywhere supports the SQLSTATE error code defined by SQL/92. Each SQLSTATE value is a 5- character string containing a 2- character class followed by a 3-character subclass. Each character can be one of the uppercase letters A through Z or the digits 0 through 9. A class that begins with A through H or 0 through 4 has been defined by the ANSI standard; other classes are implementation defined. Similarly, subclasses of standard classes that start with the same characters (A-H, 0-4) are standard. The subclass 000 always means that no subclass code is defined. The most common SQLSTATE value is 00000, which indicates successful completion.

| SQLSTATE | Error message  |  |
|----------|--|--|
| 00000    | "(no message)" on page 72  |  |
| 01000    | "Warning" on page 314  |  |
| 01003    | "Null value eliminated in aggregate function" on page 221  |  |
| 01004    | "Value truncated" on page 312  |  |
| 01S02    | "Cursor option values changed" on page 140   |  |
| 01W01    | "Invalid data conversion: NULL was inserted for column 3%1'<br>on line %2." on page 184                        |  |
| 01W02    | "Using temporary table" on page 310  |  |
| 01W03    | "Invalid data conversion" on page 184  |  |
| 01W04    | "Row has been updated since last time read" on page 243  |  |
| 01W05    | "Procedure has completed" on page 232  |  |
| 01W06    | "Value for column %1' in table %2' has changed" on page 312  |  |
| 01W07    | "Language extension detected in syntax" on page 210  |  |
| 01W08    | "Statement cannot be executed" on page 255   |  |
| 01W09    | "More information required" on page 213  |  |
| 01W10    | "Transaction log backup page only partially full" on page 291  |  |
| 01W11    | "Database option %1' for user %2' has an invalid setting" on page 145  |  |
| 01W12    | "Character set translation to %1' cannot be performed; %2' is used instead" on page 121                        |  |
| 01W13    | "Database server cannot convert data from/to character set<br>'%1', conversion may not be correct" on page 147 |  |
| 01W14    | "Language %1' is not supported, %2' will be used" on page 209  |  |

| SQLSTATE | Error message   |
|----------|---|
| 01W15    | "Unsupported character set %1' and unsupported language<br>%2'; language used is %3' instead" on page 301                   |
| 01W16    | "Illegal user selectivity estimate specified" on page 173   |
| 01W17    | "%1' is an unknown option" on page 76   |
| 01W19    | "Database created without any schema" on page 142   |
| 01W21    | "A row could not be converted to the new schema format" on page 80  |
| 01WC1    | "An invalid multi-byte input character was encountered" on page 86  |
| 01WC2    | "An invalid multi-byte output character was encountered" on page 87   |
| 01WC3    | "An input character could not be converted to database<br>character set and simple substitution took place" on page 84      |
| 01WC4    | "An output character could not be converted to the application character set and simple substitution took place" on page 88 |
| 02000    | "Row not found" on page 245   |
| 04W07    | "A dbspace has reached its maximum file size" on page 80  |
| 04W08    | "The server attempted to access a page beyond the end of the maximum allowable dbspace file size" on page 284               |
| 07001    | "Not enough values for host variables" on page 220  |
| 07002    | "Not enough fields allocated in SQLDA" on page 218  |
| 07003    | "Error opening cursor" on page 160  |
| 07005    | "Can only describe a SELECT statement" on page 93   |
| 07009    | "Invalid descriptor index" on page 187  |
| 07W01    | "Invalid type on DESCRIBE statement" on page 200  |
| 07W02    | "Invalid statement" on page 198   |
| 07W03    | "Invalid prepared statement type" on page 195   |
| 07W04    | "SQLDA fields inconsistent for a multi-row SQLDA" on page 254   |
| 07W05    | "SQLDA data type invalid" on page 254   |
| 07W06    | "Invalid SQL identifier" on page 197  |
| 07W07    | "Host variables may not be used within a batch" on page 170   |
| 07W08    | "Invalid sqllen field in SQLDA" on page 197   |
| 08001    | "Database cannot be started %1" on page 142   |

| SQLSTATE | Error message  |
|----------|--|
| 08003    | "Not connected to a database" on page 218                            |
| 08004    | "User ID '%1' does not exist" on page 307                            |
| 08W01    | "Database server not found" on page 148                              |
| 08W02    | "Connection not found" on page 129                                   |
| 08W03    | "Database server connection limit exceeded" on page 147              |
| 08W04    | "Connections to database have been disabled" on page 130             |
| 08W05    | "Cannot open transaction log file %1" on page 110                    |
| 08W06    | "There are still active database connections" on page 286            |
| 08W07    | "Unable to start database server" on page 298                        |
| 08W08    | "Invalid database server command line" on page 186                   |
| 08W09    | "Unable to start specified database: %1" on page 299                 |
| 08W10    | "Specified database not found" on page 253                           |
| 08W11    | "Specified database is invalid" on page 253                          |
| 08W12    | "Communication error" on page 127                                    |
| 08W13    | "Not enough memory to start" on page 219                             |
| 08W14    | "Database name required to start server" on page 144                 |
| 08W15    | "Client/server communications protocol version mismatch" on page 123 |
| 08W16    | "Database server not running in multi-user mode" on page 148         |
| 08W17    | "Error writing to transaction log file" on page 161                  |
| 08W18    | "Sqlpp/dblib version mismatch" on page 255                           |
| 08W19    | "Client/database server version mismatch" on page 123                |
| 08W21    | "Authentication violation" on page 91                                |
| 08W22    | "Database page size too big" on page 145                             |
| 08W23    | "Database server already running" on page 146                        |
| 08W24    | "Invalid parameter" on page 194                                      |
| 08W25    | "Invalid local database switch" on page 192                          |
| 08W26    | "Dynamic memory exhausted" on page 158                               |
| 08W27    | "Database name not unique" on page 144                               |
| 08W28    | "Request denied no active databases" on page 238                     |
| 08W29    | "Request to start/stop database denied" on page 238                  |
| 08W30    | "The selected database is currently inactive" on page 284            |
|          |  |

| SQLSTATE | Error message   |
|----------|---|
| 08W32    | "Invalid database page size" on page 185  |
| 08W33    | "Database creation failed: %1" on page 143  |
| 08W34    | "Could not load the store DLL "%1"" on page 136   |
| 08W35    | "Could not execute store DLL (%1) entry point." on page 134                                   |
| 08W36    | "Cannot create item (%1) in the specified dbspace." on page 99                                |
| 08W37    | "The connection parameters file could not be found" on page 274                               |
| 08W38    | "Error parsing connection parameter string" on page 161                                       |
| 08W39    | "No database file specified" on page 216  |
| 08W40    | "Database is active" on page 143  |
| 08W41    | "Database "%1" needs recovery" on page 141  |
| 08W42    | "Database upgrade failed" on page 149   |
| 08W43    | "Database upgrade not possible" on page 149   |
| 08W44    | "Could not load the backup/restore DLL "%1"" on page 135                                      |
| 08W45    | "Could not execute backup/restore DLL (%1) entry point." on page 133                          |
| 08W46    | "Error during backup: %1" on page 159   |
| 08W47    | "Incorrect store DLL (%1) version." on page 175   |
| 08W48    | "Authentication failed" on page 91  |
| 08W49    | "Parse error: %1" on page 226   |
| 08W50    | " <sup>%</sup> 1' is not a write file for <sup>%</sup> 2" on page 78                          |
| 08W51    | "Invalid IQ database command line option or parameter value: %1" on page 190                  |
| 08W52    | "Cannot initialize IQ memory manager: %1" on page 107   |
| 08W53    | "Cannot allocate System V resources" on page 94   |
| 08W54    | "Parse error: %1" on page 226   |
| 08W55    | "Server not found and unable to autostart" on page 250  |
| 08W56    | "Specified database file already in use." on page 252   |
| 08W57    | "Database upgrade not possible; RowGenerator table not<br>owned by user dbo" on page 150      |
| 08W58    | "Database upgrade not possible; user tables have table ids in system table range" on page 150 |
| 08W59    | "Certicom handshake failure" on page 120  |

| SQLSTATE | Error message   |
|----------|---|
| 08W60    | "Connection error: %1" on page 128  |
| 08W61    | "Certicom initialization on server failed" on page 120                          |
| 08W62    | "Incorrect or missing encryption key" on page 174                               |
| 08W63    | "Decryption error: %1" on page 153  |
| 08W64    | "Database server cannot convert data from/to character set<br>'%1"" on page 146 |
| 08W65    | "Client out of memory" on page 123  |
| 08W66    | "Encryption error: %1" on page 158  |
| 09W02    | "Illegal cursor operation attempt" on page 172                                  |
| 09W04    | "INSERT/DELETE on cursor can modify only one table" on page 178                 |
| 09W05    | "Cannot uniquely identify rows in cursor" on page 116                           |
| 09W06    | "Cursor is restricted to FETCH NEXT operations" on page 138                     |
| 09W07    | "statement's size limit is invalid." on page 258                                |
| 09W08    | "Cannot update or delete an all-NULL row from table '%1" on page 119            |
| 0A000    | "Feature %1' not implemented" on page 165                                       |
| 0AW01    | "Language extension" on page 209  |
| 0AW02    | "Transact-SQL feature not supported" on page 290                                |
| 0AW03    | "Disallowed language extension detected in syntax near %1""<br>on page 154      |
| 0AW04    | "Triggers and procedures not supported in runtime server" on page 294           |
| 0AW05    | "Statement is not allowed in passthrough mode" on page 257                      |
| 0AW06    | "Computed columns are not supported in this database" on page 128               |
| 0AW07    | "Feature not available with UltraLite" on page 165                              |
| 0AW08    | "You cannot synchronize with uncommitted transactions" on page 316              |
| 0AW09    | "Synchronization server failed to commit the upload" on page 263                |
| 0AW10    | "DTC transactions are not supported on this platform" on page 157               |
| 0AW11    | "Download failed because of conflicts with existing rows." on page 156          |

| SQLSTATE | Error message   |
|----------|---|
| 0AW12    | "Synchronization failed due to an unspecified error on the server." on page 261                 |
| 0AW13    | "Cannot change synchronization user_name when status of the last upload is unknown." on page 96 |
| 0AW14    | "Plan can not be generated for this type of statement" on page 228                              |
| 21000    | "SELECT returns more than one row" on page 249  |
| 21W01    | "Subquery cannot return more than one row" on page 259  |
| 22001    | "Right truncation of string data" on page 242   |
| 22002    | "No indicator variable provided for NULL result" on page 216                                    |
| 22003    | "Value %1 out of range for destination" on page 311   |
| 22005    | "Error in assignment" on page 159   |
| 22012    | "Division by zero" on page 156  |
| 22019    | "Invalid escape character '%1" on page 187  |
| 22024    | "Unterminated C string" on page 302   |
| 22025    | "Invalid escape sequence '%1" on page 188   |
| 22W02    | "Row has changed since last read operation cancelled" on<br>page 244                            |
| 22W03    | "Invalid TEXTPTR value used with WRITETEXT or READTEXT" on page 199                             |
| 23502    | "Column %1' in table %2' cannot be NULL" on page 125  |
| 23503    | "No primary key value for foreign key %1' in table %2" on page 217                              |
| 23504    | "Number of columns allowing NULLs exceeds limit" on page 221                                    |
| 23505    | "Index %1' for table %2' would not be unique" on page 176                                       |
| 23506    | "Invalid value for column <sup>3</sup> %1' in table <sup>3</sup> %2" on page 203                |
| 23507    | "The specified foreign key (%1) can not be enforced" on<br>page 285                             |
| 23W01    | "Primary key for table '%1' is not unique" on page 230  |
| 23W05    | "Primary key for row in table %1' is referenced by foreign key<br>%2' in table %3" on page 229  |
| 24000    | "Cursor not in a valid state" on page 139   |
| 24501    | "Cursor not open" on page 139   |
| 24502    | "Cursor already open" on page 138   |

| SQLSTATE | Error message  |
|----------|--|
| 24503    | "No current row of cursor" on page 215   |
| 24504    | "Invalid scroll position '%1" on page 196  |
| 24W01    | "Cursor has not been declared" on page 138   |
| 26501    | "SQL statement error" on page 254  |
| 28000    | "Password must be at least %1 characters" on page 227  |
| 28000    | "Invalid user ID or password" on page 202  |
| 28000    | "Invalid user ID or password" on page 202  |
| 28W01    | "Invalid user ID or password on preprocessed module" on page 202                             |
| 28W02    | "Integrated logins are not permitted" on page 180  |
| 28W03    | "Integrated logins are required, standard logins are not permitted" on page 181              |
| 28W04    | "Integrated login failed" on page 179  |
| 28W05    | "Integrated logins are not supported for this database" on page 180                          |
| 28W06    | "The integrated login ID guest can only be mapped to the guest database user ID" on page 278 |
| 28W07    | "Cannot map a login ID to the sys or public user ID" on page 108                             |
| 28W08    | "The login ID %1' is already mapped to user ID %2" on page 280                               |
| 28W09    | "The login ID <sup>%</sup> 1' has not been mapped to any database user ID" on page 280       |
| 2D501    | "COMMIT/ROLLBACK not allowed within trigger actions"<br>on page 127                          |
| 33000    | "Invalid SQL descriptor name" on page 197  |
| 37505    | "Wrong number of parameters to function %1" on page 315                                      |
| 3B001    | "Savepoint %1' not found" on page 246  |
| 3B002    | "ROLLBACK TO SAVEPOINT not allowed" on page 243  |
| 3BW01    | "Savepoints require a rollback log" on page 246  |
| 3BW02    | "Result set not allowed from within an atomic compound<br>statement" on page 241             |
| 40000    | "Run time SQL error %1" on page 245  |
| 40001    | "Deadlock detected" on page 152  |
| 40W01    | "Internal database error %1 transaction rolled back" on                                      |

| SQLSTATE | Error message   |
|----------|---|
|          | page 181  |
| 40W02    | "Terminated by user transaction rolled back" on page 272  |
| 40W03    | "Disk full %1' transaction rolled back" on page 155   |
| 40W04    | "I/O error %1 transaction rolled back" on page 171  |
| 40W05    | "Disk write failure '%1' transaction rolled back" on page 155   |
| 40W06    | "All threads are blocked" on page 82  |
| 40W07    | "Connection was terminated" on page 129   |
| 40W08    | "Memory error transaction rolled back" on page 210  |
| 42501    | "%1" on page 73   |
| 42R01    | "Referential integrity actions other than RESTRICT not<br>allowed for temporary tables" on page 235                                   |
| 42R02    | "Tables related by key constraint must both be permanent or<br>both be temporary created with ON COMMIT PRESERVE<br>ROWS" on page 272 |
| 42R03    | "Key constraint between temporary tables requires a primary<br>key (not unique constraint)" on page 208                               |
| 42U00    | "View references '%1', which is a temporary object. Views can<br>only refer to permanent objects." on page 313                        |
| 42U01    | "Illegal reference to correlation name %1' in ON condition" on page 173   |
| 42U02    | "Owner '%1' used in a qualified column reference does not<br>match correlation name '%2" on page 224                                  |
| 42U03    | "Set clause for column %1' used incorrectly" on page 251  |
| 42W01    | "User '%1' already has GRANT permission" on page 304  |
| 42W02    | "Operation would cause a group cycle" on page 224   |
| 42W03    | "User %1' is not a user group" on page 306  |
| 42W04    | "Syntax error near '%1' %2" on page 264   |
| 42W05    | "Unknown function %1" on page 300   |
| 42W06    | "Invalid use of an aggregate function" on page 201  |
| 42W07    | "Invalid host variable" on page 189   |
| 42W08    | "Invalid expression near %1" on page 189  |
| 42W09    | "SETUSER not allowed in procedures, triggers, events or batches" on page 251  |
| 42W13    | "Invalid column number" on page 183   |

| SQLSTATE | Error message  |
|----------|--|
| 42W14    | "Variable %1' not found" on page 313   |
| 42W15    | "There is already a variable named %1" on page 287                                     |
| 42W16    | "Invalid option '%1' no PUBLIC setting exists" on page 193                             |
| 42W17    | "Invalid setting for option '%1" on page 196   |
| 42W18    | "User %1' has the row in %2' locked" on page 305                                       |
| 42W19    | "Not allowed while '%1' is using the database" on page 217                             |
| 42W20    | "CHECKPOINT statement requires a rollback log" on page 122                             |
| 42W21    | "Table in use" on page 270   |
| 42W22    | "Attempted two active database requests" on page 90                                    |
| 42W23    | "Procedure in use by %1" on page 232   |
| 42W24    | "Label '%1' not found" on page 208   |
| 42W25    | "Invalid absolute or relative offset in FETCH" on page 182                             |
| 42W26    | "Wrong number of variables in FETCH" on page 316                                       |
| 42W27    | "%1" on page 74  |
| 42W28    | "COMMIT/ROLLBACK not allowed within atomic operation"<br>on page 126                   |
| 42W29    | "Procedure or trigger calls have nested too deeply" on<br>page 233                     |
| 42W30    | "Update operation attempted on a read-only cursor" on page 302                         |
| 42W31    | "Update operation attempted on non-updatable query" on page 303                        |
| 42W32    | "Cannot modify column %1' in table %2" on page 108                                     |
| 42W33    | "Table '%1' not found" on page 269   |
| 42W34    | "User %1' already has membership in group %2" on page 304                              |
| 42W35    | "Update operation attempted on non-updatable remote query"<br>on page 303              |
| 42W36    | "FOR UPDATE has been incorrectly specified for a READ<br>ONLY cursor." on page 166     |
| 42W37    | "Cannot update column '%1' since it appears in the ORDER<br>BY clause." on page 117    |
| 42W38    | "Cannot update column '%1' since it does not appear in the SELECT clause." on page 118 |
| 42W40    | "Duplicate referencing column" on page 157   |

| SQLSTATE | Error message   |
|----------|---|
| 42W41    | "Duplicate insert column" on page 157   |
| 42W42    | "Parameter name missing in call to procedure %1" on<br>page 225                           |
| 42W43    | "Only PUBLIC settings are allowed for option %1" on page 223                              |
| 42W44    | "More columns are being dropped from table %1' than are defined" on page 212              |
| 42W45    | "Cannot set a temporary option for user %1" on page 114                                   |
| 42W46    | "Only the DBA can set the option <sup>3</sup> %1 <sup>*</sup> " on page 223               |
| 42W47    | "Parameter '%1' not found in procedure '%2" on page 225                                   |
| 42W48    | "Syntax error, cannot specify IQ specific options without specifying IQ PATH" on page 265 |
| 42W49    | "TRUNCATE TABLE statement cannot refer to a view" on page 294                             |
| 42W50    | "READTEXT or WRITETEXT statement cannot refer to a view" on page 234                      |
| 42W51    | "VALIDATE TABLE statement must refer to a base table" on page 311                         |
| 42W52    | "The option %1' can only be set as a temporary option" on page 281                        |
| 42W53    | "The option %1' cannot be set from within a procedure" on page 281                        |
| 42W54    | "Signature %1' does not match procedure parameters" on page 252                           |
| 42W55    | "User owns procedures in use" on page 308   |
| 42W56    | "User owns tables in use" on page 309   |
| 42W57    | "Java class %1' not found" on page 204  |
| 42W58    | "Jar '%1' not found" on page 204  |
| 42W59    | "The Select list for the derived table %1' has no expression to match %2" on page 283     |
| 42W60    | "Alias <sup>%</sup> 1' is not unique" on page 82  |
| 42W61    | "Definition for alias %1' must appear before its first reference"<br>on page 153          |
| 42W62    | "Row in table <sup>%</sup> 1' was modified or deleted in BEFORE<br>trigger" on page 244   |
| 42W63    | "Procedure <sup>%</sup> 1' is no longer valid" on page 230                                |

| SQLSTATE | Error message  |
|----------|--|
| 42W64    | "Trigger or foreign key for table '%1' is no longer valid" on page 293   |
| 42W65    | "Function or column reference to %1' in the ORDER BY clause is invalid" on page 168                              |
| 42W66    | "Trigger name %1' is ambiguous" on page 293  |
| 42W67    | "CREATE/DROP STATISTICS statement cannot refer to virtual tables" on page 136                                    |
| 42W68    | "Aggregated expression %1' contains multiple columns of<br>which one or more are outer references" on page 81    |
| 42W69    | "The aggregate expression '%1' must appear in either the select<br>list or a HAVING clause subquery" on page 273 |
| 42W70    | "Grouped query contains more than one distinct aggregate function" on page 170                                   |
| 42W71    | "Statement contains an illegal usage of the NUMBER(*) function" on page 256                                      |
| 42W73    | "There is no way to join to %1" on page 288  |
| 42W74    | "Index %1' can not be clustered" on page 175   |
| 42W79    | "Statement contains an illegal usage of the non-deterministic function %1" on page 256                           |
| 44000    | "WITH CHECK OPTION violated for insert/update on base table %1" on page 314                                      |
| 52002    | "Column <sup>%</sup> 1' found in more than one table need a correlation name" on page 124                        |
| 52003    | "Column %1' not found" on page 125   |
| 52004    | "Derived table %1' has no name for column %2" on page 154  |
| 52005    | "Column '%1' not found in table '%2" on page 126   |
| 52009    | "Primary key column %1' already defined" on page 229   |
| 52010    | "Item '%1' already exists" on page 203   |
| 52012    | "More than one table is identified as %1" on page 213  |
| 52W02    | "Correlation name %1' not found" on page 131   |
| 52W03    | "Cannot find index named '%1"" on page 105   |
| 52W04    | "Index name %1' not unique" on page 177  |
| 52W05    | "Table cannot have two primary keys" on page 270   |
| 52W06    | "Foreign key '%1' for table '%2' duplicates an existing foreign<br>key" on page 167                              |

| SQLSTATE | Error message   |
|----------|---|
| 52W07    | "Foreign key name %1' not found" on page 167  |
| 52W08    | "There is more than one way to join '%1' to '%2" on page 287                            |
| 52W09    | "Procedure '%1' not found" on page 231  |
| 52W10    | "Trigger %1' not found" on page 292   |
| 52W11    | "Trigger definition conflicts with existing triggers" on page 292                       |
| 52W12    | "Invalid REFERENCES clause in trigger definition" on page 195                           |
| 52W13    | "Dbspace '%1' not found" on page 151  |
| 52W14    | "Table <sup>3</sup> %1' is in an outer join cycle" on page 268                          |
| 52W15    | "Table <sup>3</sup> %1' requires a unique correlation name" on page 269                 |
| 52W16    | "User message %1 already exists" on page 307  |
| 52W17    | "User message %1 not found" on page 308   |
| 52W18    | "User-defined type '%1' not found" on page 310  |
| 52W19    | "Dbspace for table %1' not found" on page 152   |
| 52W20    | "Too many columns in table" on page 289   |
| 52W21    | "Data definition statements not allowed in procedures or triggers" on page 140          |
| 52W22    | "GRANT of column permission on view not allowed" on page 169                            |
| 52W23    | "Invalid expression in WHERE clause of Transact-SQL outer join" on page 188             |
| 52W24    | "Invalid join type used with Transact-SQL outer join" on page 191                       |
| 52W25    | "Invalid comparison" on page 183  |
| 52W40    | "Index name %1' is ambiguous" on page 176   |
| 52W41    | "too many temporary tables in connection" on page 290                                   |
| 52W42    | "Table name %1' is ambiguous" on page 271   |
| 53002    | "Wrong number of values for INSERT" on page 315   |
| 53003    | "Function or column reference to '%1' must also appear in a GROUP BY" on page 169       |
| 53005    | "Invalid ORDER BY specification" on page 194  |
| 53011    | "Number of columns defined for the view does not match<br>SELECT statement" on page 222 |

| SQLSTATE | Error message  |
|----------|--|
| 53018    | "Cannot convert %1 to a %2" on page 97   |
| 53019    | "Return type of void from procedure '%1' cannot be used in any expression" on page 241 |
| 53023    | "Subquery allowed only one select list item" on page 259                               |
| 53026    | "SELECT lists in UNION do not match in length" on page 248                             |
| 53030    | "Column %1' in foreign key has a different definition than<br>primary key" on page 124 |
| 53W01    | "ALTER clause conflict" on page 83   |
| 53W02    | "Cannot update an expression" on page 117  |
| 53W04    | "There is no way to join %1' to %2" on page 288  |
| 53W05    | "Cannot alter a column in an index" on page 95   |
| 53W06    | "Cannot delete a column referenced in a trigger definition" on page 100                |
| 53W07    | "Error number %1 for RAISERROR may not be less than 17000" on page 160                 |
| 53W08    | "Format string argument number %1 is invalid" on page 168                              |
| 53W09    | "Invalid data type for column in WRITETEXT or READTEXT" on page 185                    |
| 54003    | "Identifier %1' too long" on page 171  |
| 55008    | "Table %1' has no primary key" on page 266   |
| 55013    | "Table already has a primary key" on page 270  |
| 55W02    | "Table must be empty" on page 271  |
| 55W03    | "Cannot drop a user that owns tables in runtime system" on page 103                    |
| 55W04    | "Cannot drop a user that owns procedures in runtime server"<br>on page 103             |
| 55W05    | "Cannot drop a user that owns messages or data types" on page 102                      |
| 55W06    | "Cannot drop a user that owns objects involved in replication"<br>on page 102          |
| 55W07    | "db_init has not been called or the call to db_init failed" on page 151                |
| 55W08    | "Modifications not permitted for read-only database" on page 212                       |
| 55W09    | "Cannot commit or rollback while enlisted in a transaction" on page 96                 |

| SQLSTATE | Error message  |
|----------|--|
| 55W10    | "Cannot enlist in a transaction while already enlisted in a transaction" on page 104     |
| 55W11    | "Cannot enlist in a transaction with uncommitted data pending" on page 104               |
| 55W12    | "%1" on page 75  |
| 55W13    | "Strongly-encrypted database files are not supported in the runtime server" on page 258  |
| 56001    | "Table %1' has a foreign key with a referential action" on page 266                      |
| 57014    | "Statement interrupted by user" on page 257  |
| 5RW01    | "Publication '%1' not found" on page 233   |
| 5RW02    | "Table '%1' has publications" on page 267  |
| 5RW03    | "Subscription to %1' for %2' already exists" on page 260                                 |
| 5RW04    | "Subscription to %1' for %2' not found" on page 260                                      |
| 5RW05    | "User `%1' is already the publisher for this database" on page 305                       |
| 5RW06    | "User '%1' is not a remote user for this database" on page 306                           |
| 5RW07    | "Remote message type %1' not found" on page 235  |
| 5RW08    | "Passthrough statement inconsistent with current passthrough"<br>on page 227             |
| 5RW09    | "Remote statement failed" on page 237  |
| 5RW10    | "A consolidated user already exists" on page 79  |
| 5RW11    | "Synchronization message type %1' not found" on page 261                                 |
| 5RW12    | "Cannot find synchronization subscription with the name <sup>3</sup> %1""<br>on page 106 |
| 5RW13    | "Cannot subscribe to '%1" on page 115  |
| 5RW14    | "Cannot modify synchronization entry using ALTER<br>PUBLICATION" on page 109             |
| 5RW15    | "Cannot modify publication entry using ALTER<br>SYNCHRONIZATION" on page 109             |
| 5RW16    | "Cannot synchronize table '%1' since it does not have a primary key" on page 115         |
| 5RW17    | "Must include primary key for table %1' in the synchronization" on page 214              |
| 5RW18    | "Cannot create synchronization entry for table %1' with BLOB primary key" on page 99     |

| SQLSTATE | Error message  |
|----------|--|
| 5RW19    | "Cannot update primary key for table '%1' involved in a publication" on page 119           |
| 5RW21    | "Cannot register '%1' since another exclusive instance is<br>running" on page 110          |
| 5RW22    | "Cannot register another %1' as an exclusive application" on page 111                      |
| 5RW23    | "Cannot register connection because of invalid application cookie" on page 112             |
| 5RW24    | "Cannot deregister application because of invalid cookie" on page 101                      |
| 5RW25    | "Cannot deregister '%1' since active registered connection<br>exists" on page 100          |
| 5RW26    | "Current connection is already registered to %1' as %2" on page 137                        |
| 5RW27    | "Another connection has already registered as '%1" on page 89                              |
| 5RW28    | "Cannot register %1' since registration cookie exhausted" on page 111                      |
| 5RW29    | "Cannot register connection to %1' since automatic label<br>exhausted" on page 112         |
| 5RW30    | "Undefined synchronization template '%1" on page 299                                       |
| 5RW31    | "Synchronization site %1' is already defined" on page 264                                  |
| 5RW32    | "Synchronization option %1' contains semi-colon, equal sign<br>or curly brace" on page 262 |
| 5RW33    | "Synchronization option %1' not found" on page 262   |
| 5RW34    | "Synchronization option is too long" on page 263   |
| 5RW35    | "Table %1' is part of a synchronization definition" on page 268                            |
| 5RW36    | "Table '%1' is already included" on page 267   |
| 5RW37    | "Cannot find synchronization user with the name '%1" on page 106                           |
| 5RW39    | "Cannot find synchronization definition with the name <sup>%</sup> 1" on page 105          |
| 99999    | "User-defined exception signaled" on page 309  |
| WB001    | "Unknown backup operation" on page 300   |
| WB002    | "Database backup not started" on page 141  |
| WB003    | "Incomplete transactions prevent transaction log renaming" on                              |

| SQLSTATE | Error message  |  |  |
|----------|--|--|--|
|          | page 174   |  |  |
| WB004    | "Unable to delete database file" on page 296   |  |  |
| WB005    | "Transaction log was truncated" on page 291  |  |  |
| WB006    | "Contents of backup files are inconsistent" on page 130  |  |  |
| WB007    | "Backup file format is invalid" on page 92   |  |  |
| WB008    | "RESTORE unable to open file %1" on page 239   |  |  |
| WB009    | "RESTORE unable to write to file <sup>3</sup> %1" on page 240  |  |  |
| WB010    | "RESTORE unable to start database %1" on page 240  |  |  |
| WB011    | "Unable to open backup log %1" on page 297   |  |  |
| WC001    | "%1' is an unknown character set label" on page 75   |  |  |
| WC002    | "Cannot convert between requested character set %1' and database character set %2" on page 97        |  |  |
| WC003    | "An invalid multi-byte input character was encountered" on page 86                                   |  |  |
| WC004    | "An invalid multi-byte output character was encountered" on page 87                                  |  |  |
| WC005    | "An input character could not be converted to database character set" on page 84                     |  |  |
| WC006    | "An output character could not be converted to the application character set" on page 88             |  |  |
| WC007    | "Character conversion reporting is not available when the single byte converter is used" on page 121 |  |  |
| WC008    | "Cannot convert between requested character sets '%1' and '%2" on page 98                            |  |  |
| WE001    | "Event %1' not found" on page 163  |  |  |
| WE002    | "Event %1' already exists" on page 162   |  |  |
| WE003    | "Schedule %1' for event %2' not found" on page 247   |  |  |
| WE004    | "Schedule %1' for event %2' already exists" on page 247  |  |  |
| WE005    | "Invalid day of week or month <sup>3</sup> %1' for event <sup>3</sup> %2" on page 186                |  |  |
| WE006    | "Invalid time '%1' for event '%2" on page 199  |  |  |
| WE007    | "Invalid start date/time for event %1" on page 198   |  |  |
| WE008    | "System event type %1' not found" on page 265  |  |  |
| WE009    | "Event %1' in use" on page 162   |  |  |

| SQLSTATE | Error message   |  |
|----------|---|--|
| WI001    | "Attempt to read beyond end-of-file in a compressed database"<br>on page 90   |  |
| WI004    | "Internal rollback log corrupted" on page 182   |  |
| WI005    | "Unable to find in index '%1' for table '%2" on page 297  |  |
| WI006    | "(no message)" on page 72   |  |
| WI008    | "(no message)" on page 73   |  |
| WI009    | "Cannot serialize Java object with class '%1"" on page 113  |  |
| WI010    | "The optimizer was unable to construct a valid access plan" on page 280   |  |
| WJ001    | "Method %1' cannot be called at this time" on page 211  |  |
| WJ002    | "Parameter not registered as output parameter" on page 226  |  |
| WJ003    | "The specified transaction isolation is invalid" on page 285  |  |
| WJ004    | "The cursor name %1' already exists" on page 275  |  |
| WJ005    | "Input parameter index out of range" on page 178  |  |
| WJ006    | "Return value cannot be set" on page 242  |  |
| WJ007    | "JDBC feature '%1' not supported" on page 206   |  |
| WJ008    | "Could not change an opened prepared statement or callable statement" on page 132                                     |  |
| WJ009    | "An internal error occurred in a %1" on page 85   |  |
| WJ010    | "Invalid operation on a closed %1" on page 192  |  |
| WJ011    | "Cannot access instance member through a class" on page 94  |  |
| WJ012    | "Cannot update member fields qualified with "final" modifier"<br>on page 118  |  |
| WJ013    | "An internal error occurred in a %1" on page 85   |  |
| WJ014    | "Invalid operation on a closed %1" on page 193  |  |
| WJ015    | "JDBC SAStatement batch execute abandoned" on page 207  |  |
| WJ016    | "Seek absolute 0 was attempted on a JDBC SAResultSet" on page 248   |  |
| WJ017    | "Invalid JDBC resultset type" on page 191   |  |
| WJ018    | "Invalid JDBC resultset concurrency" on page 191  |  |
| WJ019    | "Cannot call the '%1' function on a JDBC resultset when it is<br>positioned on an insert row" on page 95              |  |
| WJ020    | "The JDBC resultset must be positioned on an insert row in<br>order to use the <sup>1</sup> %1' function" on page 278 |  |

| SQLSTATE | Error message  |  |  |
|----------|--|--|--|
| WJ021    | "Cannot uniquely identify column '%2' of table '%1' in the current JDBC resultset" on page 116 |  |  |
| WJ022    | "The database does not support the Java virtual machine" on page 276                           |  |  |
| WJ023    | "%1' is not a public Java class, and cannot be referenced from SQL" on page 77                 |  |  |
| WJ024    | "%1' is not a public Java reference, and cannot be referenced from SQL" on page 77             |  |  |
| WJ025    | "JDK '%1' is not a supported JDK" on page 207  |  |  |
| WJ026    | "The JDK version in %1' does not match %2" on page 279   |  |  |
| WJ027    | "Java SecurityManager class not found: %1" on page 205   |  |  |
| WJ028    | "Exception occurred while loading Java SecurityManager" on page 163                            |  |  |
| WJ029    | "The database needs to be restarted for this Java related command" on page 277                 |  |  |
| WL001    | "'%1' is not a known file format for loading or unloading tables" on page 76                   |  |  |
| WL002    | "Cannot access file <sup>3</sup> %1' %2" on page 93  |  |  |
| WL004    | "UNLOAD TABLE cannot be used to unload a view" on page 301                                     |  |  |
| WL005    | "Unable to enlist transaction; DTC may be down" on page 296                                    |  |  |
| WL006    | "Unable to reenlist transaction; DTC may be down" on page 298                                  |  |  |
| WO001    | "Unable to connect to server %1': %2" on page 295  |  |  |
| WO002    | "Unable to connect to server '%1': server definition is circular"<br>on page 295               |  |  |
| WO003    | "Remote server '%1' is currently configured as read only" on page 236                          |  |  |
| WO004    | "Remote server '%1' could not be found; Add the server using CREATE SERVER" on page 236        |  |  |
| WO005    | "Server '%1': %2" on page 249  |  |  |
| WO006    | "Backwards scrolling cursors are not supported for remote objects" on page 92                  |  |  |
| WO007    | "The remote table '%1' could not be found" on page 283   |  |  |
| WO008    | "Could not access column information for the table %1" on page 131                             |  |  |

| SQLSTATE | Error message   |  |  |
|----------|---|--|--|
| WO009    | "Not enough memory is allocated to the Java virtual machine<br>for remote access" on page 219                 |  |  |
| WO010    | "%1" on page 74   |  |  |
| WO011    | "The remote server does not support an auto-incrementing data type" on page 282                               |  |  |
| WO012    | "Remote server does not have the ability to support this statement" on page 237                               |  |  |
| WO013    | "External login for server '%1' could not be found" on page 164   |  |  |
| WO014    | "Server capability name '% 1' could not be found in the SYS.SYSCAPABILITYNAME table." on page 250             |  |  |
| WO015    | "The data type specified for column <sup>3</sup> %1' is not compatible with the actual data type" on page 276 |  |  |
| WO016    | "The column '%1' does not exist in the remote table" on<br>page 273   |  |  |
| WO017    | "The length specified for column %1' is different than the actual length" on page 279                         |  |  |
| WO018    | "Null attribute mismatch for column %1" on page 220   |  |  |
| WO019    | "Identity attribute mismatch for column '%1" on page 172  |  |  |
| WO020    | "The table specification %1' identifies more than one remote table" on page 286                               |  |  |
| WO021    | "Creating remote tables with computed columns is not supported" on page 137                                   |  |  |
| WO022    | "The data type of column '%1' is not supported" on page 275   |  |  |
| WO023    | "OMNI cannot handle expressions involving remote tables<br>inside stored procedures" on page 222              |  |  |
| WP000    | "Argument %1 of procedure %2' cannot be null" on page 89  |  |  |
| WP001    | "Procedure %1' terminated with unhandled exception %2" on page 231  |  |  |
| WP002    | "'%1' is not a valid class file" on page 78   |  |  |
| WP003    | "Could not decompress class '%1' from Jar." on page 133   |  |  |
| WP004    | "Cannot remove class %1': member of Jar" on page 113  |  |  |
| WP005    | "Invalid class byte code" on page 182   |  |  |
| WP006    | "Java virtual machine could not be started" on page 205   |  |  |
| WP007    | "Namespace heap exhausted at internal function: %1" on page 214   |  |  |

| SQLSTATE | Error message  |  |  |
|----------|--|--|--|
| WP008    | "Java VM heap exhausted at internal function: %1" on page 206                                    |  |  |
| WP009    | "Resource governor for %1' exceeded" on page 239   |  |  |
| WP010    | "Invalid jar file" on page 190   |  |  |
| WP011    | "Previous error lost prior to RESIGNAL" on page 228  |  |  |
| WP012    | "Insufficient cache to start Java virtual machine" on page 179                                   |  |  |
| WW001    | "The pattern is too long" on page 282  |  |  |
| WW002    | "Cannot stop the database server" on page 114  |  |  |
| WW003    | "Calling functions outside the database server is not supported"<br>on page 92                   |  |  |
| WW004    | "Mismatch between external function platform specifier and current operating system" on page 211 |  |  |
| WW005    | "Need a dynamic library name" on page 215  |  |  |
| WW006    | "Could not load dynamic library %1"" on page 135   |  |  |
| WW007    | "Could not find '%1' in dynamic library '%2" on page 134   |  |  |
| WW008    | "Could not allocate resources to call external function" on page 132                             |  |  |
| WW009    | "Expression has unsupported data type" on page 164   |  |  |
| WW010    | "Too many parameters to this external procedure call" on<br>page 289                             |  |  |
| WW011    | "A thread used internally could not be started" on page 81                                       |  |  |
| WW012    | "RAISERROR executed: %1" on page 234   |  |  |
| WW013    | "Class '%1' has no public field '%2" on page 122   |  |  |
| WW014    | "Invalid type for field reference" on page 200   |  |  |
| WW015    | "Field %1' of class %2' cannot be null" on page 166  |  |  |
| WW016    | "Index type specification of '%1' is invalid" on page 177  |  |  |
| WW017    | "An attempt to delete database %1' failed" on page 83  |  |  |
| WW018    | "Cannot deserialize Java object" on page 101   |  |  |
| WW019    | "Rollback occurred due to deadlock during prefetch" on page 242                                  |  |  |
| WW022    | "Cannot create an index on Java class <sup>3</sup> %1"" on page 98                               |  |  |
| WW023    | "Cannot insert or update computed column %1" on page 107   |  |  |

| SQLSTATE | Error message   |  |
|----------|---|--|
| WW024    | "The communications environment could not be created" on page 274       |  |
| WW025    | "An internal error was generated by the test harness" on page 86        |  |
| WW026    | "The external function call is incompatible" on page 277                |  |
| WW027    | "A conflict with the DBMLSync download phase was detected" on page 79   |  |
| WW028    | "At least one of the specified dbspaces was not calibrated." on page 90 |  |

## Error messages indexed by Sybase error code

Sybase error codes are a set of error codes for use by all Sybase products, including Adaptive Server Enterprise. For every Sybase error code returned by Adaptive Server Anywhere, there is a matching Adaptive Server Anywhere error code. In many cases Adaptive Server Anywhere error codes offer a finer level of granularity than their Sybase error code counterparts, thus some Sybase error codes in the following table are non-unique.

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 0                    | -631                                   | "RAISERROR executed: %1" on page 234  |
| 102                  | -171                                   | "Error opening cursor" on page 160  |
| 102                  | -199                                   | "INSERT/DELETE on cursor can modify only one table" on page 178                           |
| 102                  | -275                                   | "Triggers and procedures not supported in runtime server" on page 294                     |
| 102                  | -273                                   | "COMMIT/ROLLBACK not allowed within trigger actions" on page 127                          |
| 102                  | -131                                   | "Syntax error near '%1' %2" on page 264   |
| 102                  | -687                                   | "Syntax error, cannot specify IQ specific options without specifying IQ PATH" on page 265 |
| 102                  | -875                                   | "There is no way to join to %1" on page 288   |
| 102                  | -145                                   | "Foreign key name '% 1' not found" on page 167  |
| 102                  | -271                                   | "Trigger definition conflicts with existing triggers" on page 292                         |
| 102                  | -272                                   | "Invalid REFERENCES clause in trigger definition" on page 195                             |
| 102                  | -635                                   | "GRANT of column permission on view<br>not allowed" on page 169                           |
| 102                  | -151                                   | "Subquery allowed only one select list<br>item" on page 259                               |
| 102                  | -269                                   | "Cannot delete a column referenced in a trigger definition" on page 100                   |
| 103                  | -250                                   | "Identifier %1' too long" on page 171   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 104                  | -854                                   | "Function or column reference to %1' in<br>the ORDER BY clause is invalid" on<br>page 168 |
| 108                  | -152                                   | "Invalid ORDER BY specification" on page 194  |
| 133                  | -262                                   | "Label %1' not found" on page 208   |
| 134                  | -261                                   | "There is already a variable named <sup>'</sup> %1""<br>on page 287                       |
| 137                  | -260                                   | "Variable '%1' not found" on page 313   |
| 154                  | -623                                   | "Data definition statements not allowed in<br>procedures or triggers" on page 140         |
| 155                  | -200                                   | "Invalid option <sup>%</sup> 1' no PUBLIC setting<br>exists" on page 193                  |
| 174                  | -154                                   | "Wrong number of parameters to function %1" on page 315                                   |
| 176                  | -611                                   | "Transact-SQL feature not supported" on page 290  |
| 176                  | -148                                   | "Unknown function <sup>3</sup> %1"" on page 300   |
| 182                  | -159                                   | "Invalid column number" on page 183   |
| 201                  | -639                                   | "Parameter name missing in call to<br>procedure %1" on page 225                           |
| 201                  | -615                                   | "Parameter %1' not found in procedure<br>%2" on page 225                                  |
| 201                  | -737                                   | "Signature %1' does not match procedure<br>parameters" on page 252                        |
| 205                  | -153                                   | "SELECT lists in UNION do not match in length" on page 248                                |
| 207                  | -124                                   | "More columns are being dropped from table %1' than are defined" on page 212              |
| 207                  | -143                                   | "Column %1' not found" on page 125  |
| 208                  | -142                                   | "Correlation name '%1' not found" on<br>page 131  |
| 209                  | -144                                   | "Column %1' found in more than one<br>table need a correlation name" on<br>page 124       |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 209                  | -163                                   | "Derived table %1' has no name for column %2" on page 154                                   |
| 213                  | -207                                   | "Wrong number of values for INSERT" on page 315   |
| 217                  | -274                                   | "Procedure or trigger calls have nested too<br>deeply" on page 233                          |
| 220                  | -158                                   | "Value %1 out of range for destination" on<br>page 311                                      |
| 230                  | -191                                   | "Cannot modify column '%1' in table '%2""<br>on page 108                                    |
| 230                  | -190                                   | "Cannot update an expression" on page 117   |
| 233                  | -195                                   | "Column <sup>%</sup> 1' in table <sup>%</sup> 2' cannot be<br>NULL" on page 125             |
| 233                  | -733                                   | "Number of columns allowing NULLs<br>exceeds limit" on page 221                             |
| 257                  | -157                                   | "Cannot convert %1 to a %2" on page 97  |
| 257                  | -705                                   | "Return type of void from procedure %1'<br>cannot be used in any expression" on<br>page 241 |
| 262                  | -121                                   | "%1" on page 73   |
| 264                  | -637                                   | "Duplicate insert column" on page 157   |
| 285                  | -708                                   | "READTEXT or WRITETEXT statement<br>cannot refer to a view" on page 234                     |
| 301                  | -147                                   | "There is more than one way to join '%1'<br>to '%2" on page 287                             |
| 301                  | -680                                   | "Invalid expression in WHERE clause of<br>Transact-SQL outer join" on page 188              |
| 301                  | -146                                   | "There is no way to join %1' to %2" on page 288   |
| 305                  | -681                                   | "Invalid join type used with Transact-SQL outer join" on page 191                           |
| 311                  | -295                                   | "Cannot uniquely identify rows in cursor"<br>on page 116                                    |
| 314                  | -122                                   | "Operation would cause a group cycle" on page 224   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 315                  | -136                                   | "Table <sup>%</sup> 1' is in an outer join cycle" on<br>page 268                                  |
| 315                  | -137                                   | "Table <sup>%</sup> 1' requires a unique correlation<br>name" on page 269                         |
| 401                  | -134                                   | "Feature %1' not implemented" on page 165   |
| 401                  | -135                                   | "Language extension" on page 209  |
| 401                  | -156                                   | "Invalid expression near %1" on page 189  |
| 409                  | 109                                    | "Null value eliminated in aggregate function" on page 221   |
| 409                  | -90                                    | "Argument %1 of procedure '%2' cannot<br>be null" on page 89                                      |
| 504                  | -265                                   | "Procedure '%1' not found" on page 231  |
| 509                  | -140                                   | "User ID '%1' does not exist" on page 307   |
| 512                  | -186                                   | "Subquery cannot return more than one row" on page 259  |
| 518                  | 103                                    | "Invalid data conversion" on page 184   |
| 532                  | 104                                    | "Row has been updated since last time read" on page 243   |
| 532                  | 106                                    | "Value for column <sup>3</sup> %1' in table <sup>3</sup> %2' has changed" on page 312             |
| 538                  | -627                                   | "Disallowed language extension detected<br>in syntax near %1" on page 154                         |
| 546                  | -194                                   | "No primary key value for foreign key<br>%1' in table %2" on page 217                             |
| 547                  | -198                                   | "Primary key for row in table %1' is<br>referenced by foreign key %2' in table<br>%3" on page 229 |
| 547                  | -677                                   | "Table <sup>3</sup> %1' has a foreign key with a referential action" on page 266                  |
| 548                  | -196                                   | "Index <sup>3</sup> %1' for table <sup>3</sup> %2' would not be<br>unique" on page 176            |
| 548                  | -209                                   | "Invalid value for column %1' in table<br>%2" on page 203   |
| 549                  | -729                                   | "The specified foreign key (%1) can not be<br>enforced" on page 285                               |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 550                  | -632                                   | "WITH CHECK OPTION violated for<br>insert/update on base table %1" on<br>page 314                |
| 553                  | -264                                   | "Wrong number of variables in FETCH"<br>on page 316  |
| 554                  | -208                                   | "Row has changed since last read<br>operation cancelled" on page 244                             |
| 557                  | -853                                   | "Cursor not in a valid state" on page 139  |
| 557                  | -170                                   | "Cursor has not been declared" on page 138   |
| 558                  | -172                                   | "Cursor already open" on page 138  |
| 559                  | -180                                   | "Cursor not open" on page 139  |
| 560                  | 100                                    | "Row not found" on page 245  |
| 560                  | -197                                   | "No current row of cursor" on page 215   |
| 573                  | -738                                   | "Password must be at least %1 characters"<br>on page 227   |
| 590                  | 111                                    | "Statement cannot be executed" on page 255   |
| 601                  | -642                                   | "Invalid SQL descriptor name" on page 197  |
| 708                  | -80                                    | "Unable to start database server" on page 298  |
| 708                  | -86                                    | "Not enough memory to start" on page 219   |
| 708                  | -679                                   | "Not enough memory is allocated to the<br>Java virtual machine for remote access" on<br>page 219 |
| 840                  | -82                                    | "Unable to start specified database: %1"<br>on page 299  |
| 840                  | -87                                    | "Database name required to start server"<br>on page 144  |
| 911                  | -83                                    | "Specified database not found" on page 253   |
| 924                  | -816                                   | "Specified database file already in use." on page 252  |
| 927                  | -97                                    | "Database page size too big" on page 145   |
| 927                  | -644                                   | "Invalid database page size" on page 185   |
|                      |  |  |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 928                  | -645                                   | "Database creation failed: %1" on page 143   |
| 932                  | -311                                   | "Internal rollback log corrupted" on page 182  |
| 950                  | -76                                    | "Request denied no active databases" on<br>page 238  |
| 950                  | -74                                    | "The selected database is currently inactive" on page 284  |
| 1205                 | -306                                   | "Deadlock detected" on page 152  |
| 1205                 | -307                                   | "All threads are blocked" on page 82   |
| 1205                 | -684                                   | "Rollback occurred due to deadlock during prefetch" on page 242  |
| 1601                 | -102                                   | "Database server connection limit<br>exceeded" on page 147   |
| 1602                 | -85                                    | "Communication error" on page 127  |
| 1602                 | -88                                    | "Client/server communications protocol<br>version mismatch" on page 123  |
| 1702                 | -616                                   | "Too many columns in table" on page 289  |
| 1709                 | -849                                   | "Referential integrity actions other than<br>RESTRICT not allowed for temporary<br>tables" on page 235                                   |
| 1709                 | -850                                   | "Tables related by key constraint must<br>both be permanent or both be temporary<br>created with ON COMMIT PRESERVE<br>ROWS" on page 272 |
| 1709                 | -865                                   | "Key constraint between temporary tables<br>requires a primary key (not unique<br>constraint)" on page 208                               |
| 1719                 | -118                                   | "Table <sup>%</sup> 1' has no primary key" on page 266   |
| 1721                 | -113                                   | "Column <sup>%</sup> 1' in foreign key has a<br>different definition than primary key" on<br>page 124                                    |
| 1801                 | -77                                    | "Database name not unique" on page 144   |
| 1802                 | -138                                   | "Dbspace '%1' not found" on page 151   |
| 1909                 | -636                                   | "Duplicate referencing column" on page 157   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 1909                 | -119                                   | "Primary key column %1' already<br>defined" on page 229                           |
| 1909                 | -251                                   | "Foreign key %1' for table %2' duplicates<br>an existing foreign key" on page 167 |
| 1921                 | -111                                   | "Index name %1' not unique" on page 177   |
| 1921                 | -678                                   | "Index name %1' is ambiguous" on page 176   |
| 1923                 | -126                                   | "Table cannot have two primary keys" on page 270                                  |
| 1923                 | -112                                   | "Table already has a primary key" on page 270                                     |
| 2561                 | -106                                   | "Cannot open transaction log file %1"<br>on page 110                              |
| 2601                 | -193                                   | "Primary key for table '%1' is not unique"<br>on page 230                         |
| 2706                 | -141                                   | "Table '%1' not found" on page 269  |
| 2715                 | -613                                   | "User-defined type '%1' not found" on page 310                                    |
| 2727                 | -189                                   | "Unable to find in index '%1' for table<br>'%2"' on page 297                      |
| 2732                 | -296                                   | "Error number %1 for RAISERROR may<br>not be less than 17000" on page 160         |
| 2748                 | -612                                   | "User message %1 not found" on page 308   |
| 2749                 | -294                                   | "Format string argument number %1 is invalid" on page 168                         |
| 3013                 | -305                                   | "I/O error %1 transaction rolled back"<br>on page 171                             |
| 3013                 | -309                                   | "Memory error transaction rolled back"<br>on page 210                             |
| 3206                 | -240                                   | "Unknown backup operation" on page 300  |
| 3206                 | -241                                   | "Database backup not started" on page 141   |
| 3206                 | -242                                   | "Incomplete transactions prevent<br>transaction log renaming" on page 174         |
| 3451                 | -672                                   | "Database upgrade failed" on page 149   |
| 3451                 | -673                                   | "Database upgrade not possible" on page 149                                       |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 3618                 | -302                                   | "Terminated by user transaction rolled<br>back" on page 272   |
| 3618                 | -304                                   | "Disk full %1' transaction rolled back"<br>on page 155  |
| 3619                 | -107                                   | "Error writing to transaction log file" on page 161   |
| 3621                 | -299                                   | "Statement interrupted by user" on page 257   |
| 3702                 | -214                                   | "Table in use" on page 270  |
| 3702                 | -215                                   | "Procedure in use by '%1" on page 232   |
| 3702                 | -750                                   | "User owns procedures in use" on page 308   |
| 3702                 | -751                                   | "User owns tables in use" on page 309   |
| 3819                 | -160                                   | "Can only describe a SELECT statement"<br>on page 93  |
| 4001                 | -105                                   | "Database cannot be started %1" on page 142   |
| 4001                 | -84                                    | "Specified database is invalid" on page 253   |
| 4001                 | -72                                    | "No database file specified" on page 216  |
| 4002                 | -103                                   | "Invalid user ID or password" on page 202   |
| 4002                 | -103                                   | "Invalid user ID or password" on page 202   |
| 4002                 | -104                                   | "Invalid user ID or password on<br>preprocessed module" on page 202   |
| 4224                 | -108                                   | "Connection not found" on page 129  |
| 4224                 | -99                                    | "Connections to database have been<br>disabled" on page 130   |
| 4224                 | -308                                   | "Connection was terminated" on page 129   |
| 4406                 | -703                                   | "Cannot insert or update computed column<br>'%1"" on page 107   |
| 4409                 | -114                                   | "Number of columns defined for the view<br>does not match SELECT statement" on<br>page 222                        |
| 4412                 | -766                                   | "View references '%1', which is a<br>temporary object. Views can only refer to<br>permanent objects." on page 313 |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 4708                 | -702                                   | "TRUNCATE TABLE statement cannot<br>refer to a view" on page 294  |
| 4901                 | -116                                   | "Table must be empty" on page 271   |
| 4939                 | -127                                   | "Cannot alter a column in an index" on page 95  |
| 5006                 | -604                                   | "A dbspace has reached its maximum file size" on page 80  |
| 5006                 | -605                                   | "The server attempted to access a page<br>beyond the end of the maximum allowable<br>dbspace file size" on page 284 |
| 5703                 | 107                                    | "Language extension detected in syntax"<br>on page 210  |
| 5849                 | -201                                   | "Invalid setting for option %1" on page 196   |
| 5864                 | -81                                    | "Invalid database server command line" on page 186  |
| 5864                 | -735                                   | "Invalid parameter" on page 194   |
| 5864                 | -79                                    | "Invalid local database switch" on page 192   |
| 5864                 | -95                                    | "Parse error: %1" on page 226   |
| 5864                 | -754                                   | "Parse error: %1" on page 226   |
| 5878                 | -204                                   | "Only the DBA can set the option %1" on page 223  |
| 5878                 | -216                                   | "The option <sup>%</sup> 1' can only be set as a temporary option" on page 281                                      |
| 5878                 | -217                                   | "The option %1' cannot be set from within<br>a procedure" on page 281   |
| 6001                 | -109                                   | "There are still active database<br>connections" on page 286  |
| 6004                 | -75                                    | "Request to start/stop database denied" on page 238   |
| 6226                 | -183                                   | "Cannot find index named '%1"" on page 105  |
| 6259                 | -263                                   | "Invalid absolute or relative offset in<br>FETCH" on page 182   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 6267                 | -814                                   | "Cannot update column %1' since it<br>appears in the ORDER BY clause." on<br>page 117  |
| 6401                 | -220                                   | "Savepoint %1' not found" on page 246  |
| 7123                 | -608                                   | "Invalid TEXTPTR value used with<br>WRITETEXT or READTEXT" on<br>page 199              |
| 7139                 | -609                                   | "Invalid data type for column in<br>WRITETEXT or READTEXT" on<br>page 185              |
| 7201                 | -155                                   | "Invalid host variable" on page 189  |
| 7203                 | -89                                    | "Database server not running in multi-user<br>mode" on page 148                        |
| 7301                 | -192                                   | "Update operation attempted on non-<br>updatable query" on page 303                    |
| 7301                 | -813                                   | "FOR UPDATE has been incorrectly<br>specified for a READ ONLY cursor." on<br>page 166  |
| 7321                 | -149                                   | "Function or column reference to %1'<br>must also appear in a GROUP BY" on<br>page 169 |
| 7337                 | 101                                    | "Value truncated" on page 312  |
| 7338                 | -728                                   | "Update operation attempted on non-<br>updatable remote query" on page 303             |
| 7364                 | -139                                   | "More than one table is identified as %1""<br>on page 213                              |
| 7374                 | -676                                   | "The specified transaction isolation is invalid" on page 285                           |
| 7705                 | -630                                   | "Invalid escape sequence %1" on page 188   |
| 7706                 | -606                                   | "The pattern is too long" on page 282  |
| 7707                 | -629                                   | "Invalid escape character %1" on<br>page 187   |
| 7732                 | -633                                   | "Update operation attempted on a read-<br>only cursor" on page 302                     |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 7740                 | -815                                   | "Cannot update column %1' since it does<br>not appear in the SELECT clause." on<br>page 118            |
| 7950                 | -100                                   | "Database server not found" on page 148  |
| 7950                 | -96                                    | "Database server already running" on page 146  |
| 8201                 | -640                                   | "Invalid descriptor index" on page 187   |
| 8205                 | -641                                   | "Error in assignment" on page 159  |
| 8405                 | -210                                   | "User %1' has the row in %2' locked" on page 305   |
| 9119                 | -78                                    | "Dynamic memory exhausted" on page 158   |
| 9502                 | -638                                   | "Right truncation of string data" on page 242  |
| 9526                 | -187                                   | "Illegal cursor operation attempt" on page 172   |
| 9819                 | -268                                   | "Trigger '%1' not found" on page 292   |
| 10356                | -624                                   | "Expression has unsupported data type" on page 164   |
| 11205                | -698                                   | "The remote server does not support an auto-incrementing data type" on page 282                        |
| 11205                | -732                                   | "Creating remote tables with computed columns is not supported" on page 137                            |
| 11205                | -736                                   | "The data type of column <sup>3</sup> %1' is not<br>supported" on page 275                             |
| 11206                | -656                                   | "Unable to connect to server '%1': %2" on page 295   |
| 11207                | -667                                   | "Could not access column information for<br>the table '%1"" on page 131                                |
| 11208                | -722                                   | "The column '%1' does not exist in the remote table" on page 273                                       |
| 11209                | -721                                   | "The data type specified for column %1' is<br>not compatible with the actual data type"<br>on page 276 |
| 11210                | -723                                   | "The length specified for column %1' is<br>different than the actual length" on<br>page 279            |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 11211                | -724                                   | "Null attribute mismatch for column %1"<br>on page 220  |
| 11212                | -725                                   | "Identity attribute mismatch for column<br>%1" on page 172  |
| 11214                | -659                                   | "Remote server %1' could not be found;<br>Add the server using CREATE SERVER"<br>on page 236              |
| 11214                | -666                                   | "The remote table <sup>%</sup> 1 <sup>'</sup> could not be<br>found" on page 283                          |
| 11215                | -726                                   | "The table specification %1' identifies<br>more than one remote table" on page 286                        |
| 11221                | -712                                   | "External login for server '%1' could not<br>be found" on page 164  |
| 11227                | -706                                   | "Remote server does not have the ability to support this statement" on page 237                           |
| 11248                | -658                                   | "Remote server %1' is currently<br>configured as read only" on page 236                                   |
| 12006                | -110                                   | "Item '%1' already exists" on page 203  |
| 13075                | 102                                    | "Using temporary table" on page 310   |
| 13204                | -150                                   | "Invalid use of an aggregate function" on page 201  |
| 13588                | 130                                    | "A row could not be converted to the new schema format" on page 80  |
| 13589                | -895                                   | "Encryption error: %1" on page 158  |
| 13589                | -894                                   | "Plan can not be generated for this type of statement" on page 228  |
| 13592                | -891                                   | "Cannot convert between requested<br>character sets %1' and %2" on page 98                                |
| 13593                | -657                                   | "Unable to connect to server %1': server<br>definition is circular" on page 295                           |
| 13594                | -889                                   | "Statement contains an illegal usage of the<br>non-deterministic function <sup>3</sup> %1" on<br>page 256 |
| 13600                | 0                                      | "(no message)" on page 72   |
| 13601                | -690                                   | "Return value cannot be set" on page 242  |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13602                | -693                                   | "JDBC feature '%1' not supported" on page 206  |
| 13603                | -694                                   | "Could not change an opened prepared<br>statement or callable statement" on<br>page 132                          |
| 13604                | -695                                   | "An internal error occurred in a %1" on page 85  |
| 13605                | -696                                   | "Invalid operation on a closed <sup>3</sup> %1" on page 192  |
| 13606                | -699                                   | "Cannot update member fields qualified<br>with "final" modifier" on page 118                                     |
| 13607                | -701                                   | "Cannot access instance member through a class" on page 94   |
| 13608                | -713                                   | "An internal error occurred in a %1" on page 85  |
| 13609                | -714                                   | "Invalid operation on a closed %1" on page 193   |
| 13613                | 114                                    | "Character set translation to %1' cannot be<br>performed; %2' is used instead" on<br>page 121                    |
| 13614                | 115                                    | "Database server cannot convert data<br>from/to character set %1', conversion may<br>not be correct" on page 147 |
| 13615                | 116                                    | "Language <sup>%</sup> 1' is not supported, <sup>%</sup> 2' will<br>be used" on page 209                         |
| 13616                | 117                                    | "Unsupported character set %1' and<br>unsupported language %2'; language used<br>is %3' instead" on page 301     |
| 13617                | 118                                    | "Illegal user selectivity estimate specified"<br>on page 173   |
| 13618                | 105                                    | "Procedure has completed" on page 232  |
| 13619                | 200                                    | "Warning" on page 314  |
| 13620                | -98                                    | "Authentication violation" on page 91  |
| 13621                | -218                                   | "Authentication failed" on page 91   |
| 13622                | -101                                   | "Not connected to a database" on page 218  |
| 13623                | -125                                   | "ALTER clause conflict" on page 83   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 13624                | -610                                   | "User message %1 already exists" on page 307                                  |
| 13625                | -120                                   | "User %1' already has GRANT<br>permission" on page 304                        |
| 13626                | -123                                   | "User %1' is not a user group" on page 306                                    |
| 13627                | -312                                   | "User %1' already has membership in<br>group %2" on page 304                  |
| 13628                | -130                                   | "Invalid statement" on page 198   |
| 13629                | -132                                   | "SQL statement error" on page 254   |
| 13630                | -133                                   | "Invalid prepared statement type" on page 195                                 |
| 13631                | -707                                   | "Statement is not allowed in passthrough mode" on page 257                    |
| 13632                | -614                                   | "Cannot drop a user that owns messages or data types" on page 102             |
| 13633                | -731                                   | "Cannot drop a user that owns objects<br>involved in replication" on page 102 |
| 13634                | -161                                   | "Invalid type on DESCRIBE statement" on page 200                              |
| 13635                | -181                                   | "No indicator variable provided for NULL result" on page 216                  |
| 13636                | -182                                   | "Not enough fields allocated in SQLDA"<br>on page 218                         |
| 13637                | -185                                   | "SELECT returns more than one row" on page 249                                |
| 13638                | -188                                   | "Not enough values for host variables" on page 220                            |
| 13639                | -266                                   | "%1" on page 74   |
| 13640                | -267                                   | "COMMIT/ROLLBACK not allowed within atomic operation" on page 126             |
| 13641                | -270                                   | "Cannot drop a user that owns procedures<br>in runtime server" on page 103    |
| 13642                | -280                                   | "Publication '%1' not found" on page 233                                      |
| 13643                | -281                                   | "Table %1' has publications" on page 267                                      |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 13644                | -282                                   | "Subscription to %1' for %2' already<br>exists" on page 260                   |
| 13645                | -283                                   | "Subscription to %1' for %2' not found"<br>on page 260                        |
| 13646                | -284                                   | "User %1' is already the publisher for this database" on page 305             |
| 13647                | -285                                   | "User %1' is not a remote user for this database" on page 306                 |
| 13648                | -286                                   | "Remote message type %1' not found" on page 235                               |
| 13649                | -287                                   | "Passthrough statement inconsistent with<br>current passthrough" on page 227  |
| 13650                | -288                                   | "Remote statement failed" on page 237   |
| 13652                | -211                                   | "Not allowed while %1' is using the database" on page 217                     |
| 13653                | -212                                   | "CHECKPOINT statement requires a rollback log" on page 122                    |
| 13654                | -221                                   | "ROLLBACK TO SAVEPOINT not allowed" on page 243                               |
| 13655                | -222                                   | "Result set not allowed from within an atomic compound statement" on page 241 |
| 13656                | -213                                   | "Savepoints require a rollback log" on page 246                               |
| 13657                | -230                                   | "Sqlpp/dblib version mismatch" on page 255                                    |
| 13658                | -231                                   | "Client/database server version mismatch"<br>on page 123                      |
| 13660                | -243                                   | "Unable to delete database file" on page 296                                  |
| 13661                | -244                                   | "Transaction log was truncated" on page 291                                   |
| 13662                | -297                                   | "User-defined exception signaled" on page 309                                 |
| 13663                | -298                                   | "Attempted two active database requests" on page 90                           |
| 13664                | -300                                   | "Run time SQL error %1" on page 245   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13665                | -301                                   | "Internal database error %1 transaction<br>rolled back" on page 181                                    |
| 13666                | -310                                   | "Attempt to read beyond end-of-file in a compressed database" on page 90                               |
| 13669                | -601                                   | "%1' is not a known file format for loading or unloading tables" on page 76                            |
| 13670                | -602                                   | "Cannot access file <sup>3</sup> %1' %2" on page 93  |
| 13672                | -643                                   | "UNLOAD TABLE cannot be used to<br>unload a view" on page 301  |
| 13673                | -607                                   | "Cannot stop the database server" on page 114  |
| 13674                | -617                                   | "Calling functions outside the database<br>server is not supported" on page 92                         |
| 13675                | -618                                   | "Mismatch between external function<br>platform specifier and current operating<br>system" on page 211 |
| 13676                | -619                                   | "Need a dynamic library name" on page 215  |
| 13677                | -620                                   | "Could not load dynamic library %1" on page 135  |
| 13678                | -621                                   | "Could not find %1' in dynamic library<br>%2" on page 134  |
| 13679                | -622                                   | "Could not allocate resources to call<br>external function" on page 132                                |
| 13680                | -625                                   | "Too many parameters to this external procedure call" on page 289                                      |
| 13681                | -626                                   | "A thread used internally could not be started" on page 81   |
| 13682                | -634                                   | "Unterminated C string" on page 302  |
| 13683                | 110                                    | "Transaction log backup page only<br>partially full" on page 291                                       |
| 13685                | -202                                   | "Only PUBLIC settings are allowed for option '%1" on page 223  |
| 13686                | 112                                    | "More information required" on page 213  |
| 13687                | -203                                   | "Cannot set a temporary option for user<br>%1" on page 114   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13688                | 113                                    | "Database option %1' for user %2' has an<br>invalid setting" on page 145                           |
| 13689                | -205                                   | "Integrated logins are not permitted" on page 180  |
| 13690                | -206                                   | "Integrated logins are required, standard logins are not permitted" on page 181                    |
| 13691                | -245                                   | "Integrated login failed" on page 179  |
| 13692                | -503                                   | "(no message)" on page 72  |
| 13693                | -504                                   | "(no message)" on page 73  |
| 13694                | -246                                   | "Integrated logins are not supported for<br>this database" on page 180                             |
| 13695                | -247                                   | "The integrated login ID guest can only be<br>mapped to the guest database user ID" on<br>page 278 |
| 13696                | -248                                   | "Cannot map a login ID to the sys or<br>public user ID" on page 108                                |
| 13697                | -249                                   | "The login ID %1' is already mapped to<br>user ID %2" on page 280                                  |
| 13698                | -313                                   | "The login ID %1' has not been mapped to<br>any database user ID" on page 280                      |
| 13699                | -646                                   | "Could not load the store DLL "%1"" on page 136  |
| 13700                | -647                                   | "Could not execute store DLL (%1) entry<br>point." on page 134                                     |
| 13701                | -711                                   | "Incorrect store DLL (%1) version." on page 175  |
| 13702                | -648                                   | "Cannot create item (%1) in the specified dbspace." on page 99                                     |
| 13703                | -93                                    | "Class '%1' has no public field '%2"' on page 122  |
| 13704                | -650                                   | "Index type specification of %1' is<br>invalid" on page 177  |
| 13705                | -651                                   | "An attempt to delete database %1' failed"<br>on page 83   |
| 13706                | -654                                   | "The connection parameters file could not<br>be found" on page 274                                 |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13707                | -655                                   | "Error parsing connection parameter<br>string" on page 161   |
| 13708                | -664                                   | "Database is active" on page 143   |
| 13709                | -665                                   | "Database "%1" needs recovery" on page 141   |
| 13710                | -668                                   | "Cursor is restricted to FETCH NEXT operations" on page 138  |
| 13711                | -669                                   | "Method %1' cannot be called at this time" on page 211   |
| 13712                | -671                                   | "Parameter not registered as output<br>parameter" on page 226  |
| 13713                | -674                                   | "statement's size limit is invalid." on page 258   |
| 13714                | -683                                   | "The cursor name '%1' already exists" on page 275  |
| 13715                | -685                                   | "Resource governor for %1' exceeded" on page 239   |
| 13717                | -689                                   | "Input parameter index out of range" on page 178   |
| 13718                | -691                                   | "Could not load the backup/restore DLL<br>"%1"" on page 135  |
| 13719                | -692                                   | "Could not execute backup/restore DLL<br>(%1) entry point." on page 133                                    |
| 13720                | -697                                   | "Error during backup: %1" on page 159  |
| 13721                | -700                                   | "SQLDA fields inconsistent for a multi-<br>row SQLDA" on page 254  |
| 13722                | -709                                   | "Computed columns are not supported in<br>this database" on page 128                                       |
| 13723                | -761                                   | "Server capability name '% 1' could not be<br>found in the<br>SYS.SYSCAPABILITYNAME table." on<br>page 250 |
| 13724                | -715                                   | "Contents of backup files are inconsistent"<br>on page 130   |
| 13725                | -716                                   | "Backup file format is invalid" on page 92   |
| 13726                | -717                                   | "RESTORE unable to open file %1" on page 239   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13727                | -718                                   | "RESTORE unable to write to file <sup>3</sup> %1""<br>on page 240                |
| 13728                | -719                                   | "RESTORE unable to start database '%1""<br>on page 240                           |
| 13729                | -720                                   | "VALIDATE TABLE statement must refer to a base table" on page 311                |
| 13730                | -727                                   | "The optimizer was unable to construct a valid access plan" on page 280          |
| 13731                | -128                                   | "Cannot drop a user that owns tables in runtime system" on page 103              |
| 13732                | -660                                   | "Server '%1': %2" on page 249  |
| 13733                | -661                                   | "Backwards scrolling cursors are not<br>supported for remote objects" on page 92 |
| 13734                | -682                                   | "%1" on page 74  |
| 13735                | -91                                    | "Procedure %1' terminated with<br>unhandled exception %2" on page 231            |
| 13736                | -92                                    | "%1' is not a valid class file" on page 78                                       |
| 13737                | -730                                   | "Invalid jar file" on page 190   |
| 13738                | -94                                    | "Invalid type for field reference" on page 200                                   |
| 13739                | -164                                   | "Namespace heap exhausted at internal function: %1" on page 214                  |
| 13740                | -165                                   | "Java VM heap exhausted at internal function: %1" on page 206                    |
| 13741                | -649                                   | "Field %1' of class %2' cannot be null" on page 166                              |
| 13742                | -652                                   | "Could not decompress class '%1' from Jar." on page 133                          |
| 13743                | -653                                   | "Cannot remove class %1': member of Jar" on page 113                             |
| 13744                | -662                                   | "Cannot serialize Java object with class<br>%1"" on page 113                     |
| 13745                | -663                                   | "Cannot deserialize Java object" on page 101                                     |
| 13746                | -670                                   | "Invalid class byte code" on page 182  |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13747                | -675                                   | "Java virtual machine could not be started"<br>on page 205   |
| 13748                | -704                                   | "Cannot create an index on Java class<br>%1" on page 98  |
| 13749                | -710                                   | "Invalid comparison" on page 183   |
| 13750                | -734                                   | "Cannot update or delete an all-NULL row<br>from table <sup>3</sup> %1" on page 119                          |
| 13751                | 120                                    | "'%1' is an unknown option" on page 76   |
| 13752                | -739                                   | "db_init has not been called or the call to<br>db_init failed" on page 151                                   |
| 13753                | -740                                   | "The communications environment could<br>not be created" on page 274   |
| 13754                | -741                                   | " <sup>3</sup> %1' is not a write file for <sup>3</sup> %2" on<br>page 78                                    |
| 13755                | -742                                   | "JDBC SAStatement batch execute<br>abandoned" on page 207  |
| 13756                | -743                                   | "Seek absolute 0 was attempted on a JDBC SAResultSet" on page 248  |
| 13757                | -744                                   | "Invalid IQ database command line option<br>or parameter value: %1" on page 190                              |
| 13758                | -745                                   | "Cannot initialize IQ memory manager:<br>%1" on page 107   |
| 13759                | -746                                   | "Cannot allocate System V resources" on page 94  |
| 13760                | -747                                   | "Invalid JDBC resultset type" on page 191  |
| 13761                | -748                                   | "Invalid JDBC resultset concurrency" on page 191   |
| 13762                | -749                                   | "Feature not available with UltraLite" on page 165   |
| 13763                | -752                                   | "Cannot call the '% 1' function on a JDBC<br>resultset when it is positioned on an insert<br>row" on page 95 |
| 13764                | -753                                   | "The JDBC resultset must be positioned on<br>an insert row in order to use the %1'<br>function" on page 278  |
| 13765                | -755                                   | "You cannot synchronize with<br>uncommitted transactions" on page 316  |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13766                | -756                                   | "Cannot uniquely identify column '%2' of<br>table '%1' in the current JDBC resultset"<br>on page 116 |
| 13767                | -289                                   | "A consolidated user already exists" on page 79  |
| 13768                | -757                                   | "Modifications not permitted for read-only database" on page 212                                     |
| 13769                | -758                                   | "The database does not support the Java virtual machine" on page 276                                 |
| 13770                | -759                                   | "SQLDA data type invalid" on page 254  |
| 13771                | -760                                   | "Invalid SQL identifier" on page 197   |
| 13772                | -762                                   | "%1' is not a public Java class, and cannot<br>be referenced from SQL" on page 77                    |
| 13773                | -763                                   | "%1' is not a public Java reference, and<br>cannot be referenced from SQL" on<br>page 77             |
| 13774                | -764                                   | "Server not found and unable to autostart"<br>on page 250  |
| 13775                | -765                                   | "Synchronization message type <sup>3</sup> %1' not<br>found" on page 261                             |
| 13776                | 119                                    | "Unable to open backup log %1"" on page 297  |
| 13777                | -767                                   | "Cannot find synchronization subscription<br>with the name %1" on page 106                           |
| 13778                | -768                                   | "Cannot subscribe to %1" on page 115   |
| 13779                | -769                                   | "Cannot modify synchronization entry<br>using ALTER PUBLICATION" on<br>page 109                      |
| 13780                | -770                                   | "Cannot modify publication entry using<br>ALTER SYNCHRONIZATION" on<br>page 109                      |
| 13781                | -771                                   | "Event %1' not found" on page 163  |
| 13782                | -772                                   | "Event %1' already exists" on page 162   |
| 13783                | -773                                   | "Schedule %1' for event %2' not found"<br>on page 247  |
| 13784                | -774                                   | "Schedule %1' for event %2' already<br>exists" on page 247   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13787                | -777                                   | "Cannot synchronize table %1' since it<br>does not have a primary key" on page 115         |
| 13788                | -778                                   | "Must include primary key for table %1'<br>in the synchronization" on page 214             |
| 13789                | -779                                   | "Cannot create synchronization entry for<br>table %1' with BLOB primary key" on<br>page 99 |
| 13790                | -780                                   | "Cannot update primary key for table %1'<br>involved in a publication" on page 119         |
| 13792                | -782                                   | "Cannot register %1' since another<br>exclusive instance is running" on page 110           |
| 13793                | -783                                   | "Cannot register another %1' as an<br>exclusive application" on page 111                   |
| 13794                | -784                                   | "Cannot register connection because of<br>invalid application cookie" on page 112          |
| 13795                | -785                                   | "Cannot deregister application because of<br>invalid cookie" on page 101                   |
| 13796                | -786                                   | "Cannot deregister %1' since active<br>registered connection exists" on page 100           |
| 13797                | -787                                   | "Current connection is already registered<br>to %1' as %2" on page 137                     |
| 13798                | -788                                   | "Another connection has already registered<br>as %1" on page 89                            |
| 13799                | -789                                   | "Cannot register '%1' since registration<br>cookie exhausted" on page 111                  |
| 13800                | -790                                   | "Cannot register connection to %1' since<br>automatic label exhausted" on page 112         |
| 13801                | -791                                   | "Invalid day of week or month '%1' for<br>event '%2" on page 186                           |
| 13802                | -792                                   | "Invalid time %1' for event %2" on page 199  |
| 13803                | -793                                   | "Invalid start date/time for event %1" on page 198   |
| 13804                | -794                                   | "Synchronization server failed to commit<br>the upload" on page 263                        |
| 13805                | -795                                   | "Undefined synchronization template<br>%1" on page 299                                     |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 13806                | -796                                   | "Synchronization site %1' is already defined" on page 264                                     |
| 13807                | -797                                   | "Synchronization option %1' contains<br>semi-colon, equal sign or curly brace" on<br>page 262 |
| 13809                | -799                                   | "DTC transactions are not supported on this platform" on page 157                             |
| 13810                | -800                                   | "Cannot commit or rollback while enlisted<br>in a transaction" on page 96                     |
| 13811                | -801                                   | "Cannot enlist in a transaction while<br>already enlisted in a transaction" on<br>page 104    |
| 13812                | -802                                   | "Cannot enlist in a transaction with<br>uncommitted data pending" on page 104                 |
| 13813                | -803                                   | "Unable to enlist transaction; DTC may be down" on page 296                                   |
| 13814                | -804                                   | "Unable to reenlist transaction; DTC may<br>be down" on page 298                              |
| 13815                | -805                                   | "Synchronization option '%1' not found"<br>on page 262  |
| 13816                | -806                                   | "System event type %1' not found" on page 265   |
| 13817                | -807                                   | "Host variables may not be used within a batch" on page 170                                   |
| 13818                | -808                                   | "An internal error was generated by the test harness" on page 86                              |
| 13819                | -809                                   | "Synchronization option is too long" on page 263  |
| 13820                | -810                                   | "Java class %1' not found" on page 204  |
| 13821                | -811                                   | "Jar '%1' not found" on page 204  |
| 13822                | -812                                   | "The Select list for the derived table %1'<br>has no expression to match %2" on<br>page 283   |
| 13823                | -817                                   | "too many temporary tables in connection"<br>on page 290                                      |
| 13824                | -818                                   | "The external function call is<br>incompatible" on page 277                                   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 13825                | -819                                   | "Table '%1' is part of a synchronization definition" on page 268                                    |
| 13826                | -820                                   | "Invalid scroll position %1" on page 196  |
| 13827                | -821                                   | "Dbspace for table %1' not found" on page 152   |
| 13828                | -822                                   | "Table '% 1' is already included" on page 267   |
| 13829                | -823                                   | "OMNI cannot handle expressions<br>involving remote tables inside stored<br>procedures" on page 222 |
| 13830                | -824                                   | "Illegal reference to correlation name %1'<br>in ON condition" on page 173                          |
| 13831                | -825                                   | "Previous error lost prior to RESIGNAL"<br>on page 228  |
| 13832                | -826                                   | "Database upgrade not possible;<br>RowGenerator table not owned by user<br>dbo" on page 150         |
| 13833                | -827                                   | "Database upgrade not possible; user<br>tables have table ids in system table range"<br>on page 150 |
| 13834                | -828                                   | "A conflict with the DBMLSync download phase was detected" on page 79                               |
| 13835                | -829                                   | "Certicom handshake failure" on page 120  |
| 13836                | -830                                   | "Alias %1' is not unique" on page 82  |
| 13837                | -831                                   | "Definition for alias %1' must appear<br>before its first reference" on page 153                    |
| 13838                | -832                                   | "Connection error: %1" on page 128  |
| 13839                | -833                                   | "Row in table '%1' was modified or<br>deleted in BEFORE trigger" on page 244                        |
| 13840                | -834                                   | "Column <sup>3</sup> %1' not found in table <sup>3</sup> %2" on page 126                            |
| 13841                | -835                                   | "Event %1' in use" on page 162  |
| 13842                | -836                                   | "Procedure %1' is no longer valid" on page 230  |
| 13843                | -837                                   | "Trigger or foreign key for table %1' is no<br>longer valid" on page 293                            |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message   |
|----------------------|--|---|
| 13844                | -838                                   | "Certicom initialization on server failed"<br>on page 120   |
| 13845                | -839                                   | "Download failed because of conflicts with existing rows." on page 156  |
| 13847                | -841                                   | "The JDK version in %1' does not match<br>%2" on page 279   |
| 13848                | -842                                   | "JDK '%1' is not a supported JDK" on page 207   |
| 13849                | -843                                   | "Cannot find synchronization user with the name %1" on page 106   |
| 13850                | -844                                   | "Cannot find synchronization definition<br>with the name %1" on page 105  |
| 13851                | -845                                   | "Owner <sup>3</sup> %1' used in a qualified column<br>reference does not match correlation name<br><sup>3</sup> %2" on page 224 |
| 13852                | -846                                   | "Set clause for column %1' used<br>incorrectly" on page 251   |
| 13853                | -847                                   | "Java SecurityManager class not found:<br>%1" on page 205   |
| 13854                | -848                                   | "Exception occurred while loading Java<br>SecurityManager" on page 163  |
| 13855                | -851                                   | "Decryption error: %1" on page 153  |
| 13856                | -852                                   | "Table name '%1' is ambiguous" on page 271  |
| 13857                | 121                                    | "Cursor option values changed" on page 140  |
| 13858                | -855                                   | "Trigger name %1' is ambiguous" on page 293   |
| 13859                | -856                                   | "Invalid sqllen field in SQLDA" on page 197   |
| 13860                | -857                                   | "Synchronization failed due to an<br>unspecified error on the server." on<br>page 261   |
| 13861                | -858                                   | "CREATE/DROP STATISTICS statement cannot refer to virtual tables" on page 136   |
| 13863                | -859                                   | "%1" on page 75   |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13864                | -860                                   | "At least one of the specified dbspaces was not calibrated." on page 90  |
| 13865                | -861                                   | "Aggregated expression %1' contains<br>multiple columns of which one or more<br>are outer references" on page 81   |
| 13866                | -862                                   | "The aggregate expression %1' must<br>appear in either the select list or a<br>HAVING clause subquery" on page 273 |
| 13867                | -863                                   | "Grouped query contains more than one distinct aggregate function" on page 170                                     |
| 13868                | -303                                   | "Disk write failure '%1' transaction<br>rolled back" on page 155   |
| 13869                | -864                                   | "Statement contains an illegal usage of the<br>NUMBER(*) function" on page 256                                     |
| 13871                | -867                                   | "Cannot change synchronization<br>user_name when status of the last upload<br>is unknown." on page 96              |
| 13872                | -868                                   | "%1' is an unknown character set label"<br>on page 75  |
| 13873                | -869                                   | "Database server cannot convert data<br>from/to character set %1" on page 146                                      |
| 13874                | -870                                   | "Cannot convert between requested<br>character set %1' and database character<br>set %2" on page 97                |
| 13875                | -871                                   | "The database needs to be restarted for this<br>Java related command" on page 277                                  |
| 13876                | -686                                   | "Insufficient cache to start Java virtual machine" on page 179   |
| 13879                | -688                                   | "Strongly-encrypted database files are not<br>supported in the runtime server" on<br>page 258                      |
| 13882                | -876                                   | "Client out of memory" on page 123   |
| 13884                | 123                                    | "Database created without any schema" on page 142  |
| 13886                | 124                                    | "Invalid data conversion: NULL was<br>inserted for column <sup>3</sup> %1' on line %2." on<br>page 184             |

| Sybase<br>error code | Adaptive Server<br>Anywhere<br>SQLCODE | Error message  |
|----------------------|--|--|
| 13888                | -877                                   | "SETUSER not allowed in procedures,<br>triggers, events or batches" on page 251  |
| 13889                | -878                                   | "Index '%1' can not be clustered" on page 175  |
| 13890                | -879                                   | "An invalid multi-byte input character was encountered" on page 86   |
| 13891                | -880                                   | "An invalid multi-byte output character was encountered" on page 87  |
| 13892                | 125                                    | "An invalid multi-byte input character was encountered" on page 86   |
| 13893                | 126                                    | "An invalid multi-byte output character was encountered" on page 87  |
| 13894                | -881                                   | "An input character could not be converted to database character set" on page 84   |
| 13895                | -882                                   | "An output character could not be<br>converted to the application character set"<br>on page 88                                       |
| 13896                | 127                                    | "An input character could not be converted<br>to database character set and simple<br>substitution took place" on page 84            |
| 13897                | 128                                    | "An output character could not be<br>converted to the application character set<br>and simple substitution took place" on<br>page 88 |
| 13898                | -883                                   | "Character conversion reporting is not<br>available when the single byte converter is<br>used" on page 121                           |
| 16846                | -840                                   | "Incorrect or missing encryption key" on page 174  |
| 36007                | -628                                   | "Division by zero" on page 156   |

### Alphabetic list of error messages

This section provides a full listing of error messages and descriptions.

Errors with an ODBC state marked "handled by ODBC driver" are not returned to ODBC applications, as the ODBC driver carries out the required actions.

#### (no message)

| Item              | Value        |
|-------------------|--------------|
| SQLCODE           | 0            |
| Constant          | SQLE_NOERROR |
| SQLSTATE          | 00000        |
| Sybase error code | 13600        |
| ODBC 2 State      | 00000        |
| ODBC 3 State      | 00000        |
|                   |              |

**Probable cause** This code indicates that there was no error or warning.

#### (no message)

| ltem              | Value          |
|-------------------|----------------|
| SQLCODE           | -503           |
| Constant          | SQLE_PREEMPTED |
| SQLSTATE          | WI006          |
| Sybase error code | 13692          |
| ODBC 2 State      | ERROR          |
| ODBC 3 State      | ERROR          |

#### (no message)

\_

| ltem              | Value      |
|-------------------|------------|
| SQLCODE           | -504       |
| Constant          | SQLE_RETRY |
| SQLSTATE          | WI008      |
| Sybase error code | 13693      |
| ODBC 2 State      | ERROR      |
| ODBC 3 State      | ERROR      |

%1

| SQLCODE           | -121   |
|-------------------|--|
| -                 |  |
| Constant          | SQLE_PERMISSION_DENIED                         |
| SQLSTATE          | 42501  |
| Sybase error code | 262  |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Description of the type of permission lacking. |

**Probable cause** You do not have the required permission to do the specified action. The message specifies the actual permission required and the object being acted upon.

#### %1

| ltem              | Value           |
|-------------------|-----------------|
| SQLCODE           | -266            |
| Constant          | SQLE_OLD_DBINIT |
| SQLSTATE          | 42W27           |
| Sybase error code | 13639           |
| ODBC 2 State      | ERROR           |
| ODBC 3 State      | ERROR           |

# Probable causeThe database is missing some system table definitions required for this<br/>statement. These system table definitions are normally created when a<br/>database is initialized. The database should be unloaded and reloaded into a<br/>database that has been initialized with a newer version of Adaptive Server<br/>Anywhere, or use DBUPGRADE to upgrade the database to the most recent<br/>version.

%1

| ltem              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -682                              |
| Constant          | SQLE_OMNI_DEBUG                   |
| SQLSTATE          | WO010                             |
| Sybase error code | 13734                             |
| ODBC 2 State      | ОК                                |
| ODBC 3 State      | ОК                                |
| Parameter 1       | The debug message for the console |
|                   |                                   |

### **Probable cause** This message is used for displaying component integration services debug messages on the console.

#### %1

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -859   |
| Constant          | SQLE_JAVA_IN_USE                                 |
| SQLSTATE          | 55W12  |
| Sybase error code | 13863  |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Description of the reason Java cannot be removed |
|                   |  |

**Probable cause** Java cannot be removed because it is being used by a table or procedure, or because an external jar or class is installed.

#### '%1' is an unknown character set label

| ltem              | Value                |
|-------------------|----------------------|
| SQLCODE           | -868                 |
| Constant          | SQLE_UNKNOWN_CHARSET |
| SQLSTATE          | WC001                |
| Sybase error code | 13872                |
| ODBC 2 State      | ERROR                |
| ODBC 3 State      | ERROR                |

### **Probable cause** The specified character set label is not recognized, so conversion from/to that character set is not possible.

#### '%1' is an unknown option

| ltem              | Value               |
|-------------------|---------------------|
| SQLCODE           | 120                 |
| Constant          | SQLE_UNKNOWN_OPTION |
| SQLSTATE          | 01W17               |
| Sybase error code | 13751               |
| ODBC 2 State      | 01000               |
| ODBC 3 State      | 01000               |
|                   |                     |

#### **Probable cause** You attempted to set the value of an option which is not known to the server. You should make sure that you did intend to set the specified option as opposed to having made a typographical error.

#### '%1' is not a known file format for loading or unloading tables

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -601                         |
| Constant          | SQLE_UNSUPPORTED_LOAD_FORMAT |
| SQLSTATE          | WL001                        |
| Sybase error code | 13669                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
| Parameter 1       | The specified format         |
|                   |                              |

### Probable cause An unsupported file format was specified for LOAD TABLE or UNLOAD TABLE.

#### '%1' is not a public Java class, and cannot be referenced from SQL

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -762                       |
| Constant          | SQLE_NON_PUBLIC_JAVA_CLASS |
| SQLSTATE          | WJ023                      |
| Sybase error code | 13772                      |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |
| Parameter 1       | Java class name            |
|                   |                            |

**Probable cause** Only public Java classes installed into the database are accessible from SQL.

# '%1' is not a public Java reference, and cannot be referenced from SQL

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -763                  |
| Constant          | SQLE_UNKNOWN_JAVA_REF |
| SQLSTATE          | WJ024                 |
| Sybase error code | 13773                 |
| ODBC 2 State      | ERROR                 |
| ODBC 3 State      | ERROR                 |
| Parameter 1       | a dotted expression   |

Probable cause The dotted expression is neither a public Java class nor a Java variable.

#### '%1' is not a valid class file

| Item     |           | Value                         |
|----------|-----------|-------------------------------|
| SQLCOI   | DE        | -92                           |
| Constant |           | SQLE_BAD_CLASS_FILE           |
| SQLSTA   | TE        | WP002                         |
| Sybase e | rror code | 13736                         |
| ODBC 2   | State     | ERROR                         |
| ODBC 3   | State     | ERROR                         |
| Paramete | r 1       | The name of the invalid file. |
|          |           |                               |

**Probable cause** 

A file passed to the INSTALL JAVA statement was not a valid Java class file.

#### '%1' is not a write file for '%2'

| ltem              | Value                |
|-------------------|----------------------|
| SQLCODE           | -741                 |
| Constant          | SQLE_NOTA_WRITE_FILE |
| SQLSTATE          | 08W50                |
| Sybase error code | 13754                |
| ODBC 2 State      | ERROR                |
| ODBC 3 State      | ERROR                |
|                   |                      |

**Probable cause** The write file specified in the ALTER WRITEFILE statement is not a writefile for the database specified.

#### A conflict with the DBMLSync download phase was detected

| Value                            |
|----------------------------------|
| -828                             |
| SQLE_RECORDING_CONFLICT_DETECTED |
| WW027                            |
| 13834                            |
| ERROR                            |
| ERROR                            |
|                                  |

Probable cause DBMLSync uses this error to detect download phase conflicts with rows modified by other connections.

#### A consolidated user already exists

\_

| ltem              | Value                                     |
|-------------------|---|
| SQLCODE           | -289                                      |
| Constant          | SQLE_CONSOLIDATED_USER_ALREADY_EXIST<br>S |
| SQLSTATE          | 5RW10                                     |
| Sybase error code | 13767                                     |
| ODBC 2 State      | S0002                                     |
| ODBC 3 State      | 42802                                     |

**Probable cause** You attempted to grant consolidated permissions when your database already has a consolidated user.

#### A dbspace has reached its maximum file size

| Value             |
|-------------------|
| -604              |
| SQLE_DBSPACE_FULL |
| 04W07             |
| 5006              |
| ERROR             |
| ERROR             |
|                   |

### **Probable cause** A dbspace has grown to its maximum number of disk pages, which is usually limited by the maximum operating system file size. This is a fatal error.

#### A row could not be converted to the new schema format

| ltem              | Value                                      |
|-------------------|--|
| SQLCODE           | 130  |
| Constant          | SQLE_ROW_DROPPED_DURING_SCHEMA_UPGR<br>ADE |
| SQLSTATE          | 01W21                                      |
| Sybase error code | 13588                                      |
| ODBC 2 State      | ОК   |
| ODBC 3 State      | ОК   |

**Probable cause** A row which was valid in the old schema is no longer valid. This could be because a column domain changed and the old value can not be cast to the new domain. Rows are also dropped if a uniqueness or foreign key constraint cannot be satisfied.

| Value                     |
|---------------------------|
| -626                      |
| SQLE_THREAD_START_FAILURE |
| WW011                     |
| 13681                     |
| ERROR                     |
| ERROR                     |
| -<br>-<br>1               |

#### A thread used internally could not be started

### Probable causeThis is a Windows95 specific error. An operating system thread could not be<br/>started that is required to execute external functions.

# Aggregated expression '%1' contains multiple columns of which one or more are outer references

| ltem              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -861                                |
| Constant          | SQLE_MULTIPLE_AGGREGATE_COLUMNS     |
| SQLSTATE          | 42W68                               |
| Sybase error code | 13865                               |
| ODBC 2 State      | 37000                               |
| ODBC 3 State      | 42000                               |
| Parameter 1       | The aggregated expression in error. |
|                   |                                     |

# **Probable cause** A subselect within the nested query contains an aggregate function whose parameters include an outer reference. In such cases, the outer reference must be the only column referenced in the expression.

#### Alias '%1' is not unique

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -830                  |
| Constant          | SQLE_ALIAS_NOT_UNIQUE |
| SQLSTATE          | 42W60                 |
| Sybase error code | 13836                 |
| ODBC 2 State      | 37000                 |
| ODBC 3 State      | ERROR                 |
| Parameter 1       | Name of the alias.    |

**Probable cause** The same alias is used more than once in a SELECT list.

#### All threads are blocked

|                | ltem  | Value                |
|----------------|---|----------------------|
|                | SQLCODE   | -307                 |
|                | Constant  | SQLE_THREAD_DEADLOCK |
|                | SQLSTATE  | 40W06                |
|                | Sybase error code   | 1205                 |
|                | ODBC 2 State  | 40001                |
|                | ODBC 3 State  | 40001                |
| Probable cause | You attempted to read or write a row and it is locked by another user. Also, all other threads (see database option THREAD_COUNT) are blocked |                      |
|                | waiting for a lock to be released. This is a deadlock situation and your transaction has been chosen as the one to rollback.                  |                      |

#### ALTER clause conflict

\_

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -125                       |
| Constant          | SQLE_ALTER_CLAUSE_CONFLICT |
| SQLSTATE          | 53W01                      |
| Sybase error code | 13623                      |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |
|                   |                            |

**Probable cause** A primary key clause, foreign key clause, or a uniqueness clause must be the only clause of an ALTER TABLE statement.

#### An attempt to delete database '%1' failed

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -651                      |
| Constant          | SQLE_DROP_DATABASE_FAILED |
| SQLSTATE          | WW017                     |
| Sybase error code | 13705                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
|                   |                           |

**Probable cause** Your attempt to delete a database file failed. You may have attempted to delete a running database. Some parts of the database may have been deleted before failure.

### An input character could not be converted to database character set

| ltem              | Value                                |  |
|-------------------|--------------------------------------|--|
| SQLCODE           | -881                                 |  |
| Constant          | SQLE_INPUT_SIMPLE_SUBSTITUTION_ERROR |  |
| SQLSTATE          | WC005                                |  |
| Sybase error code | 13894                                |  |
| ODBC 2 State      | ERROR                                |  |
| ODBC 3 State      | ERROR                                |  |

# Probable cause While the server was performing character set conversion on an input string, some character(s) could not be represented in the database character set and need to be substituted. The operation was aborted. See document on the On\_Charset\_conversion\_failure option.

# An input character could not be converted to database character set and simple substitution took place

| lt | tem              | Value                                      |
|----|------------------|--|
| S  | QLCODE           | 127  |
| С  | Constant         | SQLE_INPUT_SIMPLE_SUBSTITUTION_WARNIN<br>G |
| S  | QLSTATE          | 01WC3                                      |
| S  | ybase error code | 13896                                      |
| O  | DDBC 2 State     | 01000                                      |
| O  | DDBC 3 State     | 01000                                      |
|    |                  |  |

Probable causeWhile the server was performing character set conversion on an input string,<br/>some character(s) could not be represented in the database character set.<br/>Those character(s) were substituted. See document on the<br/>On\_Charset\_conversion\_failure option.

#### An internal error occurred in a '%1'

| Item              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -695                              |
| Constant          | SQLE_JDBC_OBJ_INTERNAL_ERR        |
| SQLSTATE          | WJ009                             |
| Sybase error code | 13604                             |
| ODBC 2 State      | ERROR                             |
| ODBC 3 State      | ERROR                             |
| Parameter 1       | Java class of the object in error |
|                   |                                   |

**Probable cause** This is an internal JDBC object error. If it can be reproduced, it should be reported to iAnywhere Solutions.

#### An internal error occurred in a '%1'

| Value                             |
|-----------------------------------|
| -713                              |
| SQLE_JNAT_OBJ_INTERNAL_ERR        |
| WJ013                             |
| 13608                             |
| ERROR                             |
| ERROR                             |
| Java class of the object in error |
|                                   |

### **Probable cause** This is an internal native Java object error. If it can be reproduced, it should be reported to iAnywhere Solutions.

#### An internal error was generated by the test harness

| ltem              | Value             |
|-------------------|-------------------|
| SQLCODE           | -808              |
| Constant          | SQLE_TEST_HARNESS |
| SQLSTATE          | WW025             |
| Sybase error code | 13818             |
| ODBC 2 State      | ERROR             |
| ODBC 3 State      | ERROR             |

**Probable cause** An internal error was generated by the test harness.

#### An invalid multi-byte input character was encountered

| Item              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -879                               |
| Constant          | SQLE_INPUT_ILLEGAL_MULTIBYTE_ERROR |
| SQLSTATE          | WC003                              |
| Sybase error code | 13890                              |
| ODBC 2 State      | ERROR                              |
| ODBC 3 State      | ERROR                              |
|                   |                                    |

**Probable cause** While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The operation is aborted.

#### An invalid multi-byte input character was encountered

| Item              | Value                                |
|-------------------|--------------------------------------|
| SQLCODE           | 125                                  |
| Constant          | SQLE_INPUT_ILLEGAL_MULTIBYTE_WARNING |
| SQLSTATE          | 01WC1                                |
| Sybase error code | 13892                                |
| ODBC 2 State      | 01000                                |
| ODBC 3 State      | 01000                                |

Probable cause While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See document on the On\_Charset\_conversion\_failure option.

#### An invalid multi-byte output character was encountered

| Item              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -880                                |
| Constant          | SQLE_OUTPUT_ILLEGAL_MULTIBYTE_ERROR |
| SQLSTATE          | WC004                               |
| Sybase error code | 13891                               |
| ODBC 2 State      | ERROR                               |
| ODBC 3 State      | ERROR                               |
|                   |                                     |

Probable cause While the server was performing character set conversion on an output string, an invalid multi-byte character was encountered. The operation is aborted. See document on the On\_Charset\_conversion\_failure option.

#### An invalid multi-byte output character was encountered

| ltem              | Value                                     |
|-------------------|---|
| SQLCODE           | 126                                       |
| Constant          | SQLE_OUTPUT_ILLEGAL_MULTIBYTE_WARNIN<br>G |
| SQLSTATE          | 01WC2                                     |
| Sybase error code | 13893                                     |
| ODBC 2 State      | 01000                                     |
| ODBC 3 State      | 01000                                     |

Probable cause While the server was performing character set conversion on an output string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See document on the On\_Charset\_conversion\_failure option.

# An output character could not be converted to the application character set

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -882                                  |
| Constant          | SQLE_OUTPUT_SIMPLE_SUBSTITUTION_ERROR |
| SQLSTATE          | WC006                                 |
| Sybase error code | 13895                                 |
| ODBC 2 State      | ERROR                                 |
| ODBC 3 State      | ERROR                                 |
|                   |                                       |

Probable causeWhile the server was performing character set conversion on an output<br/>string, some character(s) could not be represented in the application character<br/>set and need to be substituted. The operation was aborted. See document on<br/>the On\_Charset\_conversion\_report option.

#### An output character could not be converted to the application character set and simple substitution took place

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | 128   |
| Constant          | SQLE_OUTPUT_SIMPLE_SUBSTITUTION_WARNI<br>NG |
| SQLSTATE          | 01WC4                                       |
| Sybase error code | 13897                                       |
| ODBC 2 State      | 01000                                       |
| ODBC 3 State      | 01000                                       |

Probable cause While the server was performing character set conversion on an output string, some character(s) could not be represented in the application character set. Those character(s) were substituted. See document on the On\_Charset\_conversion\_failure option.

#### Another connection has already registered as '%1'

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -788                           |
| Constant          | SQLE_NOT_UNIQUE_CONN_REG_LABEL |
| SQLSTATE          | 5RW27                          |
| Sybase error code | 13798                          |
| ODBC 2 State      | 42000                          |
| ODBC 3 State      | 42S02                          |
| Parameter 1       | Registered connection label    |
|                   |                                |

**Probable cause** You attempted to register a connection with a label already in use for the same application.

#### Argument %1 of procedure '%2' cannot be null

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -90  |
| Constant          | SQLE_ARGUMENT_CANNOT_BE_NULL                                       |
| SQLSTATE          | WP000  |
| Sybase error code | 409  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
| Parameter 1       | The argument number which cannot be null.                          |
| Parameter 2       | The name of the procedure which cannot receive the null parameter. |

# **Probable cause** You passed a null value to a procedure expecting a scalar argument. For example, a Java procedure which has an 'int' argument cannot receive a null value.

#### At least one of the specified dbspaces was not calibrated.

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -860                        |
| Constant          | SQLE_DBSPACE_NOT_CALIBRATED |
| SQLSTATE          | WW028                       |
| Sybase error code | 13864                       |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |

Probable cause You attempted to calibrate a dbspace that was not open or was too small.

#### Attempt to read beyond end-of-file in a compressed database

| ltem              | Value           |
|-------------------|-----------------|
| SQLCODE           | -310            |
| Constant          | SQLE_BEYOND_EOF |
| SQLSTATE          | WI001           |
| Sybase error code | 13666           |
| ODBC 2 State      | ERROR           |
| ODBC 3 State      | ERROR           |
|                   |                 |

**Probable cause** While reading the database file, an attempt was made to read beyond the end of the file. This is a fatal internal error.

#### Attempted two active database requests

| Item              | Value               |
|-------------------|---------------------|
| SQLCODE           | -298                |
| Constant          | SQLE_DOUBLE_REQUEST |
| SQLSTATE          | 42W22               |
| Sybase error code | 13663               |
| ODBC 2 State      | ERROR               |
| ODBC 3 State      | ERROR               |

Probable cause In Embedded SQL, you attempted to submit a database request while you have another request in process. This often occurs in Windows when processing the WM\_PAINT message causes a database request, and you get a second WM PAINT before the database request has completed.

#### Authentication failed

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -218                       |
| Constant          | SQLE_AUTHENTICATION_FAILED |
| SQLSTATE          | 08W48                      |
| Sybase error code | 13621                      |
| ODBC 2 State      | 08001                      |
| ODBC 3 State      | 08001                      |
|                   |                            |

**Probable cause** You set the database\_authentication or connection\_authentication option incorrectly.

#### Authentication violation

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -98                           |
| Constant          | SQLE_AUTHENTICATION_VIOLATION |
| SQLSTATE          | 08W21                         |
| Sybase error code | 13620                         |
| ODBC 2 State      | 08001                         |
| ODBC 3 State      | 08001                         |
|                   |                               |

### **Probable cause** You attempted to connect to a server which has been authenticated for exclusive use with a specific application.

#### Backup file format is invalid

| Item              | Value  |  |
|-------------------|--|--|
| SQLCODE           | -716   |  |
| Constant          | SQLE_RESTORE_INVALID_FORMAT  |  |
| SQLSTATE          | WB007  |  |
| Sybase error code | 13725  |  |
| ODBC 2 State      | ERROR  |  |
| ODBC 3 State      | ERROR  |  |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |  |

**Probable cause** The format of an archive file to be used during a RESTORE is invalid.

#### Backwards scrolling cursors are not supported for remote objects

| _ | ltem              | Value                      |
|---|-------------------|----------------------------|
|   | SQLCODE           | -661                       |
|   | Constant          | SQLE_OMNI_BACKWARDS_CURSOR |
|   | SQLSTATE          | WO006                      |
|   | Sybase error code | 13733                      |
|   | ODBC 2 State      | ERROR                      |
|   | ODBC 3 State      | ERROR                      |
|   |                   |                            |

Probable causeBackwards scrolling cursors are not supported for remote objects. Change<br/>the client program to use forward scrolling cursors only.

#### Calling functions outside the database server is not supported

| Item              | Value                             |  |
|-------------------|-----------------------------------|--|
| SQLCODE           | -617                              |  |
| Constant          | SQLE_EXTERNAL_CALLS_NOT_SUPPORTED |  |
| SQLSTATE          | WW003                             |  |
| Sybase error code | 13674                             |  |
| ODBC 2 State      | ERROR                             |  |
| ODBC 3 State      | ERROR                             |  |

# **Probable cause** You attempted to call a stored procedure that, in turn, calls a function in a dynamically loaded module. The operating system on which this stored procedure was called does not support such an action.

#### Can only describe a SELECT statement

| Value                   |  |
|-------------------------|--|
| -160                    |  |
| SQLE_DESCRIBE_NONSELECT |  |
| 07005                   |  |
| 3819                    |  |
| ОК                      |  |
| ОК                      |  |
|                         |  |

### **Probable cause** In the C language interface, you attempted to describe the select list of a statement other than a SELECT statement.

#### Cannot access file '%1' -- %2

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -602                    |
| Constant          | SQLE_CANNOT_ACCESS_FILE |
| SQLSTATE          | WL002                   |
| Sybase error code | 13670                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
| Parameter 1       | The filename            |
| Parameter 2       | The cause of the error  |
|                   | •                       |

# **Probable cause** A file cannot be accessed. For example, a file referenced by LOAD TABLE does not exist or cannot be read. The message will contain the reason for the error.

#### Cannot access instance member through a class

| Item              | Value                              |  |
|-------------------|------------------------------------|--|
| SQLCODE           | -701                               |  |
| Constant          | SQLE_CANNOT_ACCESS_INSTANCE_MEMBER |  |
| SQLSTATE          | WJ011                              |  |
| Sybase error code | 13607                              |  |
| ODBC 2 State      | ERROR                              |  |
| ODBC 3 State      | ERROR                              |  |
|                   |                                    |  |

Probable cause Non-static fields or methods must be accessed through an object instance.

#### **Cannot allocate System V resources**

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -746                     |
| Constant          | SQLE_IQ_SYSTEM_V_FAILURE |
| SQLSTATE          | 08W53                    |
| Sybase error code | 13759                    |
| ODBC 2 State      | 08001                    |
| ODBC 3 State      | 08001                    |
|                   |                          |

 Probable cause
 IQ was unable to allocate System V resources. Please delete unused System V semaphores and shared memory segments or increase OS configuration values for these resources.

| ltem              | Value                |  |
|-------------------|----------------------|--|
| SQLCODE           | -127                 |  |
| Constant          | SQLE_COLUMN_IN_INDEX |  |
| SQLSTATE          | 53W05                |  |
| Sybase error code | 4939                 |  |
| ODBC 2 State      | ERROR                |  |
| ODBC 3 State      | ERROR                |  |
|                   |                      |  |

#### Cannot alter a column in an index

**Probable cause** You may have attempted to delete or modify the definition of a column that is part of a primary or foreign key. You may have attempted to delete a column that has an index on it. In this case, DROP the index or key, perform the ALTER statement, and then add the index or key again.

# Cannot call the '%1' function on a JDBC resultset when it is positioned on an insert row

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | -752  |
| Constant          | SQLE_JDBC_INVALID_OPER_ON_INSERT_ROW        |
| SQLSTATE          | WJ019                                       |
| Sybase error code | 13763                                       |
| ODBC 2 State      | ERROR                                       |
| ODBC 3 State      | ERROR                                       |
| Parameter 1       | Name of the resultset function being called |
| ·                 |   |

### **Probable cause** Some resultset function such as 'updateRow' and 'deleteRow' are invalid when the cursor of the resultset is positioned at the insert row.

# Cannot change synchronization user\_name when status of the last upload is unknown.

| Value                        |  |
|------------------------------|--|
| -867                         |  |
| SQLE_CANNOT_CHANGE_USER_NAME |  |
| 0AW13                        |  |
| 13871                        |  |
| 37000                        |  |
| 42000                        |  |
|                              |  |

**Probable cause** The synchronization server uses the user\_name to track synchronizations. If the status of the previous upload is unknown then you must resolve this condition before changing the user.

#### Cannot commit or rollback while enlisted in a transaction

| Item              | Value   |  |
|-------------------|---|--|
| SQLCODE           | -800  |  |
| Constant          | SQLE_CANNOT_COMMIT_OR_ROLLBACK_WHIL<br>E_ENLISTED |  |
| SQLSTATE          | 55W09   |  |
| Sybase error code | 13810   |  |
| ODBC 2 State      | ERROR   |  |
| ODBC 3 State      | ERROR   |  |

**Probable cause** You tried to explicitly commit or rollback on a connection that is enlisted in a transaction. You must use the Commit/Abort protocol of the transaction instead.

#### Cannot convert %1 to a %2

| ltem              | Value                                    |
|-------------------|--|
| SQLCODE           | -157                                     |
| Constant          | SQLE_CONVERSION_ERROR                    |
| SQLSTATE          | 53018                                    |
| Sybase error code | 257                                      |
| ODBC 2 State      | 07006                                    |
| ODBC 3 State      | 07006                                    |
| Parameter 1       | The value that could not be converted.   |
| Parameter 2       | The name of the type for the conversion. |

Probable causeYou supplied to or fetched from the database an invalid value. For example,<br/>the value 12X might have been supplied where a number was required.

# Cannot convert between requested character set '%1' and database character set '%2'

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -870                           |
| Constant          | SQLE_FAILED_TO_START_CONVERTER |
| SQLSTATE          | WC002                          |
| Sybase error code | 13874                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
|                   |                                |

# **Probable cause** The server is unable to convert between the connection character set that was specified and the database character set. This could happen when the conversion tables are not properly installed.

#### Cannot convert between requested character sets '%1' and '%2'

| Item              | Value                                      |
|-------------------|--|
| SQLCODE           | -891                                       |
| Constant          | SQLE_FAILED_TO_START_CONVERTER_2_CHAR SETS |
| SQLSTATE          | WC008                                      |
| Sybase error code | 13592                                      |
| ODBC 2 State      | ERROR                                      |
| ODBC 3 State      | ERROR                                      |

### **Probable cause** The server is unable to convert between the two specified character sets. This could happen when the conversion tables are not properly installed.

#### Cannot create an index on Java class '%1'

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -704                            |
| Constant          | SQLE_CANNOT_INDEX_ON_JAVA_CLASS |
| SQLSTATE          | WW022                           |
| Sybase error code | 13748                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |
| Parameter 1       | The name of the class.          |
|                   |                                 |

### **Probable cause** An operation requiring an index was attempted in which at attempt was made to create an index on a Java class type.

#### Cannot create item (%1) in the specified dbspace.

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -648                            |
| Constant          | SQLE_INVALID_DBSPACE_FOR_CREATE |
| SQLSTATE          | 08W36                           |
| Sybase error code | 13702                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |
|                   | •                               |

| Probable cause | The dbspace specified is invalid. For example, an index must be created in a |
|----------------|--|
|                | dbspace of the same type as the underlying table.                            |

# Cannot create synchronization entry for table '%1' with BLOB primary key

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -779                       |
| Constant          | SQLE_BLOB_IN_SYNC_TABLE_PK |
| SQLSTATE          | 5RW18                      |
| Sybase error code | 13789                      |
| ODBC 2 State      | 42000                      |
| ODBC 3 State      | 42S02                      |
| Parameter 1       | Name of the table          |
|                   |                            |

# Probable cause You attempted to create a synchronization on a table with BLOB primary key.

#### Cannot delete a column referenced in a trigger definition

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -269                   |
| Constant          | SQLE_COLUMN_IN_TRIGGER |
| SQLSTATE          | 53W06                  |
| Sybase error code | 102                    |
| ODBC 2 State      | ERROR                  |
| ODBC 3 State      | ERROR                  |
|                   | •                      |

#### Probable cause

You attempted to delete a column referenced in a trigger definition. DROP the trigger before performing the ALTER statement.

#### Cannot deregister '%1' since active registered connection exists

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -786                    |
| Constant          | SQLE_DEREG_APP_IN_USE   |
| SQLSTATE          | 5RW25                   |
| Sybase error code | 13796                   |
| ODBC 2 State      | 42000                   |
| ODBC 3 State      | 42802                   |
| Parameter 1       | Name of the application |
|                   |                         |

### **Probable cause** You attempted to deregister an application while there are still active connection registered to that application.

#### Cannot deregister application because of invalid cookie

| ltem                              | Value                    |
|-----------------------------------|--------------------------|
| SQLCODE                           | -785                     |
| Constant                          | SQLE_DEREG_APP_NOT_FOUND |
| SQLSTATE                          | 5RW24                    |
| Sybase error code                 | 13795                    |
| ODBC 2 State                      | 42000                    |
| ODBC 3 State                      | 42S02                    |
| Sybase error code<br>ODBC 2 State | 13795<br>42000           |

## **Probable cause** Application has not been registered successfully or it has already been deregistered previously.

#### Cannot deserialize Java object

\_

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -663                            |
| Constant          | SQLE_JAVA_DESERIALIZATION_ERROR |
| SQLSTATE          | WW018                           |
| Sybase error code | 13745                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |
|                   |                                 |

**Probable cause** The persisted Java object cannot be read from the database column. Possibly, the class of the object has been removed or modified.

#### Cannot drop a user that owns messages or data types

| ltem              | Value                                    |
|-------------------|--|
| SQLCODE           | -614                                     |
| Constant          | SQLE_USER_OWNS_MESSAGES_OR_DATATYPE<br>S |
| SQLSTATE          | 55W05                                    |
| Sybase error code | 13632                                    |
| ODBC 2 State      | 42000                                    |
| ODBC 3 State      | 42000                                    |
|                   |  |

#### Probable cause

You attempted to drop a user who is the creator of a message or user-defined data type. The message or user-defined data type must be dropped first.

#### Cannot drop a user that owns objects involved in replication

| _ | Item              | Value                             |
|---|-------------------|-----------------------------------|
| _ | SQLCODE           | -731                              |
|   | Constant          | SQLE_USER_OWNS_REPLICATED_OBJECTS |
|   | SQLSTATE          | 55W06                             |
|   | Sybase error code | 13633                             |
|   | ODBC 2 State      | 42000                             |
|   | ODBC 3 State      | 42000                             |
|   |                   |                                   |

**Probable cause** You attempted to drop a user who is the creator of a database object involved in replication. For example, the user may own a table that is part of a publication.

#### Cannot drop a user that owns procedures in runtime server

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -270                      |
| Constant          | SQLE_USER_OWNS_PROCEDURES |
| SQLSTATE          | 55W04                     |
| Sybase error code | 13641                     |
| ODBC 2 State      | 42000                     |
| ODBC 3 State      | 42000                     |

# **Probable cause** You attempted to drop a user who owns procedures while using the runtime server. This operation would result in dropping procedures, and the runtime server cannot drop procedures. Use the full server.

#### Cannot drop a user that owns tables in runtime system

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -128                  |
| Constant          | SQLE_USER_OWNS_TABLES |
| SQLSTATE          | 55W03                 |
| Sybase error code | 13731                 |
| ODBC 2 State      | 42000                 |
| ODBC 3 State      | 42000                 |

**Probable cause** You attempted to drop a user who owns tables, while running the runtime server. This operation would result in dropping tables, which is not permitted in the runtime server. Use the full server.

# Cannot enlist in a transaction while already enlisted in a transaction

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -801  |
| Constant          | SQLE_CANNOT_ENLIST_WHILE_ALREADY_ENLI<br>STED |
| SQLSTATE          | 55W10   |
| Sybase error code | 13811   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |

### **Probable cause** You tried to enlist a second transaction on a connection that is already enlisted in a transaction.

#### Cannot enlist in a transaction with uncommitted data pending

|   | ltem              | Value  |
|---|-------------------|--|
| - | SQLCODE           | -802   |
|   | Constant          | SQLE_CANNOT_ENLIST_WITH_UNCOMMITTED_<br>DATA |
|   | SQLSTATE          | 55W11  |
|   | Sybase error code | 13812  |
|   | ODBC 2 State      | ERROR  |
|   | ODBC 3 State      | ERROR  |
|   |                   | -  |

### **Probable cause** You tried to enlist a transaction on a connection that has pending uncommitted data.

#### Cannot find index named '%1'

| ltem              | Value                                   |
|-------------------|---|
| SQLCODE           | -183                                    |
| Constant          | SQLE_INDEX_NOT_FOUND                    |
| SQLSTATE          | 52W03                                   |
| Sybase error code | 6226                                    |
| ODBC 2 State      | S0012                                   |
| ODBC 3 State      | 42812                                   |
| Parameter 1       | Name of the index that cannot be found. |
|                   |   |

Probable causeYou attempted to drop an index that does not exist. Check for spelling errors.<br/>Check whether the index name must be qualified by a user ID.

#### Cannot find synchronization definition with the name '%1'

| ltem              | Value                                  |
|-------------------|--|
| SQLCODE           | -844                                   |
| Constant          | SQLE_SYNC_DEFINITION_NOT_FOUND         |
| SQLSTATE          | 5RW39                                  |
| Sybase error code | 13850                                  |
| ODBC 2 State      | S0002                                  |
| ODBC 3 State      | 42S02                                  |
| Parameter 1       | Name of the synchronization definition |
|                   |  |

### **Probable cause** You misspelled the name of a synchronization definition or you did not qualify it correctly with a user name.

#### Cannot find synchronization subscription with the name '%1'

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -767                           |
| Constant          | SQLE_SYNCHRONIZATION_NOT_FOUND |
| SQLSTATE          | 5RW12                          |
| Sybase error code | 13777                          |
| ODBC 2 State      | S0002                          |
| ODBC 3 State      | 42S02                          |
| Parameter 1       | Name of the subscription       |
|                   |                                |

**Probable cause** 

You misspelled the name of a synchronization subscription or you did not qualify it correctly with a user name.

#### Cannot find synchronization user with the name '%1'

|   | Item              | Value  |
|---|-------------------|--|
|   | SQLCODE           | -843   |
|   | Constant          | SQLE_SYNC_SITE_NOT_FOUND                               |
|   | SQLSTATE          | 5RW37  |
|   | Sybase error code | 13849  |
|   | ODBC 2 State      | S0002  |
|   | ODBC 3 State      | 42S02  |
|   | Parameter 1       | Name of the synchronization user                       |
|   |                   |  |
| <b>Probable cause</b> You misspelled the name of a synchronization site or your |                   | me of a synchronization site or you did not qualify it |

**De cause** You misspelled the name of a synchronization site or you did not qualify it correctly with a user name.

\_

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -745                          |
| Constant          | SQLE_IQ_MEMORY_MANAGER_FAILED |
| SQLSTATE          | 08W52                         |
| Sybase error code | 13758                         |
| ODBC 2 State      | 08001                         |
| ODBC 3 State      | 08001                         |
|                   |                               |

#### Cannot insert or update computed column '%1'

| Item              | Value                                    |
|-------------------|--|
| SQLCODE           | -703                                     |
| Constant          | SQLE_COMPUTED_COLUMN_WRITE_ATTEMPTE<br>D |
| SQLSTATE          | WW023                                    |
| Sybase error code | 4406                                     |
| ODBC 2 State      | ERROR                                    |
| ODBC 3 State      | ERROR                                    |
| Parameter 1       | The name of the column.                  |

# **Probable cause** Computed column values cannot be modified explicitly. Their value is determined implicitly from the computed expression value.

#### Cannot map a login ID to the sys or public user ID

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -248                         |
| Constant          | SQLE_INTEGRATED_LOGON_SYSMAP |
| SQLSTATE          | 28W07                        |
| Sybase error code | 13696                        |
| ODBC 2 State      | 28000                        |
| ODBC 3 State      | 28000                        |
|                   | ·                            |

Probable cause You attempted to map a login ID to either sys or public

#### Cannot modify column '%1' in table '%2'

|                | Item   | Value                                      |
|----------------|--|--|
|                | SQLCODE  | -191                                       |
|                | Constant   | SQLE_CANNOT_MODIFY                         |
|                | SQLSTATE   | 42W32                                      |
|                | Sybase error code  | 230  |
|                | ODBC 2 State   | 42000                                      |
|                | ODBC 3 State   | 42000                                      |
|                | Parameter 1  | Name of the column that cannot be changed. |
|                | Parameter 2  | Name of the table containing the column.   |
|                |  |  |
| Probable cause | You may have tried to modify a column that you do not have permission to<br>modify. You may have tried to modify a column defined as an expression<br>(such as column1+column2) in a view. |  |

#### Cannot modify publication entry using ALTER SYNCHRONIZATION

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -770                           |
| Constant          | SQLE_CANNOT_MODIFY_PUB_AS_SYNC |
| SQLSTATE          | 5RW15                          |
| Sybase error code | 13780                          |
| ODBC 2 State      | 42000                          |
| ODBC 3 State      | 42S02                          |

# **Probable cause** You attempted to modify a publication entry using an alter synchronization statement.

#### Cannot modify synchronization entry using ALTER PUBLICATION

| ltem              | Value                          |  |
|-------------------|--------------------------------|--|
| SQLCODE           | -769                           |  |
| Constant          | SQLE_CANNOT_MODIFY_SYNC_AS_PUB |  |
| SQLSTATE          | 5RW14                          |  |
| Sybase error code | 13779                          |  |
| ODBC 2 State      | 42000                          |  |
| ODBC 3 State      | 42802                          |  |

### **Probable cause** You attempted to modify a synchronization entry using an alter publication statement.

#### Cannot open transaction log file -- %1

| Item              | Value   |  |
|-------------------|---|--|
| SQLCODE           | -106  |  |
| Constant          | SQLE_CANNOT_OPEN_LOG                              |  |
| SQLSTATE          | 08W05   |  |
| Sybase error code | 2561  |  |
| ODBC 2 State      | 08003   |  |
| ODBC 3 State      | 08003   |  |
| Parameter 1       | Reason why transaction log file cannot be opened. |  |

# Probable causeThe database server was unable to open the named transaction log file. The<br/>log file name may include an invalid device or directory. If this is the case,<br/>you can use the DBLOG utility to find out where the transaction log should<br/>be and perhaps change it.

#### Cannot register '%1' since another exclusive instance is running

| Item              | Value                           |  |
|-------------------|---------------------------------|--|
| SQLCODE           | -782                            |  |
| Constant          | SQLE_SAME_EXCLUSIVE_APP_RUNNING |  |
| SQLSTATE          | 5RW21                           |  |
| Sybase error code | 13792                           |  |
| ODBC 2 State      | 42000                           |  |
| ODBC 3 State      | 42S02                           |  |
| Parameter 1       | Name of the application         |  |

# **Probable cause** You attempted to start an application but another exclusive instance of the same application is already registered.

| Item              | Value                         |  |
|-------------------|-------------------------------|--|
| SQLCODE           | -789                          |  |
| Constant          | SQLE_APP_REG_COOKIE_EXHAUSTED |  |
| SQLSTATE          | 5RW28                         |  |
| Sybase error code | 13799                         |  |
| ODBC 2 State      | 42000                         |  |
| ODBC 3 State      | 42S02                         |  |
| Parameter 1       | Name of the application       |  |
|                   |                               |  |

Probable cause Cannot register until someone deregistered.

#### Cannot register another '%1' as an exclusive application

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -783                    |
| Constant          | SQLE_SAME_APP_RUNNING   |
| SQLSTATE          | 5RW22                   |
| Sybase error code | 13793                   |
| ODBC 2 State      | 42000                   |
| ODBC 3 State      | 42S02                   |
| Parameter 1       | Name of the application |

## **Probable cause** You attempted to register an exclusive application but another instance of the same application is already registered.

#### Cannot register connection because of invalid application cookie

| Value                |  |
|----------------------|--|
| -784                 |  |
| SQLE_CANNOT_REG_CONN |  |
| 5RW23                |  |
| 13794                |  |
| 42000                |  |
| 42S02                |  |
|                      |  |

**Probable cause** Application registration cannot be found for the given cookie.

#### Cannot register connection to '%1' since automatic label exhausted

| ltem |                   | Value                              |  |
|------|-------------------|------------------------------------|--|
|      | SQLCODE           | -790                               |  |
|      | Constant          | SQLE_CONN_REG_AUTO_LABEL_EXHAUSTED |  |
|      | SQLSTATE          | 5RW29                              |  |
|      | Sybase error code | 13800                              |  |
|      | ODBC 2 State      | 42000                              |  |
|      | ODBC 3 State      | 42S02                              |  |
|      | Parameter 1       | Name of the application            |  |
|      |                   |                                    |  |

Probable cause

You may register using a specified label instead.

| ltem              | Value  |  |
|-------------------|--|--|
| SQLCODE           | -653   |  |
| Constant          | SQLE_CLASS_MEMBER_OF_JAR                         |  |
| SQLSTATE          | WP004  |  |
| Sybase error code | 13743  |  |
| ODBC 2 State      | ERROR  |  |
| ODBC 3 State      | ERROR  |  |
| Parameter 1       | The name of the class file that can't be removed |  |
|                   | •  |  |

**Probable cause** You attempted to remove a class file which is still part of a Jar. (It must be removed with the Jar)

#### Cannot serialize Java object with class '%1'

| Item              | Value   |  |
|-------------------|---|--|
| SQLCODE           | -662  |  |
| Constant          | SQLE_JAVA_SERIALIZATION_ERROR                     |  |
| SQLSTATE          | WI009   |  |
| Sybase error code | 13744   |  |
| ODBC 2 State      | ERROR   |  |
| ODBC 3 State      | ERROR   |  |
| Parameter 1       | The class of the value that cannot be serialized. |  |
|                   |   |  |

**Probable cause** The Java object cannot be serialized as a persistent database column.

#### Cannot set a temporary option for user '%1'

|                | Item   | Value                                   |
|----------------|--|---|
|                | SQLCODE  | -203                                    |
|                | Constant   | SQLE_TEMPORARY_NOT_ALLOWED              |
|                | SQLSTATE   | 42W45                                   |
|                | Sybase error code  | 13687                                   |
|                | ODBC 2 State   | 42000                                   |
|                | ODBC 3 State   | 42000                                   |
|                | Parameter 1  | user ID whose option was to be changed. |
|                |  |   |
| Probable cause | TEMPORARY options are set on a connection basis. To change an option<br>for another user, do not specify TEMPORARY in the SET OPTION<br>statement. |   |

#### Cannot stop the database server

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -607                    |
| Constant          | SQLE_CANNOT_STOP_SERVER |
| SQLSTATE          | WW002                   |
| Sybase error code | 13673                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |

### **Probable cause** The server has determined that it cannot be shut down at this time. Normally, this error should not occur.

#### Cannot subscribe to '%1'

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -768                     |
| Constant          | SQLE_CANNOT_SUBSCRIBE    |
| SQLSTATE          | 5RW13                    |
| Sybase error code | 13778                    |
| ODBC 2 State      | 42000                    |
| ODBC 3 State      | 42S02                    |
| Parameter 1       | Name of the publication. |

**Probable cause** Some publications are not subscribable such as a synchronization publication.

#### Cannot synchronize table '%1' since it does not have a primary key

| Value                             |
|-----------------------------------|
| -777                              |
| SQLE_CANNOT_SYNC_TABLE_WITHOUT_PK |
| 5RW16                             |
| 13787                             |
| 42000                             |
| 42S02                             |
| Name of the table                 |
|                                   |

**Probable cause** Table for synchronization must contain a primary key.

# Cannot uniquely identify column '%2' of table '%1' in the current JDBC resultset

| ltem              | Value  |  |
|-------------------|--|--|
| SQLCODE           | -756   |  |
| Constant          | SQLE_JDBC_TBL_COL_NOT_FOUND_IN_RESULT<br>SET |  |
| SQLSTATE          | WJ021  |  |
| Sybase error code | 13766  |  |
| ODBC 2 State      | ERROR  |  |
| ODBC 3 State      | ERROR  |  |
| Parameter 1       | Table name                                   |  |
| Parameter 2       | Column name                                  |  |

**Probable cause** Failed to identify a column in a JDBC resultset with the given table name and column name. This can happen either the given names are not found or they are ambiguous.

#### Cannot uniquely identify rows in cursor

| Item              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -295                               |
| Constant          | SQLE_CANNOT_UNIQUELY_IDENTIFY_ROWS |
| SQLSTATE          | 09W05                              |
| Sybase error code | 311                                |
| ODBC 2 State      | 42000                              |
| ODBC 3 State      | 42000                              |
|                   |                                    |

Probable causeYou opened a UNIQUE cursor on a SELECT statement for which a set of<br/>columns uniquely identifying each row cannot be generated. One of the<br/>tables may not be defined with a primary key or uniqueness constraint, or the<br/>SELECT statement may involve a UNION or GROUP BY.

#### Cannot update an expression

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -190                       |
| Constant          | SQLE_NON_UPDATEABLE_COLUMN |
| SQLSTATE          | 53W02                      |
| Sybase error code | 230                        |
| ODBC 2 State      | 37000                      |
| ODBC 3 State      | 42000                      |
|                   |                            |

### **Probable cause** You tried to update a column in a query that is a database expression rather than a column in a table.

# Cannot update column '%1' since it appears in the ORDER BY clause.

| Item              | Value   |  |
|-------------------|---|--|
| SQLCODE           | -814  |  |
| Constant          | SQLE_CANNOT_UPDATE_ORDER_BY_COLUMN                      |  |
| SQLSTATE          | 42W37   |  |
| Sybase error code | 6267  |  |
| ODBC 2 State      | 42000   |  |
| ODBC 3 State      | 42000   |  |
| Parameter 1       | Name of the column that appears in the ORDER BY clause. |  |

#### **Probable cause** You attempted to update a column that appears in the ORDER BY clause. The ANSI\_UPDATE\_CONSTRAINTS option controls whether this update is allowed.

# Cannot update column '%1' since it does not appear in the SELECT clause.

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -815  |
| Constant          | SQLE_UPDATE_NOT_IN_SELECT                                     |
| SQLSTATE          | 42W38   |
| Sybase error code | 7740  |
| ODBC 2 State      | 42000   |
| ODBC 3 State      | 42000   |
| Parameter 1       | Name of the column that does not appear in the SELECT clause. |
|                   |   |

 
 Probable cause
 You attempted to update a column that does not explicitly appear in the SELECT list. The ANSI\_UPDATE\_CONSTRAINTS option controls whether this update is allowed.

#### Cannot update member fields qualified with "final" modifier

| Item |                   | Value                          |  |
|------|-------------------|--------------------------------|--|
|      | SQLCODE           | -699                           |  |
|      | Constant          | SQLE_CANNOT_UPDATE_FINAL_FIELD |  |
|      | SQLSTATE          | WJ012                          |  |
|      | Sybase error code | 13606                          |  |
|      | ODBC 2 State      | ERROR                          |  |
|      | ODBC 3 State      | ERROR                          |  |

### **Probable cause** An attempt was made to modify a Java member that was qualified with the "final" modifier. Such members are constant and cannot be modified.

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -734  |
| Constant          | SQLE_CANNOT_UPDATE_NULL_ROW                     |
| SQLSTATE          | 09W08   |
| Sybase error code | 13750   |
| ODBC 2 State      | 42000   |
| ODBC 3 State      | 42000   |
| Parameter 1       | The name of the table which cannot be modified. |
|                   |   |

#### Cannot update or delete an all-NULL row from table '%1'

Probable causeYou attempted to modify or delete a row in the specified table, which is part<br/>of the null-supplying side of an outer join. However, the cursor is currently<br/>positioned on a derived row that contains an all-NULL row for this table,<br/>which is the result of the failure of one or more ON conditions to evaluate to<br/>TRUE. Verify that the UPDATE or DELETE statement is correct.

#### Cannot update primary key for table '%1' involved in a publication

| ltem              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -780                              |
| Constant          | SQLE_ARTICLE_PK_CANNOT_BE_UPDATED |
| SQLSTATE          | 5RW19                             |
| Sybase error code | 13790                             |
| ODBC 2 State      | 42000                             |
| ODBC 3 State      | 42S02                             |
| Parameter 1       | Name of the table.                |
|                   |                                   |

# **Probable cause** The primary key of a table involved in a publication cannot be updated. The database option "Prevent\_article\_pkey\_update" can be set to "OFF" to allow updates to the primary key of table involved in a publication.

#### Certicom handshake failure

|                | ltem                           | Value   |  |
|----------------|--------------------------------|---|--|
|                | SQLCODE                        | -829  |  |
|                | Constant                       | SQLE_CERTICOM_HANDSHAKE_FAILED                                  |  |
|                | SQLSTATE                       | 08W59   |  |
|                | Sybase error code              | 13835   |  |
|                | ODBC 2 State                   | 08S01   |  |
|                | ODBC 3 State                   | 08S01   |  |
|                |                                |   |  |
| Probable cause | The connection failed process. | nection failed because of a failure in the Certicom handshaking |  |

#### Certicom initialization on server failed

| ltem              | Value                            |
|-------------------|----------------------------------|
| SQLCODE           | -838                             |
| Constant          | SQLE_CERTICOM_INIT_FAILED_ON_SRV |
| SQLSTATE          | 08W61                            |
| Sybase error code | 13844                            |
| ODBC 2 State      | 08S01                            |
| ODBC 3 State      | 08S01                            |
|                   |                                  |

**Probable cause** The connection failed because the initialization of the Certicom library on the server failed.

# Character conversion reporting is not available when the single byte converter is used

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -883   |
| Constant          | SQLE_CHARACTER_CONVERSION_REPORT_NOT<br>_AVAILABLE |
| SQLSTATE          | WC007  |
| Sybase error code | 13898  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |

**Probable cause** You attempted to set the On\_Charset\_conversion\_failure option to produce either warning or error report. This setting is not available when the single-byte to single-byte converter is used.

# Character set translation to '%1' cannot be performed; '%2' is used instead

| 114   |
|---|
| SQLE_CANNOT_PERFORM_CHAR_TRANSLATIO<br>N          |
| 01W12   |
| 13613   |
| 01000   |
| 01000   |
| Name of character set the application requested.  |
| Name of character set the database will be using. |
|   |

# **Probable cause** The server is unable to do a character translation from the character set the database is using to the character set the application requested.

#### **CHECKPOINT** statement requires a rollback log

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -212                          |
| Constant          | SQLE_CHECKPOINT_REQUIRES_UNDO |
| SQLSTATE          | 42W20                         |
| Sybase error code | 13653                         |
| ODBC 2 State      | 40001                         |
| ODBC 3 State      | 40001                         |
|                   | 1                             |

#### Probable cause

You cannot use a CHECKPOINT statement when the database server is running in bulk mode without a rollback log.

#### Class '%1' has no public field '%2'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -93  |
| Constant          | SQLE_FIELD_NOT_FOUND   |
| SQLSTATE          | WW013  |
| Sybase error code | 13703  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
| Parameter 1       | The name of the class in which the named field could not be found. |
| Parameter 2       | The name of the field which could not be found.                    |

**Probable cause** An expression referenced a field which either does not exist or is not public.

#### **Client out of memory**

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -876                      |
| Constant          | SQLE_CLIENT_OUT_OF_MEMORY |
| SQLSTATE          | 08W65                     |
| Sybase error code | 13882                     |
| ODBC 2 State      | S1001                     |
| ODBC 3 State      | HY001                     |

| Probable cause | A failure occurred when the database client was trying to allocate memory. |
|----------------|--|
|----------------|--|

#### Client/database server version mismatch

-

|             | ltem                | Value  |
|-------------|---------------------|--|
|             | SQLCODE             | -231   |
|             | Constant            | SQLE_DBLIB_ENGINE_MISMATCH                           |
|             | SQLSTATE            | 08W19  |
|             | Sybase error code   | 13658  |
|             | ODBC 2 State        | 08001  |
|             | ODBC 3 State        | 08001  |
|             |                     |  |
| hable cause | Vour avacutable use | a database interface library that does not match the |

**Probable cause** Your executable uses a database interface library that does not match the version number of the database server.

#### **Client/server communications protocol version mismatch**

| ltem              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -88                    |
| Constant          | SQLE_PROTOCOL_MISMATCH |
| SQLSTATE          | 08W15                  |
| Sybase error code | 1602                   |
| ODBC 2 State      | 08S01                  |
| ODBC 3 State      | 08S01                  |

**Probable cause** The connection failed because the protocol versions of the client and the server do not match. Make sure the client and server software are the same version.

# Column '%1' found in more than one table -- need a correlation name

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -144                          |
| Constant          | SQLE_COLUMN_AMBIGUOUS         |
| SQLSTATE          | 52002                         |
| Sybase error code | 209                           |
| ODBC 2 State      | 37000                         |
| ODBC 3 State      | 42000                         |
| Parameter 1       | Name of the ambiguous column. |
|                   |                               |

# **Probable cause** You have not put a correlation name on a column that is found in more than one of the tables referenced in a query. You need to add a correlation name to the reference.

# Column '%1' in foreign key has a different definition than primary key

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -113                         |
| Constant          | SQLE_INVALID_FOREIGN_KEY_DEF |
| SQLSTATE          | 53030                        |
| Sybase error code | 1721                         |
| ODBC 2 State      | 42000                        |
| ODBC 3 State      | 42000                        |
| Parameter 1       | Name of the problem column.  |

**Probable cause** The data type of the column in the foreign key is not the same as the data type of the column in the primary key. Change the definition of one of the columns using ALTER TABLE.

#### Column '%1' in table '%2' cannot be NULL

-

| ltem              | Value                                    |
|-------------------|--|
| SQLCODE           | -195                                     |
| Constant          | SQLE_COLUMN_CANNOT_BE_NULL               |
| SQLSTATE          | 23502                                    |
| Sybase error code | 233                                      |
| ODBC 2 State      | 23000                                    |
| ODBC 3 State      | 23000                                    |
| Parameter 1       | Name of the column that cannot be NULL.  |
| Parameter 2       | Name of the table containing the column. |
|                   | •  |

Probable cause You have not supplied a value where a value is required. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

#### Column '%1' not found

| ltem              | Value                                       |
|-------------------|---|
| SQLCODE           | -143  |
| Constant          | SQLE_COLUMN_NOT_FOUND                       |
| SQLSTATE          | 52003                                       |
| Sybase error code | 207   |
| ODBC 2 State      | S0002                                       |
| ODBC 3 State      | 42S22                                       |
| Parameter 1       | Name of the column that could not be found. |
|                   |   |

### **Probable cause** You misspelled the name of a column, or the column you are looking for is in a different table.

#### Column '%1' not found in table '%2'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -834   |
| Constant          | SQLE_COLUMN_NOT_FOUND_IN_TABLE                             |
| SQLSTATE          | 52005  |
| Sybase error code | 13840  |
| ODBC 2 State      | S0002  |
| ODBC 3 State      | 42S22  |
| Parameter 1       | Name of the column that could not be found.                |
| Parameter 2       | Name of the table that was supposed to contain the column. |

**Probable cause** You misspelled the name of a column, or the column you are looking for is in a different table.

#### COMMIT/ROLLBACK not allowed within atomic operation

|   | ltem  | Value                   |
|---|---|-------------------------|
| - | SQLCODE                                       | -267                    |
|   | Constant                                      | SQLE_ATOMIC_OPERATION   |
|   | SQLSTATE                                      | 42W28                   |
|   | Sybase error code                             | 13640                   |
|   | ODBC 2 State                                  | 37000                   |
|   | ODBC 3 State                                  | 42000                   |
|   | SQLSTATE<br>Sybase error code<br>ODBC 2 State | 42W28<br>13640<br>37000 |

**Probable cause** You attempted a COMMIT or ROLLBACK statement while executing within an atomic operation.

#### COMMIT/ROLLBACK not allowed within trigger actions

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -273                           |
| Constant          | SQLE_INVALID_TRIGGER_STATEMENT |
| SQLSTATE          | 2D501                          |
| Sybase error code | 102                            |
| ODBC 2 State      | 37000                          |
| ODBC 3 State      | 42000                          |

**Probable cause** You attempted to execute a statement that is not allowed while performing a trigger action. COMMIT and ROLLBACK statements cannot be executed from a trigger.

#### **Communication error**

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -85                       |
| Constant          | SQLE_COMMUNICATIONS_ERROR |
| SQLSTATE          | 08W12                     |
| Sybase error code | 1602                      |
| ODBC 2 State      | 08S01                     |
| ODBC 3 State      | 08S01                     |

Probable cause

There is a communication problem between the application and the server.

#### Computed columns are not supported in this database

| Item              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -709                                |
| Constant          | SQLE_COMPUTED_COLUMNS_NOT_SUPPORTED |
| SQLSTATE          | 0AW06                               |
| Sybase error code | 13722                               |
| ODBC 2 State      | 37000                               |
| ODBC 3 State      | 42000                               |
|                   |                                     |

#### Probable cause

The current database is an older database and does not have catalog support for computed (materialized) columns. To use this feature, upgrade your database to the most recent version.

#### **Connection error: %1**

|                | Item   | Value                                |
|----------------|--|--------------------------------------|
|                | SQLCODE  | -832                                 |
|                | Constant   | SQLE_CONNECTION_ERROR                |
|                | SQLSTATE   | 08W60                                |
|                | Sybase error code  | 13838                                |
|                | ODBC 2 State   | 08001                                |
|                | ODBC 3 State   | 08001                                |
|                | Parameter 1  | Description of the connection error. |
|                |  |                                      |
| Probable cause | An error occurred while attempting to establish a connection with the database server, but before attempting to connect to a database. Failure to initialize a communication link during the connection attempt is an example of this error. Creating a debug log file using the Debug and LogFile |                                      |

connection parameters may provide more information.

#### **Connection not found**

| Value                     |
|---------------------------|
| -108                      |
| SQLE_CONNECTION_NOT_FOUND |
| 08W02                     |
| 4224                      |
| 08003                     |
| 08003                     |
|                           |

### **Probable cause** The specified connection name on a DISCONNECT or SET CONNECTION statement is invalid.

#### **Connection was terminated**

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -308                       |
| Constant          | SQLE_CONNECTION_TERMINATED |
| SQLSTATE          | 40W07                      |
| Sybase error code | 4224                       |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |

# Probable causeYour database connection has been terminated and your transaction has been<br/>rolled back. The connection may have been terminated because a DBA<br/>executed a DROP CONNECTION statement, or because the database server<br/>was shut down, or because your network connection to the database server<br/>was interrupted.

#### Connections to database have been disabled

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -99                       |
| Constant          | SQLE_CONNECTIONS_DISABLED |
| SQLSTATE          | 08W04                     |
| Sybase error code | 4224                      |
| ODBC 2 State      | 08005                     |
| ODBC 3 State      | 08005                     |
|                   |                           |

# Probable cause Connections to the network database server have been disabled. You will receive this error until connections have been enabled.

#### Contents of backup files are inconsistent

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -715                      |
| Constant          | SQLE_RESTORE_INCONSISTENT |
| SQLSTATE          | WB006                     |
| Sybase error code | 13724                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
| '                 |                           |

**Probable cause** During a RESTORE, the contents of a backup that was done to two or more disk or tape devices were found to be inconsistent.

#### Correlation name '%1' not found

| Item              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -142                                  |
| Constant          | SQLE_CORRELATION_NAME_NOT_FOUND       |
| SQLSTATE          | 52W02                                 |
| Sybase error code | 208                                   |
| ODBC 2 State      | S0002                                 |
| ODBC 3 State      | 42S02                                 |
| Parameter 1       | Name of the invalid correlation name. |
|                   | '                                     |

**Probable cause** You misspelled a correlation name, or you used a table name instead of the correlation name.

#### Could not access column information for the table '%1'

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -667                                  |
| Constant          | SQLE_OMNI_RMT_COLUMNS_NOTFOUND        |
| SQLSTATE          | WO008                                 |
| Sybase error code | 11207                                 |
| ODBC 2 State      | ERROR                                 |
| ODBC 3 State      | ERROR                                 |
| Parameter 1       | The complete name of the remote table |
|                   | •                                     |

### **Probable cause** Column information for the table could not be accessed. Check privileges for the table.

#### Could not allocate resources to call external function

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -622                        |
| Constant          | SQLE_ERROR_CALLING_FUNCTION |
| SQLSTATE          | WW008                       |
| Sybase error code | 13679                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
| ODBC 5 State      | EKKOK                       |

**Probable cause** The external function could not be called due to a shortage of operating system resources. If the operating system supports threads, the maximum thread count should be increased.

# Could not change an opened prepared statement or callable statement

| Item              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -694                                |
| Constant          | SQLE_CANNOT_CHANGE_OPENED_STATEMENT |
| SQLSTATE          | WJ008                               |
| Sybase error code | 13603                               |
| ODBC 2 State      | ERROR                               |
| ODBC 3 State      | ERROR                               |

# **Probable cause** You attempted to change the SQL statement of an opened prepared statement or callable statement. Prepared statement and callable statement must be closed before attempting such changes.

| Could not decompress clas | s '%1' from Jar. |
|---------------------------|------------------|
|---------------------------|------------------|

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -652                                  |
| Constant          | SQLE_CANNOT_DECOMPRESS_CLASS          |
| SQLSTATE          | WP003                                 |
| Sybase error code | 13742                                 |
| ODBC 2 State      | ERROR                                 |
| ODBC 3 State      | ERROR                                 |
| Parameter 1       | The name of the class file in the Jar |

Probable cause The Java runtime library must be installed to extract class files from .ZIPs or .JARs

#### Could not execute backup/restore DLL (%1) entry point.

\_

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -692                        |
| Constant          | SQLE_BACKUP_ENTRY_NOT_FOUND |
| SQLSTATE          | 08W45                       |
| Sybase error code | 13719                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
|                   |                             |

Probable cause An attempt to locate or execute the backup/restore DLL entry point failed.

#### Could not execute store DLL (%1) entry point.

| Value                      |
|----------------------------|
| -647                       |
| SQLE_STORE_ENTRY_NOT_FOUND |
| 08W35                      |
| 13700                      |
| ERROR                      |
| ERROR                      |
|                            |

Probable cause

An attempt to locate or execute the store DLL entry point failed.

#### Could not find '%1' in dynamic library '%2'

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -621  |
| Constant          | SQLE_COULD_NOT_FIND_FUNCTION  |
| SQLSTATE          | WW007   |
| Sybase error code | 13678   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | Name of the function which could not be found.                        |
| Parameter 2       | Name of the dynamic library in which the function could not be found. |

**Probable cause** The external function could not be found in the dynamic library.

| Could not | load dynamic | library '%1' |
|-----------|--------------|--------------|
|-----------|--------------|--------------|

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -620   |
| Constant          | SQLE_COULD_NOT_LOAD_LIBRARY                            |
| SQLSTATE          | WW006  |
| Sybase error code | 13677  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
| Parameter 1       | Name of the dynamic library which could not be loaded. |
|                   |  |

**Probable cause** This error is usually caused by a failure to load a dynamic library named in an external function call. This error can also occur if other libraries such as the Java virtual machine library are missing.

#### Could not load the backup/restore DLL "%1"

| Value                  |
|------------------------|
| -691                   |
| SQLE_BACKUP_NOT_LOADED |
| 08W44                  |
| 13718                  |
| ERROR                  |
| ERROR                  |
|                        |

**Probable cause** An attempt to load the backup/restore DLL failed.

#### Could not load the store DLL "%1"

| ltem              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -646                  |
| Constant          | SQLE_STORE_NOT_LOADED |
| SQLSTATE          | 08W34                 |
| Sybase error code | 13699                 |
| ODBC 2 State      | ERROR                 |
| ODBC 3 State      | ERROR                 |

**Probable cause** An attempt to load the store DLL failed.

#### **CREATE/DROP STATISTICS statement cannot refer to virtual tables**

| _ | ltem              | Value                                       |
|---|-------------------|---|
|   | SQLCODE           | -858  |
|   | Constant          | SQLE_HISTOGRAMS_NOT_SUPPORTED_ON_OBJ<br>ECT |
|   | SQLSTATE          | 42W67                                       |
|   | Sybase error code | 13861                                       |
|   | ODBC 2 State      | 37000                                       |
|   | ODBC 3 State      | 42000                                       |
|   |                   |   |

Probable causeYou attempted to use CREATE/DROP STATISTICS to create/drop one or<br/>more histograms on a virtual database object, such as a view or remote table.<br/>The CREATE STATISTICS and DROP STATISTICS statements can only<br/>refer to base tables, local temporary tables, or global temporary tables in the<br/>ASA database that you are connected to.

#### Creating remote tables with computed columns is not supported

| ltem              | Value                            |
|-------------------|----------------------------------|
| SQLCODE           | -732                             |
| Constant          | SQLE_OMNI_COMPUTED_NOT_SUPPORTED |
| SQLSTATE          | WO021                            |
| Sybase error code | 11205                            |
| ODBC 2 State      | ERROR                            |
| ODBC 3 State      | ERROR                            |
|                   | •                                |

| Probable cause | Computed columns are not supported in 'CREATE TABLE' statements |
|----------------|---|
|                | which specify a remote location.                                |

#### Current connection is already registered to '%1' as '%2'

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -787                         |
| Constant          | SQLE_CONN_ALREADY_REGISTERED |
| SQLSTATE          | 5RW26                        |
| Sybase error code | 13797                        |
| ODBC 2 State      | 42000                        |
| ODBC 3 State      | 42S02                        |
| Parameter 1       | Name of the application      |
| Parameter 2       | Registered connection label  |
|                   |                              |

**Probable cause** You attempted to register this connection more than once.

#### Cursor already open

| Value                    |
|--------------------------|
| -172                     |
| SQLE_CURSOR_ALREADY_OPEN |
| 24502                    |
| 558                      |
| 24000                    |
| 24000                    |
|                          |

**Probable cause** You attempted to OPEN a cursor that is already open.

#### Cursor has not been declared

| _ | Item              | Value                    |
|---|-------------------|--------------------------|
|   | SQLCODE           | -170                     |
|   | Constant          | SQLE_CURSOR_NOT_DECLARED |
|   | SQLSTATE          | 24W01                    |
|   | Sybase error code | 557                      |
|   | ODBC 2 State      | 24000                    |
|   | ODBC 3 State      | 24000                    |
|   |                   |                          |

**Probable cause** You attempted to OPEN a cursor that has not been declared.

#### Cursor is restricted to FETCH NEXT operations

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -668                  |
| Constant          | SQLE_NO_SCROLL_CURSOR |
| SQLSTATE          | 09W06                 |
| Sybase error code | 13710                 |
| ODBC 2 State      | S1106                 |
| ODBC 3 State      | HY106                 |

Probable causeAn illegal FETCH operation has been detected for a NO SCROLL cursor.<br/>For a forward-only cursor the only permitted FETCH operations are FETCH<br/>RELATIVE 0 and FETCH NEXT (FETCH RELATIVE 1).

#### Cursor not in a valid state

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -853                      |
| Constant          | SQLE_CURSOR_INVALID_STATE |
| SQLSTATE          | 24000                     |
| Sybase error code | 557                       |
| ODBC 2 State      | 24000                     |
| ODBC 3 State      | 24000                     |
|                   | •                         |

**Probable cause** You attempted to use a cursor that is not in a valid state for the attempted operation. For example, the cursor may have encountered an error.

#### **Cursor not open**

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -180                 |
| Constant          | SQLE_CURSOR_NOT_OPEN |
| SQLSTATE          | 24501                |
| Sybase error code | 559                  |
| ODBC 2 State      | 34000                |
| ODBC 3 State      | 34000                |
|                   |                      |

Probable cause You attempted to use a cursor that has not been opened.

#### Cursor option values changed

| ltem              | Value                       |  |
|-------------------|-----------------------------|--|
| SQLCODE           | 121                         |  |
| Constant          | SQLE_CURSOR_OPTIONS_CHANGED |  |
| SQLSTATE          | 01S02                       |  |
| Sybase error code | 13857                       |  |
| ODBC 2 State      | 01S02                       |  |
| ODBC 3 State      | 01S02                       |  |
|                   |                             |  |

#### Probable cause

The engine could not support the requested cursor option values for the associated query, and similar option settings were substituted.

#### Data definition statements not allowed in procedures or triggers

| _ | Item              | Value                              |
|---|-------------------|------------------------------------|
|   | SQLCODE           | -623                               |
|   | Constant          | SQLE_DDL_NOT_ALLOWED_IN_PROCEDURES |
|   | SQLSTATE          | 52W21                              |
|   | Sybase error code | 154                                |
|   | ODBC 2 State      | ERROR                              |
|   | ODBC 3 State      | ERROR                              |
|   |                   |                                    |

# **Probable cause** The procedure or trigger definition contains a data definition statement (such as CREATE, DROP, GRANT, REVOKE, ALTER). These statements are not allowed within procedures or triggers.

#### Database "%1" needs recovery

| Item              | Value   |  |
|-------------------|---|--|
| SQLCODE           | -665  |  |
| Constant          | SQLE_DATABASE_NEEDS_RECOVERY                      |  |
| SQLSTATE          | 08W41   |  |
| Sybase error code | 13709   |  |
| ODBC 2 State      | ERROR   |  |
| ODBC 3 State      | ERROR   |  |
| Parameter 1       | The filename of the database that needs recovery. |  |
|                   |   |  |

**Probable cause** The database quit abnormally the last time it was used. Database recovery must be performed before proceeding.

#### Database backup not started

| ltem              | Value                   |  |
|-------------------|-------------------------|--|
| SQLCODE           | -241                    |  |
| Constant          | SQLE_BACKUP_NOT_STARTED |  |
| SQLSTATE          | WB002                   |  |
| Sybase error code | 3206                    |  |
| ODBC 2 State      | ERROR                   |  |
| ODBC 3 State      | ERROR                   |  |
|                   |                         |  |

### **Probable cause** A database backup could not be started. Either you do not have DBA authority, or another backup has started and not completed.

#### Database cannot be started -- %1

| Item              | Value                                   |
|-------------------|---|
| SQLCODE           | -105                                    |
| Constant          | SQLE_UNABLE_TO_CONNECT                  |
| SQLSTATE          | 08001                                   |
| Sybase error code | 4001                                    |
| ODBC 2 State      | 08001                                   |
| ODBC 3 State      | 08001                                   |
| Parameter 1       | Reason that database cannot be started. |

Probable cause

The specified database cannot be started. Either it does not exist, it is not a database, it is corrupt, or it is an older format.

#### Database created without any schema

| ltem              | Value             |
|-------------------|-------------------|
| SQLCODE           | 123               |
| Constant          | SQLE_DATABASE_NEW |
| SQLSTATE          | 01W19             |
| Sybase error code | 13884             |
| ODBC 2 State      | OK                |
| ODBC 3 State      | ОК                |
|                   |                   |

**Probable cause** An Ultralite database was created without a schema provided. A schema upgrade must occur before any database operations can take place.

#### Database creation failed: %1

| Item              | Value                                     |  |
|-------------------|---|--|
| SQLCODE           | -645                                      |  |
| Constant          | SQLE_DATABASE_NOT_CREATED                 |  |
| SQLSTATE          | 08W33                                     |  |
| Sybase error code | 928                                       |  |
| ODBC 2 State      | 08004                                     |  |
| ODBC 3 State      | 08004                                     |  |
| Parameter 1       | Reason that the database was not created. |  |
|                   |   |  |

**Probable cause** Your attempt to initialize a file for a database or for a write file failed.

#### Database is active

| ltem              | Value                |  |
|-------------------|----------------------|--|
| SQLCODE           | -664                 |  |
| Constant          | SQLE_DATABASE_ACTIVE |  |
| SQLSTATE          | 08W40                |  |
| Sybase error code | 13708                |  |
| ODBC 2 State      | ERROR                |  |
| ODBC 3 State      | ERROR                |  |
|                   |                      |  |

**Probable cause** An attempt was made to create a writefile for a database that is currently active.

#### Database name not unique

| ltem  | Value                                      |  |
|---|--|--|
| SQLCODE   | -77  |  |
| Constant  | SQLE_ALIAS_CLASH                           |  |
| SQLSTATE  | 08W27                                      |  |
| Sybase error code   | 1801                                       |  |
| ODBC 2 State  | 08001                                      |  |
| ODBC 3 State  | 08001                                      |  |
| Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State | SQLE_ALIAS_CLASH<br>08W27<br>1801<br>08001 |  |

#### Probable cause

The database cannot be started as its name is conflicting with a previously started database.

#### Database name required to start server

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -87                         |
| Constant          | SQLE_DATABASE_NAME_REQUIRED |
| SQLSTATE          | 08W14                       |
| Sybase error code | 840                         |
| ODBC 2 State      | 08001                       |
| ODBC 3 State      | 08001                       |
|                   |                             |
| <br>              |                             |

### **Probable cause** You did not supply a database name. A database name is required to start a database server (version 5.5.x or earlier).

| Database option '%1' for user ' | '%2' has an invalid setting |
|---------------------------------|-----------------------------|
|---------------------------------|-----------------------------|

| Item              | Value   |
|-------------------|---|
| SQLCODE           | 113   |
| Constant          | SQLE_INVALID_OPTION_ON_CONNECT                          |
| SQLSTATE          | 01W11   |
| Sybase error code | 13688   |
| ODBC 2 State      | 01000   |
| ODBC 3 State      | 01000   |
| Parameter 1       | Name of the database option that has the invalid value. |
| Parameter 2       | Name of the user attempting to connect.                 |

# Probable causeUpon processing a connection request for a specific user, the server<br/>processed a database option from the SYSOPTIONS table which had an<br/>invalid setting. The erroneous option setting is ignored; in its place, the<br/>server will use the default option value for the current database.

#### Database page size too big

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -97                    |
| Constant          | SQLE_PAGE_SIZE_TOO_BIG |
| SQLSTATE          | 08W22                  |
| Sybase error code | 927                    |
| ODBC 2 State      | 08004                  |
| ODBC 3 State      | 08004                  |

**Probable cause** You attempted to start a database or create a write file for a database with a page size that exceeds the maximum page size of the running server. Either restart the server with this database named on the command line, or restart the server with a larger page size.

#### Database server already running

| Value                       |
|-----------------------------|
| -96                         |
| SQLE_ENGINE_ALREADY_RUNNING |
| 08W23                       |
| 7950                        |
| S1000                       |
| HY000                       |
|                             |

#### Probable cause

The database server was not able to start because a server with the same name was already running.

#### Database server cannot convert data from/to character set '%1'

| ltem              | Value                                |
|-------------------|--------------------------------------|
| SQLCODE           | -869                                 |
| Constant          | SQLE_UNSUPPORTED_CHARACTER_SET_ERROR |
| SQLSTATE          | 08W64                                |
| Sybase error code | 13873                                |
| ODBC 2 State      | 08S01                                |
| ODBC 3 State      | 08S01                                |
| Parameter 1       | Name of the requested character set. |
|                   | •                                    |

Probable causeThe database server cannot convert character data from/to the character set<br/>requested by the application, possibly because the character set is not<br/>supported, or because database server character set translation is disabled<br/>(see -ct switch on database server). The connection fails.

# Database server cannot convert data from/to character set '%1', conversion may not be correct

| ltem              | Value                                      |
|-------------------|--|
| SQLCODE           | 115  |
| Constant          | SQLE_UNSUPPORTED_CHARACTER_SET_WARNI<br>NG |
| SQLSTATE          | 01W13                                      |
| Sybase error code | 13614                                      |
| ODBC 2 State      | 01000                                      |
| ODBC 3 State      | 01000                                      |
| Parameter 1       | Name of the requested character set.       |

Probable cause The database server cannot convert character data from/to the character set requested by the application, possibly because the character set is not supported, or because database server character set translation is disabled (see -ct switch on database server). The connection succeeds, but character conversion may not be correct for all characters.

#### Database server connection limit exceeded

|               | Item              | Value  |
|---------------|-------------------|--|
|               | SQLCODE           | -102   |
|               | Constant          | SQLE_TOO_MANY_CONNECTIONS                              |
|               | SQLSTATE          | 08W03  |
|               | Sybase error code | 1601   |
|               | ODBC 2 State      | 08004  |
|               | ODBC 3 State      | 08004  |
|               |                   |  |
| robable cause |                   | nber of computers allowed to connect to the server. If |

Probable cause You exceeded the number of computers allowed to connect to the server. If you are running the network database server, the limit is spelled out in your license agreement. The server may be running low on cache such that it cannot accept any more database connections. The personal database server is restricted to 10 connections.

#### Database server not found

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -100                    |
| Constant          | SQLE_ENGINE_NOT_RUNNING |
| SQLSTATE          | 08W01                   |
| Sybase error code | 7950                    |
| ODBC 2 State      | 08001                   |
| ODBC 3 State      | 08001                   |

**Probable cause** The database server is not running, or the interface library is unable to find it.

#### Database server not running in multi-user mode

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -89                       |
| Constant          | SQLE_ENGINE_NOT_MULTIUSER |
| SQLSTATE          | 08W16                     |
| Sybase error code | 7203                      |
| ODBC 2 State      | 08001                     |
| ODBC 3 State      | 08001                     |
|                   |                           |

**Probable cause** The database server was started for bulk loading (the -b switch) and cannot be used as a network server. Stop the database server, and start again without -b.

#### Database upgrade failed

| Value                        |
|------------------------------|
| -672                         |
| SQLE_DATABASE_UPGRADE_FAILED |
| 08W42                        |
| 3451                         |
| 08004                        |
| 08004                        |
|                              |

**Probable cause** Your attempt to upgrade a database failed. This could be caused by a failure to locate one of the SQL script files used to define the system table changes.

#### Database upgrade not possible

| Item              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -673                               |
| Constant          | SQLE_DATABASE_UPGRADE_NOT_POSSIBLE |
| SQLSTATE          | 08W43                              |
| Sybase error code | 3451                               |
| ODBC 2 State      | 08004                              |
| ODBC 3 State      | 08004                              |
|                   | 1                                  |

**Probable cause** An attempt to upgrade a database failed. The database is too old to be upgraded.

## Database upgrade not possible; RowGenerator table not owned by user dbo

| ltem              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -826                               |
| Constant          | SQLE_DBO_DOES_NOT_OWN_ROWGENERATOR |
| SQLSTATE          | 08W57                              |
| Sybase error code | 13832                              |
| ODBC 2 State      | 08004                              |
| ODBC 3 State      | 08004                              |

**Probable cause** 

An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

## Database upgrade not possible; user tables have table ids in system table range

|   | Item              | Value                            |
|---|-------------------|----------------------------------|
| _ | SQLCODE           | -827                             |
|   | Constant          | SQLE_USER_TABLES_IN_SYSTEM_RANGE |
|   | SQLSTATE          | 08W58                            |
|   | Sybase error code | 13833                            |
|   | ODBC 2 State      | 08004                            |
|   | ODBC 3 State      | 08004                            |
|   |                   |                                  |

**Probable cause** An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

#### db\_init has not been called or the call to db\_init failed

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -739                    |
| Constant          | SQLE_DB_INIT_NOT_CALLED |
| SQLSTATE          | 55W07                   |
| Sybase error code | 13752                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
|                   |                         |

**Probable cause** The SQLCA passed to a dblib entry point has not been initialized by a call to db\_init or the call to db\_init failed.

#### Dbspace '%1' not found

\_

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -138   |
| Constant          | SQLE_DBSPACE_NOT_FOUND                       |
| SQLSTATE          | 52W13  |
| Sybase error code | 1802   |
| ODBC 2 State      | S0002  |
| ODBC 3 State      | 42S02  |
| Parameter 1       | Name of the dbspace that could not be found. |

Probable cause You tried to access a dbspace that the database server could not find.

#### Dbspace for table '%1' not found

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -821  |
| Constant          | SQLE_DBSPACE_FOR_TABLE_UNAVAILABLE                  |
| SQLSTATE          | 52W19   |
| Sybase error code | 13827   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | Name of the table whose dbspace could not be found. |

**Probable cause** You tried to access a table in a dbspace that the database server could not find. You may need to change the filename associated with the dbspace using the ALTER DBSPACE statement.

#### **Deadlock detected**

| ltem              | Value         |
|-------------------|---------------|
| SQLCODE           | -306          |
| Constant          | SQLE_DEADLOCK |
| SQLSTATE          | 40001         |
| Sybase error code | 1205          |
| ODBC 2 State      | 40001         |
| ODBC 3 State      | 40001         |

**Probable cause** You attempted to read or write a row and it is locked by another user. Also, the other user is blocked directly or indirectly on your own transaction. This is a deadlock situation and your transaction has been chosen as the one to rollback.

#### Decryption error: %1

| Item              | Value                                   |
|-------------------|---|
| SQLCODE           | -851                                    |
| Constant          | SQLE_DECRYPT_ERROR                      |
| SQLSTATE          | 08W63                                   |
| Sybase error code | 13855                                   |
| ODBC 2 State      | 08001                                   |
| ODBC 3 State      | 08001                                   |
| Parameter 1       | Description of the error that occurred. |

Probable cause An error occurred during decryption.

#### Definition for alias '%1' must appear before its first reference

| Item              | Value                      |  |
|-------------------|----------------------------|--|
| SQLCODE           | -831                       |  |
| Constant          | SQLE_ALIAS_NOT_YET_DEFINED |  |
| SQLSTATE          | 42W61                      |  |
| Sybase error code | 13837                      |  |
| ODBC 2 State      | 37000                      |  |
| ODBC 3 State      | ERROR                      |  |
| Parameter 1       | Name of the alias.         |  |

### **Probable cause** An expression contains a reference to an alias, but the alias is defined later in the SELECT list. The alias definition must appear before its first reference.

#### Derived table '%1' has no name for column %2

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -163   |
| Constant          | SQLE_NO_COLUMN_NAME                              |
| SQLSTATE          | 52004  |
| Sybase error code | 209  |
| ODBC 2 State      | 37000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Name of the derived table.                       |
| Parameter 2       | Number of the column for which there is no name. |

Probable causeThe specified column of the derived table has no column name. Use a select<br/>list alias in the query specification or use a derived columns specifier.

#### Disallowed language extension detected in syntax near '%1'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -627   |
| Constant          | SQLE_INVALID_SYNTAX_EXTENSION                          |
| SQLSTATE          | 0AW03  |
| Sybase error code | 538  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
| Parameter 1       | The word or symbol where the syntax has been detected. |
|                   | -  |

Probable causeThe statement you are trying to execute contains extensions to ANSI 1992<br/>Entry Level SQL. These extensions are not allowed by the current settings.

#### Disk full '%1' -- transaction rolled back

| Item              | Value            |
|-------------------|------------------|
| SQLCODE           | -304             |
| Constant          | SQLE_DEVICE_FULL |
| SQLSTATE          | 40W03            |
| Sybase error code | 3618             |
| ODBC 2 State      | ERROR            |
| ODBC 3 State      | ERROR            |
|                   |                  |

### **Probable cause** Your hard disk is out of space. A ROLLBACK WORK statement has been automatically executed.

#### Disk write failure '%1' -- transaction rolled back

| _ | Item              | Value                  |  |
|---|-------------------|------------------------|--|
| - | SQLCODE           | -303                   |  |
|   | Constant          | SQLE_DISK_WRITE_FAILED |  |
|   | SQLSTATE          | 40W05                  |  |
|   | Sybase error code | 13868                  |  |
|   | ODBC 2 State      | ERROR                  |  |
|   | ODBC 3 State      | ERROR                  |  |
|   |                   |                        |  |

**Probable cause** A disk write failed. A ROLLBACK WORK statement has been automatically executed.

#### **Division by zero**

| Item              | Value               |
|-------------------|---------------------|
| SQLCODE           | -628                |
| Constant          | SQLE_DIV_ZERO_ERROR |
| SQLSTATE          | 22012               |
| Sybase error code | 36007               |
| ODBC 2 State      | 22012               |
| ODBC 3 State      | 22012               |

Probable cause A division by zero operation was detected.

#### Download failed because of conflicts with existing rows.

|              | ltem  | Value                  |
|--------------|---|------------------------|
|              | SQLCODE   | -839                   |
|              | Constant  | SQLE_DOWNLOAD_CONFLICT |
|              | SQLSTATE  | 0AW11                  |
|              | Sybase error code   | 13845                  |
|              | ODBC 2 State  | 37000                  |
|              | ODBC 3 State  | 42000                  |
|              |   |                        |
| obable cause | You attempted a download-only synchronization with modified rows in the |                        |

Probable causeYou attempted a download-only synchronization with modified rows in the<br/>UltraLite database. These was a conflict between one or more rows in the<br/>download stream and rows in the UltraLite database.

#### DTC transactions are not supported on this platform

| ltem              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -799                                |
| Constant          | SQLE_DTC_TRANSACTIONS_NOT_SUPPORTED |
| SQLSTATE          | 0AW10                               |
| Sybase error code | 13809                               |
| ODBC 2 State      | ERROR                               |
| ODBC 3 State      | ERROR                               |
|                   |                                     |

**Probable cause** You tried to enlist a DTC transactions on a platform that does not support this feature.

#### **Duplicate insert column**

\_

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -637                         |
| Constant          | SQLE_DUPLICATE_INSERT_COLUMN |
| SQLSTATE          | 42W41                        |
| Sybase error code | 264                          |
| ODBC 2 State      | 37000                        |
| ODBC 3 State      | 42000                        |

**Probable cause** You supplied a duplicate column name in the list of insert columns.

#### **Duplicate referencing column**

| ltem              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -636                              |
| Constant          | SQLE_DUPLICATE_REFERENCING_COLUMN |
| SQLSTATE          | 42W40                             |
| Sybase error code | 1909                              |
| ODBC 2 State      | 37000                             |
| ODBC 3 State      | 42000                             |

**Probable cause** You supplied a duplicate column name in the list of referencing columns.

#### Dynamic memory exhausted

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -78                           |
| Constant          | SQLE_DYNAMIC_MEMORY_EXHAUSTED |
| SQLSTATE          | 08W26                         |
| Sybase error code | 9119                          |
| ODBC 2 State      | S1001                         |
| ODBC 3 State      | HY001                         |

**Probable cause** A failure occurred when the database server was trying to allocate dynamic memory.

#### **Encryption error: %1**

| Item              | Value                                   |
|-------------------|---|
| SQLCODE           | -895                                    |
| Constant          | SQLE_ENCRYPT_ERROR                      |
| SQLSTATE          | 08W66                                   |
| Sybase error code | 13589                                   |
| ODBC 2 State      | 08001                                   |
| ODBC 3 State      | 08001                                   |
| Parameter 1       | Description of the error that occurred. |

Probable cause An error occurred during encryption.

#### Error during backup: %1

| Item              | Value             |
|-------------------|-------------------|
| SQLCODE           | -697              |
| Constant          | SQLE_BACKUP_ERROR |
| SQLSTATE          | 08W46             |
| Sybase error code | 13720             |
| ODBC 2 State      | ERROR             |
| ODBC 3 State      | ERROR             |

Probable cause An error occurred during a BACKUP statement.

#### **Error in assignment**

|                | ltem              | Value  |
|----------------|-------------------|--|
|                | SQLCODE           | -641   |
|                | Constant          | SQLE_ERROR_IN_ASSIGNMENT                               |
|                | SQLSTATE          | 22005  |
|                | Sybase error code | 8205   |
|                | ODBC 2 State      | 22005  |
|                | ODBC 3 State      | 22018  |
|                |                   |  |
| Probable cause | In a GET DESCRIP  | TOR statement, the data type of the host variable must |

Probable causeIn a GET DESCRIPTOR statement, the data type of the host variable must<br/>correspond to the data type of the descriptor item.

#### Error number %1 for RAISERROR may not be less than 17000

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -296                           |
| Constant          | SQLE_ERROR_NUMBER_OUT_OF_RANGE |
| SQLSTATE          | 53W07                          |
| Sybase error code | 2732                           |
| ODBC 2 State      | 37000                          |
| ODBC 3 State      | 42000                          |
| Parameter 1       | Error number.                  |

**Probable cause** 

You supplied an invalid error number in a RAISERROR statement. The number must be greater than or equal to 17000.

#### Error opening cursor

|                | ltem                  | Value  |
|----------------|-----------------------|--|
|                | SQLCODE               | -171   |
|                | Constant              | SQLE_OPEN_CURSOR_ERROR                         |
|                | SQLSTATE              | 07003  |
|                | Sybase error code     | 102  |
|                | ODBC 2 State          | 24000  |
|                | ODBC 3 State          | 24000  |
|                |                       |  |
| Probable cause | You attempted to open | n a cursor on a statement that is not a SELECT |

statement or a CALL or EXEC statement.

\_

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -655                 |
| Constant          | SQLE_GEN_PARSE_ERROR |
| SQLSTATE          | 08W38                |
| Sybase error code | 13707                |
| ODBC 2 State      | 08001                |
| ODBC 3 State      | 08001                |
|                   |                      |

### **Probable cause** The connection string could not be parsed. The string or connection parameter file contains a syntax error.

#### Error writing to transaction log file

| ltem              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -107                   |
| Constant          | SQLE_ERROR_WRITING_LOG |
| SQLSTATE          | 08W17                  |
| Sybase error code | 3619                   |
| ODBC 2 State      | ERROR                  |
| ODBC 3 State      | ERROR                  |
|                   |                        |

**Probable cause** The database server got an I/O error writing the transaction log file. Perhaps the disk is full or the log file name is invalid.

#### Event '%1' already exists

| ltem              | Value                                  |
|-------------------|--|
| SQLCODE           | -772                                   |
| Constant          | SQLE_EVENT_ALREADY_EXISTS              |
| SQLSTATE          | WE002                                  |
| Sybase error code | 13782                                  |
| ODBC 2 State      | ERROR                                  |
| ODBC 3 State      | ERROR                                  |
| Parameter 1       | Name of the event that already exists. |
|                   | •                                      |

#### Probable cause

You have attempted to create an event with a name that already exists in SYS.SYSEVENT.

#### Event '%1' in use

| Item              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -835                              |
| Constant          | SQLE_EVENT_IN_USE                 |
| SQLSTATE          | WE009                             |
| Sybase error code | 13841                             |
| ODBC 2 State      | ERROR                             |
| ODBC 3 State      | ERROR                             |
| Parameter 1       | Name of the event that is in use. |
|                   |                                   |

Probable cause You have attempted to drop an event that is currently in use.

#### Event '%1' not found

| Item              | Value                                      |
|-------------------|--|
| SQLCODE           | -771                                       |
| Constant          | SQLE_EVENT_NOT_FOUND                       |
| SQLSTATE          | WE001                                      |
| Sybase error code | 13781                                      |
| ODBC 2 State      | ERROR                                      |
| ODBC 3 State      | ERROR                                      |
| Parameter 1       | Name of the event that could not be found. |
|                   | 1  |

**Probable cause** You have attempted to reference an event with a name that does not exist in SYS.SYSEVENT.

#### Exception occurred while loading Java SecurityManager

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -848                       |
| Constant          | SQLE_JAVA_SECMGR_EXCEPTION |
| SQLSTATE          | WJ028                      |
| Sybase error code | 13854                      |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |

### **Probable cause** A Java exception occurred while loading the Java SecurityManager for this connection.

#### Expression has unsupported data type

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -624                      |
| Constant          | SQLE_DATATYPE_NOT_ALLOWED |
| SQLSTATE          | WW009                     |
| Sybase error code | 10356                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |

**Probable cause** Either an external function or Java method is declared to have a parameter or result data type which is not supported, or a Java field reference with unsupported result type was attempted.

#### External login for server '%1' could not be found

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -712                           |
| Constant          | SQLE_OMNI_EXTLOGIN_NOT_FOUND   |
| SQLSTATE          | WO013                          |
| Sybase error code | 11221                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
| Parameter 1       | The name of the remote server. |
|                   |                                |

Probable cause An external login for the server and user does not exist.

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -134                       |
| Constant          | SQLE_NOT_IMPLEMENTED       |
| SQLSTATE          | 0A000                      |
| Sybase error code | 401                        |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |
| Parameter 1       | The unimplemented feature. |

#### Feature '%1' not implemented

**Probable cause** You attempted to carry out an operation or use a feature that is not implemented in this version of Adaptive Server Anywhere.

#### Feature not available with UltraLite

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -749                            |
| Constant          | SQLE_NOT_SUPPORTED_IN_ULTRALITE |
| SQLSTATE          | 0AW07                           |
| Sybase error code | 13762                           |
| ODBC 2 State      | 37000                           |
| ODBC 3 State      | 42000                           |

**Probable cause** You attempted to execute a statement or use a feature that is not supported in an UltraLite database. For example, UltraLite does not support statements that modify the schema of the database.

#### Field '%1' of class '%2' cannot be null

null.

|                | Item   | Value                                       |
|----------------|--|---|
|                | SQLCODE  | -649  |
|                | Constant   | SQLE_FIELD_CANNOT_BE_NULL                   |
|                | SQLSTATE   | WW015                                       |
|                | Sybase error code  | 13741                                       |
|                | ODBC 2 State   | ERROR                                       |
|                | ODBC 3 State   | ERROR                                       |
|                | Parameter 1  | The name of the field which cannot be null. |
|                | Parameter 2  | The name of the class which has the field.  |
|                |  |   |
| Probable cause | An attempt was made to store a SQL null value in a Java object field whas a Java type that cannot be null. For example, the Java int type cann |   |

# FOR UPDATE has been incorrectly specified for a READ ONLY cursor.

|   | ltem              | Value   |
|---|-------------------|---|
|   | SQLCODE           | -813  |
|   | Constant          | SQLE_NON_UPDATEABLE_CURSOR  |
|   | SQLSTATE          | 42W36   |
|   | Sybase error code | 7301  |
|   | ODBC 2 State      | 42000   |
|   | ODBC 3 State      | 42000   |
| Probable cause You attempted to declare a cursor FOR UPDATE on a query that is not updatable. Queries that contain DISTINCT, GROUP BY, HAVING, or UNION, or that contain aggregate functions are read only. If the ANSI_UPDATE_CONSTRAINTS option is on, then queries that contai join are read only. If the query references a view then the view may be rupdatable. |                   | at contain DISTINCT, GROUP BY, HAVING, or<br>in aggregate functions are read only. If the<br>NSTRAINTS option is on, then queries that contain an |

#### Foreign key '%1' for table '%2' duplicates an existing foreign key

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -251                                  |
| Constant          | SQLE_DUPLICATE_FOREIGN_KEY            |
| SQLSTATE          | 52W06                                 |
| Sybase error code | 1909                                  |
| ODBC 2 State      | 42000                                 |
| ODBC 3 State      | 42000                                 |
| Parameter 1       | The role name of the new foreign key. |
| Parameter 2       | The table containing the foreign key. |
|                   |                                       |

#### **Probable cause** You attempted to define a foreign key that already exists.

#### Foreign key name '%1' not found

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -145                                  |
| Constant          | SQLE_FOREIGN_KEY_NAME_NOT_FOUND       |
| SQLSTATE          | 52W07                                 |
| Sybase error code | 102                                   |
| ODBC 2 State      | 37000                                 |
| ODBC 3 State      | 42000                                 |
| Parameter 1       | Name of the non-existing foreign key. |

**Probable cause** You misspelled the name of a foreign key, or the foreign key does not exist.

#### Format string argument number %1 is invalid

| Value                              |
|------------------------------------|
| -294                               |
| SQLE_INVALID_FORMAT_STRING_ARG_NUM |
| 53W08                              |
| 2749                               |
| 37000                              |
| 42000                              |
| Argument number.                   |
|                                    |

# Probable causeYou supplied an invalid argument number in the format string for a PRINT<br/>or RAISERROR statement. The number must be between 1 and 20 and must<br/>not exceed the number of arguments provided.

# Function or column reference to '%1' in the ORDER BY clause is invalid

| _ | Item              | Value  |
|---|-------------------|--|
| - | SQLCODE           | -854   |
|   | Constant          | SQLE_INVALID_ORDERBY_COLUMN  |
|   | SQLSTATE          | 42W65  |
|   | Sybase error code | 104  |
|   | ODBC 2 State      | 37000  |
|   | ODBC 3 State      | 42000  |
|   | Parameter 1       | Name of the column referenced directly, or in an expression, in the ORDER BY clause. |

**Probable cause** You specified a function or column reference in the ORDER BY clause that is semantically invalid. For example, for DISTINCT queries the ORDER BY clause may only refer to items in the query's SELECT list.

### Function or column reference to '%1' must also appear in a GROUP BY

|   | ltem              | Value   |
|---|-------------------|---|
| _ | SQLCODE           | -149  |
|   | Constant          | SQLE_INVALID_GROUP_SELECT   |
|   | SQLSTATE          | 53003   |
|   | Sybase error code | 7321  |
|   | ODBC 2 State      | 37000   |
|   | ODBC 3 State      | 42000   |
|   | Parameter 1       | Name of the column referenced directly, or in an expression, that must be in the GROUP BY clause. |

Probable cause You used a non-aggregate function or column reference in the select list or in a nested query block that does not appear in the GROUP BY clause. In a query using GROUP BY, select list items that are not aggregate functions must also appear in the GROUP BY clause. If the select list item is a column reference or an alias, you may add the column name or alias to the GROUP BY clause. If the select list item is a scalar function, ensure that the function's arguments in the GROUP BY clause match exactly with those in the select list. In some cases, you may want to use the MAX function on the column name (or another aggregate function) instead of adding the column to the GROUP BY clause.

#### GRANT of column permission on view not allowed

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -635                           |
| Constant          | SQLE_NO_COLUMN_PERMS_FOR_VIEWS |
| SQLSTATE          | 52W22                          |
| Sybase error code | 102                            |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |

Probable cause You cannot grant permissions on columns for views.

#### Grouped query contains more than one distinct aggregate function

| Value                           |
|---------------------------------|
| -863                            |
| SQLE_INVALID_DISTINCT_AGGREGATE |
| 42W70                           |
| 13867                           |
| 37000                           |
| 42000                           |
|                                 |

**Probable cause** Two or more DISTINCT aggregate functions were specified in the same grouped query. Any query block can only contain at most one DISTINCT aggregate function.

#### Host variables may not be used within a batch

| ltem              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -807                   |
| Constant          | SQLE_HOSTVARS_IN_BATCH |
| SQLSTATE          | 07W07                  |
| Sybase error code | 13817                  |
| ODBC 2 State      | ERROR                  |
| ODBC 3 State      | ERROR                  |
|                   |                        |

**Probable cause** You have attempted to execute a batch which contains host variable references. Host variables are not supported within a batch.

| Item              | Value             |
|-------------------|-------------------|
| <br>SQLCODE       | -305              |
| Constant          | SQLE_DEVICE_ERROR |
| SQLSTATE          | 40W04             |
| Sybase error code | 3013              |
| ODBC 2 State      | ERROR             |

ERROR

#### I/O error %1 -- transaction rolled back

ODBC 3 State

Probable causeAdaptive Server Anywhere has detected a problem with your hard disk. A<br/>ROLLBACK WORK statement has been automatically executed.

#### Identifier '%1' too long

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -250                     |
| Constant          | SQLE_IDENTIFIER_TOO_LONG |
| SQLSTATE          | 54003                    |
| Sybase error code | 103                      |
| ODBC 2 State      | 37000                    |
| ODBC 3 State      | 42000                    |
| Parameter 1       | The identifier in error. |

Probable cause An identifier is longer than 128 characters.

#### Identity attribute mismatch for column '%1'

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -725                        |
| Constant          | SQLE_OMNI_IDENTITY_MISMATCH |
| SQLSTATE          | WO019                       |
| Sybase error code | 11212                       |
| ODBC 2 State      | ОК                          |
| ODBC 3 State      | ОК                          |
| Parameter 1       | The name of the column.     |
|                   |                             |

Probable cause

The identity attribute of the column specified in the 'CREATE EXISTING' statement differs from the identity attribute of the actual column.

#### Illegal cursor operation attempt

|                | Item   | Value                     |
|----------------|--|---------------------------|
|                | SQLCODE  | -187                      |
|                | Constant   | SQLE_CURSOROP_NOT_ALLOWED |
|                | SQLSTATE   | 09W02                     |
|                | Sybase error code  | 9526                      |
|                | ODBC 2 State   | 07005                     |
|                | ODBC 3 State   | 07005                     |
|                |  |                           |
| Probable cause | You attempted an illegal cursor operation. For example, you may be<br>attempting to OPEN a cursor for a statement that is neither a SELECT nor a<br>BATCH. |                           |

| Illegal reference to correlation name '% | %1' in ON condition |
|--|---------------------|
|--|---------------------|

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -824  |
| Constant          | SQLE_INVALID_CORRELATION_NAME_REFERE NCE              |
| SQLSTATE          | 42U01   |
| Sybase error code | 13830   |
| ODBC 2 State      | S0002   |
| ODBC 3 State      | 42S02   |
| Parameter 1       | The correlation name which is incorrectly referenced. |

### **Probable cause** Your query contains a reference in an table expression's ON condition to a correlation name that is not contained in that table expression.

#### Illegal user selectivity estimate specified

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | 118                        |
| Constant          | SQLE_INVALID_USER_ESTIMATE |
| SQLSTATE          | 01W16                      |
| Sybase error code | 13617                      |
| ODBC 2 State      | 01000                      |
| ODBC 3 State      | 01000                      |

## **Probable cause** You specified a user selectivity estimate that is either not a literal constant or is outside the range 0.0 to 100.0 (estimates are specified as percentages). The estimate has been ignored.

#### Incomplete transactions prevent transaction log renaming

| ltem              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -242                              |
| Constant          | SQLE_BACKUP_CANNOT_RENAME_LOG_YET |
| SQLSTATE          | WB003                             |
| Sybase error code | 3206                              |
| ODBC 2 State      | ERROR                             |
| ODBC 3 State      | ERROR                             |
|                   |                                   |

Probable causeThe last page in the transaction log was read by a call to db\_backup. One or<br/>more currently active connections have partially completed transactions,<br/>preventing the transaction log file from being renamed. Reissue the<br/>db\_backup call.

#### Incorrect or missing encryption key

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -840                    |
| Constant          | SQLE_BAD_ENCRYPTION_KEY |
| SQLSTATE          | 08W62                   |
| Sybase error code | 16846                   |
| ODBC 2 State      | 08001                   |
| ODBC 3 State      | 08001                   |

**Probable cause** The database is encrypted with a key. There was no key given to start the database, or the key given was incorrect.

#### Incorrect store DLL (%1) version.

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -711                        |
| Constant          | SQLE_STORE_VERSION_MISMATCH |
| SQLSTATE          | 08W47                       |
| Sybase error code | 13701                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
|                   |                             |

| Probable cause | The store and server DLL versions do not match. |
|----------------|---|
|----------------|---|

#### Index '%1' can not be clustered

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -878  |
| Constant          | SQLE_CLUSTERED_INDEX_NOT_ALLOWED                    |
| SQLSTATE          | 42W74   |
| Sybase error code | 13889   |
| ODBC 2 State      | 42000   |
| ODBC 3 State      | 42000   |
| Parameter 1       | Name of the index that could not be made clustered. |
|                   |   |

**Probable cause** You attempted to create a clustered index (including key indexes) but the new index cannot be created, e.g., because the table already has a clustered index.

#### Index '%1' for table '%2' would not be unique

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | -196  |
| Constant          | SQLE_INDEX_NOT_UNIQUE                       |
| SQLSTATE          | 23505                                       |
| Sybase error code | 548   |
| ODBC 2 State      | 23000                                       |
| ODBC 3 State      | 23000                                       |
| Parameter 1       | Name of the index that would not be unique. |
| Parameter 2       | Name of the table that contains the index.  |
|                   |   |

## **Probable cause** You attempted to insert or update a row that has the same value as another row in some column, and there is a constraint that does not allow two rows to have the same value in that column.

#### Index name '%1' is ambiguous

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -678                         |
| Constant          | SQLE_AMBIGUOUS_INDEX_NAME    |
| SQLSTATE          | 52W40                        |
| Sybase error code | 1921                         |
| ODBC 2 State      | S0011                        |
| ODBC 3 State      | 42S11                        |
| Parameter 1       | Name of the ambiguous index. |
|                   |                              |

### **Probable cause** A statement has referred to an index name which is not unique. Preface the index name by a table and/or owner name.

#### Index name '%1' not unique

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -111                       |
| Constant          | SQLE_INDEX_NAME_NOT_UNIQUE |
| SQLSTATE          | 52W04                      |
| Sybase error code | 1921                       |
| ODBC 2 State      | S0011                      |
| ODBC 3 State      | 42S11                      |
| Parameter 1       | Name of the invalid index. |
|                   |                            |

**Probable cause** You attempted to create an index with the same name as an existing index.

#### Index type specification of '%1' is invalid

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -650                    |
| Constant          | SQLE_INVALID_INDEX_TYPE |
| SQLSTATE          | WW016                   |
| Sybase error code | 13704                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |

#### Probable cause

IQ index types can be specified for IQ indexes only.

#### Input parameter index out of range

| ltem              | Value                |  |
|-------------------|----------------------|--|
| SQLCODE           | -689                 |  |
| Constant          | SQLE_BAD_PARAM_INDEX |  |
| SQLSTATE          | WJ005                |  |
| Sybase error code | 13717                |  |
| ODBC 2 State      | ERROR                |  |
| ODBC 3 State      | ERROR                |  |

#### Probable cause

The range for valid parameters is from 1 up to the number of host variables specified in the prepared/callable statement.

#### **INSERT/DELETE** on cursor can modify only one table

| ltem              | Value               |
|-------------------|---------------------|
| SQLCODE           | -199                |
| Constant          | SQLE_ONLY_ONE_TABLE |
| SQLSTATE          | 09W04               |
| Sybase error code | 102                 |
| ODBC 2 State      | 37000               |
| ODBC 3 State      | 42000               |

# **Probable cause** You attempted to insert into a cursor and have specified values for more than one table; or you attempted to delete from a cursor that involves a join. Insert into one table at a time. For DELETE, use the FROM clause to specify which table you wish to delete from.

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -686                            |
| Constant          | SQLE_JAVA_VM_INSUFFICIENT_CACHE |
| SQLSTATE          | WP012                           |
| Sybase error code | 13876                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |
|                   |                                 |

#### Insufficient cache to start Java virtual machine

**Probable cause** Insufficient cache was available to start the Java virtual machine. Restart the engine with a larger cache size.

#### Integrated login failed

|                   | ltem              | Value                        |
|-------------------|-------------------|------------------------------|
|                   | SQLCODE           | -245                         |
|                   | Constant          | SQLE_INTEGRATED_LOGON_FAILED |
|                   | SQLSTATE          | 28W04                        |
|                   | Sybase error code | 13691                        |
|                   | ODBC 2 State      | 28000                        |
|                   | ODBC 3 State      | 28000                        |
|                   |                   |                              |
| ale alela a accas | <b>T</b>          |                              |

**Probable cause** The integrated login failed. You may not have a system account on the server machine.

#### Integrated logins are not permitted

|          | ltem              | Value   |
|----------|-------------------|---|
|          | SQLCODE           | -205  |
|          | Constant          | SQLE_INVALID_STANDARD_LOGON                   |
|          | SQLSTATE          | 28W02   |
|          | Sybase error code | 13689   |
|          | ODBC 2 State      | 28000   |
|          | ODBC 3 State      | 28000   |
|          |                   |   |
| le cause | The LOGIN_MODI    | E database option is set to STANDARD, and you |

 Probable cause
 The LOGIN\_MODE database option is set to STANDARD, and you attempted an integrated login. Change the option setting or supply an explicit user ID.

#### Integrated logins are not supported for this database

|                | ltem               | Value  |
|----------------|--------------------|--|
|                | SQLCODE            | -246   |
|                | Constant           | SQLE_INTEGRATED_LOGON_UNSUPPORTED  |
|                | SQLSTATE           | 28W05  |
|                | Sybase error code  | 13694  |
|                | ODBC 2 State       | 28000  |
|                | ODBC 3 State       | 28000  |
|                |                    |  |
| Probable cause | SYS.SYSLOGIN table | s an older database and does not have a<br>e to map integrated login IDs to database user IDs. You<br>tabase to use integrated logins. |

Ρ

#### Integrated logins are required, standard logins are not permitted

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -206                          |
| Constant          | SQLE_INVALID_INTEGRATED_LOGON |
| SQLSTATE          | 28W03                         |
| Sybase error code | 13690                         |
| ODBC 2 State      | 28000                         |
| ODBC 3 State      | 28000                         |
|                   |                               |

Probable cause The LOGIN\_MODE database option is set to INTEGRATED, and you attempted a standard login. Change the option setting or use an integrated login.

#### Internal database error %1 -- transaction rolled back

| Item              | Value                        |  |
|-------------------|------------------------------|--|
| SQLCODE           | -301                         |  |
| Constant          | SQLE_DATABASE_ERROR          |  |
| SQLSTATE          | 40W01                        |  |
| Sybase error code | 13665                        |  |
| ODBC 2 State      | ERROR                        |  |
| ODBC 3 State      | ERROR                        |  |
| Parameter 1       | Identification of the error. |  |
|                   | •                            |  |

## **Probable cause** An internal database error occurred. If it can be reproduced, it should be reported to iAnywhere Solutions. A ROLLBACK WORK statement has been automatically executed.

#### Internal rollback log corrupted

| ltem              | Value              |
|-------------------|--------------------|
| SQLCODE           | -311               |
| Constant          | SQLE_LOG_CORRUPTED |
| SQLSTATE          | WI004              |
| Sybase error code | 932                |
| ODBC 2 State      | ERROR              |
| ODBC 3 State      | ERROR              |
|                   |                    |

## **Probable cause** While processing a COMMIT or ROLLBACK, corruption was found in the internal rollback log. This is a fatal internal error.

#### Invalid absolute or relative offset in FETCH

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -263                        |
| Constant          | SQLE_INVALID_FETCH_POSITION |
| SQLSTATE          | 42W25                       |
| Sybase error code | 6259                        |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |

**Probable cause** You specified an offset in a FETCH that was invalid or NULL.

#### Invalid class byte code

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -670                     |
| Constant          | SQLE_BAD_CLASS_BYTE_CODE |
| SQLSTATE          | WP005                    |
| Sybase error code | 13746                    |
| ODBC 2 State      | ERROR                    |
| ODBC 3 State      | ERROR                    |

**Probable cause** A binary expression passed to the INSTALL JAVA statement was not a valid Java class.

#### Invalid column number

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -159                       |
| Constant          | SQLE_INVALID_COLUMN_NUMBER |
| SQLSTATE          | 42W13                      |
| Sybase error code | 182                        |
| ODBC 2 State      | 42000                      |
| ODBC 3 State      | 42000                      |
|                   | •                          |

**Probable cause** You gave an invalid column number, or the column you are looking for is in a different table.

#### Invalid comparison

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -710                    |
| Constant          | SQLE_INVALID_COMPARISON |
| SQLSTATE          | 52W25                   |
| Sybase error code | 13749                   |
| ODBC 2 State      | 37000                   |
| ODBC 3 State      | 42000                   |

**Probable cause** An attempt was made to compare two arguments that do not support comparison. For example, it is not valid to compare a Java object with another Java object, unless the class of the object supports a valid compareTo() method.

#### Invalid data conversion

| _ | Item              | Value               |
|---|-------------------|---------------------|
|   | SQLCODE           | 103                 |
|   | Constant          | SQLE_CANNOT_CONVERT |
|   | SQLSTATE          | 01W03               |
|   | Sybase error code | 518                 |
|   | ODBC 2 State      | 01S01               |
|   | ODBC 3 State      | 01S01               |

# **Probable cause** The database could not convert a value to the required type. The value being converted was either supplied to the database on an insert, update or as a host bind variable, or was a value retrieved from the database into a host variable or SQLDA.

## Invalid data conversion: NULL was inserted for column '%1' on line %2.

| Item              | Value  |
|-------------------|--|
| SQLCODE           | 124  |
| Constant          | SQLE_CANNOT_CONVERT_LOAD_TABLE   |
| SQLSTATE          | 01W01  |
| Sybase error code | 13886  |
| ODBC 2 State      | 07006  |
| ODBC 3 State      | 07006  |
| Parameter 1       | Name of the column where NULL was inserted.                                |
| Parameter 2       | Line number of the data file where the invalid data conversion took place. |

## Probable causeThe database could not convert a value to the required type. The value being<br/>converted was supplied to the database in a data file and inserted using<br/>LOAD TABLE. A NULL value has been inserted into the column.

#### Invalid data type for column in WRITETEXT or READTEXT

| Item              | Value                            |
|-------------------|----------------------------------|
| SQLCODE           | -609                             |
| Constant          | SQLE_INVALID_TEXT_IMAGE_DATATYPE |
| SQLSTATE          | 53W09                            |
| Sybase error code | 7139                             |
| ODBC 2 State      | ERROR                            |
| ODBC 3 State      | ERROR                            |
|                   | •                                |

### **Probable cause** You referenced a column in a WRITETEXT or READTEXT statement that is not defined for storing text or image data.

#### Invalid database page size

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -644                   |
| Constant          | SQLE_PAGE_SIZE_INVALID |
| SQLSTATE          | 08W32                  |
| Sybase error code | 927                    |
| ODBC 2 State      | 42000                  |
| ODBC 3 State      | 42000                  |
|                   |                        |

## **Probable cause** You attempted to create a database with an invalid page size. The page size for an Adaptive Server Anywhere database must be either 1024, 2048, or 4096 bytes.

#### Invalid database server command line

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -81                       |
| Constant          | SQLE_INVALID_COMMAND_LINE |
| SQLSTATE          | 08W08                     |
| Sybase error code | 5864                      |
| ODBC 2 State      | 08001                     |
| ODBC 3 State      | 08001                     |

### **Probable cause** It was not possible to start the database server because the command line was invalid.

#### Invalid day of week or month '%1' for event '%2'

| Item              | Value                                    |
|-------------------|--|
| SQLCODE           | -791                                     |
| Constant          | SQLE_INVALID_EVENT_DAY                   |
| SQLSTATE          | WE005                                    |
| Sybase error code | 13801                                    |
| ODBC 2 State      | ERROR                                    |
| ODBC 3 State      | ERROR                                    |
| Parameter 1       | Day-of-week name or day-of-month number. |
| Parameter 2       | Name of the event being scheduled.       |
|                   |  |

### **Probable cause** You have attempted to create a schedule with an invalid day-of-week name or day-of-month number.

#### Invalid descriptor index

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -640                          |
| Constant          | SQLE_INVALID_DESCRIPTOR_INDEX |
| SQLSTATE          | 07009                         |
| Sybase error code | 8201                          |
| ODBC 2 State      | S1002                         |
| ODBC 3 State      | 07009                         |

#### Invalid escape character '%1'

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -629                     |
| Constant          | SQLE_INVALID_ESCAPE_CHAR |
| SQLSTATE          | 22019                    |
| Sybase error code | 7707                     |
| ODBC 2 State      | S1000                    |
| ODBC 3 State      | 22019                    |
|                   |                          |

**Probable cause** The escape character string length must be exactly one.

#### Invalid escape sequence '%1'

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -630                    |
| Constant          | SQLE_INVALID_ESCAPE_SEQ |
| SQLSTATE          | 22025                   |
| Sybase error code | 7705                    |
| ODBC 2 State      | S1000                   |
| ODBC 3 State      | 22025                   |
| Parameter 1       | The escaped character   |
|                   | 1                       |

**Probable cause** A LIKE pattern contains an invalid use of the escape character. The escape character may only precede the special characters '%', '\_', '[', and the escape character itself.

#### Invalid expression in WHERE clause of Transact-SQL outer join

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -680                            |
| Constant          | SQLE_INVALID_TSQL_OJ_EXPRESSION |
| SQLSTATE          | 52W23                           |
| Sybase error code | 301                             |
| ODBC 2 State      | 37000                           |
| ODBC 3 State      | 42000                           |

**Probable cause** An expression in the WHERE clause of a query which uses Transact-SQL syntax contains a comparison of a column from the null-supplying table with a subquery or an expression which references a column from another table.

#### Invalid expression near '%1'

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -156                    |
| Constant          | SQLE_EXPRESSION_ERROR   |
| SQLSTATE          | 42W08                   |
| Sybase error code | 401                     |
| ODBC 2 State      | 37000                   |
| ODBC 3 State      | 42000                   |
| Parameter 1       | The invalid expression. |
|                   |                         |

**Probable cause** You supplied an expression which the database server cannot understand. For example, you may have tried to add two dates.

#### Invalid host variable

| ltem              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -155                  |
| Constant          | SQLE_VARIABLE_INVALID |
| SQLSTATE          | 42W07                 |
| Sybase error code | 7201                  |
| ODBC 2 State      | 37000                 |
| ODBC 3 State      | 42000                 |

**Probable cause** You supplied an invalid host variable to the database using the C language interface. You may have supplied the variable as a host variable or through a SQLDA.

#### Invalid IQ database command line option or parameter value: %1

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -744                         |
| Constant          | SQLE_IQ_INVALID_COMMAND_LINE |
| SQLSTATE          | 08W51                        |
| Sybase error code | 13757                        |
| ODBC 2 State      | 08001                        |
| ODBC 3 State      | 08001                        |
|                   | •                            |

**Probable cause** An invalid command line option was used. The option began with '-iq', but is either invalid or contained a bad parameter.

#### Invalid jar file

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -730   |
| Constant          | SQLE_BAD_JAR_FILE  |
| SQLSTATE          | WP010  |
| Sybase error code | 13737  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |

#### **Probable cause**

A file passed to the INSTALL JAVA statement was not a valid jar file.

#### Invalid JDBC resultset concurrency

| Item  | Value  |
|---|--|
| SQLCODE   | -748   |
| Constant  | SQLE_JDBC_INVALID_RESULTSET_CONCURREN<br>CY                            |
| SQLSTATE  | WJ018  |
| Sybase error code   | 13761  |
| ODBC 2 State  | ERROR  |
| ODBC 3 State  | ERROR  |
| Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State | SQLE_JDBC_INVALID_RESULTSET_CONCURREN<br>CY<br>WJ018<br>13761<br>ERROR |

Probable cause An invalid resultset concurrency was used when creating a JDBC statement.

#### Invalid JDBC resultset type

| ltem              | Value                            |
|-------------------|----------------------------------|
| SQLCODE           | -747                             |
| Constant          | SQLE_JDBC_INVALID_RESULTSET_TYPE |
| SQLSTATE          | WJ017                            |
| Sybase error code | 13760                            |
| ODBC 2 State      | ERROR                            |
| ODBC 3 State      | ERROR                            |
|                   |                                  |

Probable cause An invalid resultset type was used when creating a JDBC statement.

#### Invalid join type used with Transact-SQL outer join

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -681                        |
| Constant          | SQLE_INVALID_TSQL_JOIN_TYPE |
| SQLSTATE          | 52W24                       |
| Sybase error code | 305                         |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |

**Probable cause** An invalid join type was used with a query that contains Transact-SQL outer join comparison operators.

#### Invalid local database switch

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -79                       |
| Constant          | SQLE_INVALID_LOCAL_OPTION |
| SQLSTATE          | 08W25                     |
| Sybase error code | 5864                      |
| ODBC 2 State      | 08001                     |
| ODBC 3 State      | 08001                     |

Probable cause An invalid database switch was found in the DBS (DatabaseSwitches) connection parameter.

#### Invalid operation on a closed '%1'

| Item |                   | Value                           |  |
|------|-------------------|---------------------------------|--|
|      | SQLCODE           | -696                            |  |
|      | Constant          | SQLE_JDBC_OBJ_CLOSED            |  |
|      | SQLSTATE          | WJ010                           |  |
|      | Sybase error code | 13605                           |  |
|      | ODBC 2 State      | ERROR                           |  |
|      | ODBC 3 State      | ERROR                           |  |
|      | Parameter 1       | Java class of the closed object |  |
|      |                   |                                 |  |

Probable cause An illegal attempt was made to access a closed JDBC object.

#### Invalid operation on a closed '%1'

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -714                            |
| Constant          | SQLE_JNAT_OBJ_CLOSED            |
| SQLSTATE          | WJ014                           |
| Sybase error code | 13609                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |
| Parameter 1       | Java class of the closed object |
|                   | •                               |

Probable cause An illegal attempt was made to access a closed native Java object.

#### Invalid option '%1' -- no PUBLIC setting exists

| Item              | Value                       |  |
|-------------------|-----------------------------|--|
| SQLCODE           | -200                        |  |
| Constant          | SQLE_INVALID_OPTION         |  |
| SQLSTATE          | 42W16                       |  |
| Sybase error code | 155                         |  |
| ODBC 2 State      | 37000                       |  |
| ODBC 3 State      | 42000                       |  |
| Parameter 1       | Name of the invalid option. |  |

## Probable causeYou may have misspelled the name of an option in the SET OPTION<br/>statement. You can only define an option for a user if the database<br/>administrator has supplied a PUBLIC value for that option.

#### Invalid ORDER BY specification

| Item              | Value              |  |
|-------------------|--------------------|--|
| SQLCODE           | -152               |  |
| Constant          | SQLE_INVALID_ORDER |  |
| SQLSTATE          | 53005              |  |
| Sybase error code | 108                |  |
| ODBC 2 State      | 37000              |  |
| ODBC 3 State      | 42000              |  |

Probable causeEither you used an integer in an ORDER BY list and the integer is larger<br/>than the number of columns in the select list, or you specified an ORDER<br/>BY expression that is semantically invalid. For example, with UNION<br/>queries you can only use integers to specify an ordering of the result.

#### Invalid parameter

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -735                   |
| Constant          | SQLE_INVALID_PARAMETER |
| SQLSTATE          | 08W24                  |
| Sybase error code | 5864                   |
| ODBC 2 State      | 08004                  |
| ODBC 3 State      | 08004                  |

**Probable cause** An error occurred while evaluating a parameter.

#### Invalid prepared statement type

\_

| Item              | Value                       |  |
|-------------------|-----------------------------|--|
| SQLCODE           | -133                        |  |
| Constant          | SQLE_INVALID_STATEMENT_TYPE |  |
| SQLSTATE          | 07W03                       |  |
| Sybase error code | 13630                       |  |
| ODBC 2 State      | ERROR                       |  |
| ODBC 3 State      | ERROR                       |  |
|                   |                             |  |

### **Probable cause** This is an internal error. If it can be reproduced, it should be reported to iAnywhere Solutions.

#### Invalid REFERENCES clause in trigger definition

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -272                          |
| Constant          | SQLE_INVALID_TRIGGER_COL_REFS |
| SQLSTATE          | 52W12                         |
| Sybase error code | 102                           |
| ODBC 2 State      | 37000                         |
| ODBC 3 State      | 42000                         |

# Probable causeYou supplied an invalid REFERENCES clause in a trigger definition. You<br/>may have specified an OLD correlation name in a BEFORE INSERT trigger,<br/>or a NEW correlation name in an AFTER DELETE trigger. In both cases,<br/>the values do not exist and cannot be referenced.

#### Invalid scroll position '%1'

| Item              | Value                 |  |
|-------------------|-----------------------|--|
| SQLCODE           | -820                  |  |
| Constant          | SQLE_INVALID_POSITION |  |
| SQLSTATE          | 24504                 |  |
| Sybase error code | 13826                 |  |
| ODBC 2 State      | ERROR                 |  |
| ODBC 3 State      | ERROR                 |  |
|                   |                       |  |

Probable cause

You attempted to scroll to a position that is not supported. Scroll positions must be between -2147483647 and 2147483646.

#### Invalid setting for option '%1'

|                | Item   | Value                       |
|----------------|--|-----------------------------|
|                | SQLCODE  | -201                        |
|                | Constant   | SQLE_INVALID_OPTION_SETTING |
|                | SQLSTATE   | 42W17                       |
|                | Sybase error code  | 5849                        |
|                | ODBC 2 State   | 37000                       |
|                | ODBC 3 State   | 42000                       |
|                | Parameter 1  | Name of the invalid option. |
|                |  |                             |
| Probable cause | You supplied an invalid value for an option in the SET statement. Some options only allow numeric values, while other options only allow the value |                             |

"on" and "off".

#### Invalid SQL descriptor name

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -642                         |
| Constant          | SQLE_INVALID_DESCRIPTOR_NAME |
| SQLSTATE          | 33000                        |
| Sybase error code | 601                          |
| ODBC 2 State      | 33000                        |
| ODBC 3 State      | 33000                        |
| ODBC 3 State      | 33000                        |

**Probable cause** You attempted to deallocate a descriptor that has not been allocated.

#### Invalid SQL identifier

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -760                        |
| Constant          | SQLE_INVALID_SQL_IDENTIFIER |
| SQLSTATE          | 07W06                       |
| Sybase error code | 13771                       |
| ODBC 2 State      | 07001                       |
| ODBC 3 State      | 07W06                       |
|                   |                             |

Probable causeAn invalid identifier was supplied through the C language interface. For<br/>example, you may have supplied a NULL string for a cursor name.

#### Invalid sqllen field in SQLDA

\_

| ltem              | Value               |
|-------------------|---------------------|
| SQLCODE           | -856                |
| Constant          | SQLE_INVALID_SQLLEN |
| SQLSTATE          | 07W08               |
| Sybase error code | 13859               |
| ODBC 2 State      | HY090               |
| ODBC 3 State      | HY090               |

 Probable cause
 An invalid length was specified in a SQLDA sqllen field. All variable length types must have a non-negative length. DT\_BINARY and DT\_VARCHAR types must have length greater than one.

#### Invalid start date/time for event '%1'

| Item              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -793                               |
| Constant          | SQLE_INVALID_EVENT_START           |
| SQLSTATE          | WE007                              |
| Sybase error code | 13803                              |
| ODBC 2 State      | ERROR                              |
| ODBC 3 State      | ERROR                              |
| Parameter 1       | Name of the event being scheduled. |

**Probable cause** You have specified an event starting date or time which has already passed.

#### Invalid statement

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -130                   |
| Constant          | SQLE_INVALID_STATEMENT |
| SQLSTATE          | 07W02                  |
| Sybase error code | 13628                  |
| ODBC 2 State      | ERROR                  |
| ODBC 3 State      | ERROR                  |

**Probable cause** The statement identifier generated by a PREPARE passed to the database for a further operation is invalid.

#### Invalid TEXTPTR value used with WRITETEXT or READTEXT

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -608                       |
| Constant          | SQLE_INVALID_TEXTPTR_VALUE |
| SQLSTATE          | 22W03                      |
| Sybase error code | 7123                       |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |
|                   |                            |

| Probable cause | You supplied an invalid value as the TEXTPTR for a WRITETEXT or |
|----------------|---|
|                | READTEXT statement.   |

#### Invalid time '%1' for event '%2'

| Item              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -792                               |
| Constant          | SQLE_INVALID_EVENT_TIME            |
| SQLSTATE          | WE006                              |
| Sybase error code | 13802                              |
| ODBC 2 State      | ERROR                              |
| ODBC 3 State      | ERROR                              |
| Parameter 1       | Time value.                        |
| Parameter 2       | Name of the event being scheduled. |
|                   | •                                  |

Probable cause You have attempted to create a schedule with an invalid start or stop time.

#### Invalid type for field reference

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -94                          |
| Constant          | SQLE_INVALID_FIELD_REFERENCE |
| SQLSTATE          | WW014                        |
| Sybase error code | 13738                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |

 Probable cause
 An expression attempted to reference a field or a method of a non-Java value. Field references via '.' and '>>' are only valid when applied to Java objects.

#### Invalid type on DESCRIBE statement

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -161   |
| Constant          | SQLE_INVALID_DESCRIBE_TYPE   |
| SQLSTATE          | 07W01  |
| Sybase error code | 13634  |
| ODBC 2 State      | ОК   |
| ODBC 3 State      | ОК   |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |

Probable cause A Java type specified on a DESCRIBE statement has no corresponding SQL type.

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -150                        |
| Constant          | SQLE_AGGREGATES_NOT_ALLOWED |
| SQLSTATE          | 42W06                       |
| Sybase error code | 13204                       |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |

#### Invalid use of an aggregate function

Probable cause You attempted to use an aggregate function inappropriately. For example, a SELECT statement cannot contain an aggregate function within a predicate in the WHERE clause unless the aggregate function constitutes an outer reference. Other invalid uses include specifying an aggregate function in the SET clause of an UPDATE statement, or using an aggregate function in a CHECK constraint.

#### Invalid user ID or password

| Item              | Value              |
|-------------------|--------------------|
| SQLCODE           | -103               |
| Constant          | SQLE_INVALID_LOGON |
| SQLSTATE          | 28000              |
| Sybase error code | 4002               |
| ODBC 2 State      | 28000              |
| ODBC 3 State      | 28000              |

Probable cause You supplied an invalid user ID or an incorrect password.

#### Invalid user ID or password

| ltem              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -103                  |
| Constant          | SQLE_INVALID_PASSWORD |
| SQLSTATE          | 28000                 |
| Sybase error code | 4002                  |
| ODBC 2 State      | 28000                 |
| ODBC 3 State      | 28000                 |

#### Invalid user ID or password on preprocessed module

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -104                      |
| Constant          | SQLE_INVALID_MODULE_LOGON |
| SQLSTATE          | 28W01                     |
| Sybase error code | 4002                      |
| ODBC 2 State      | 28000                     |
| ODBC 3 State      | 28000                     |

**Probable cause** You specified an invalid user ID or password when a module was preprocessed.

| ltem              | Value  |
|-------------------|--|
| <br>SQLCODE       | -209   |
| Constant          | SQLE_INVALID_COLUMN_VALUE                              |
| SQLSTATE          | 23506  |
| Sybase error code | 548  |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 23000  |
| Parameter 1       | Name of the column that was assigned an invalid value. |
| Parameter 2       | Name of the table containing the column.               |
|                   |  |

#### Invalid value for column '%1' in table '%2'

**Probable cause** You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

#### Item '%1' already exists

| Item              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -110                                  |
| Constant          | SQLE_NAME_NOT_UNIQUE                  |
| SQLSTATE          | 52010                                 |
| Sybase error code | 12006                                 |
| ODBC 2 State      | S0001                                 |
| ODBC 3 State      | 42S01                                 |
| Parameter 1       | Name of the item that already exists. |

### **Probable cause** You attempted to create a file, table, view, column, foreign key, or publication with the same name as an existing one.

#### Jar '%1' not found

| Item              | Value              |
|-------------------|--------------------|
| SQLCODE           | -811               |
| Constant          | SQLE_JAR_NOT_FOUND |
| SQLSTATE          | 42W58              |
| Sybase error code | 13821              |
| ODBC 2 State      | 42000              |
| ODBC 3 State      | 42000              |
| Parameter 1       | Name of the jar.   |

**Probable cause** The jar with this name does not exist in SYS.SYSJAR.

#### Java class '%1' not found

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -810                      |
| Constant          | SQLE_JAVA_CLASS_NOT_FOUND |
| SQLSTATE          | 42W57                     |
| Sybase error code | 13820                     |
| ODBC 2 State      | 42000                     |
| ODBC 3 State      | 42000                     |
| Parameter 1       | Name of the Java class.   |
|                   |                           |

**Probable cause** The Java class with this name does not exist in SYS.SYSJAVACLASS.

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | -847  |
| Constant          | SQLE_JAVA_SECMGR_NOT_FOUND                  |
| SQLSTATE          | WJ027                                       |
| Sybase error code | 13853                                       |
| ODBC 2 State      | ERROR                                       |
| ODBC 3 State      | ERROR                                       |
| Parameter 1       | The class name of the Java SecurityManager. |
|                   | 1   |

### **Probable cause** The class specified is either not a SecurityManager subclass or cannot be found.

#### Java virtual machine could not be started

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -675                     |
| Constant          | SQLE_JAVA_VM_NOT_STARTED |
| SQLSTATE          | WP006                    |
| Sybase error code | 13747                    |
| ODBC 2 State      | ERROR                    |
| ODBC 3 State      | ERROR                    |

## **Probable cause** A problem was encountered starting the Java virtual machine. Possible problems include not enough memory, or incomplete installation of the Java runtime support classes.

#### Java VM heap exhausted at internal function: %1

|                | Item   | Value  |
|----------------|--|--|
|                | SQLCODE  | -165   |
|                | Constant   | SQLE_JAVA_VM_HEAP_EXHAUSTED                      |
|                | SQLSTATE   | WP008  |
|                | Sybase error code  | 13740  |
|                | ODBC 2 State   | ERROR  |
|                | ODBC 3 State   | ERROR  |
|                | Parameter 1  | The internal function is for debugging purposes. |
|                |  |  |
| Probable cause | The amount of space allocated for the Java VM is insufficient to continue allocating new objects. Increase the size by using: set option public.java_heap_size = nnnnnnn |  |

#### JDBC feature '%1' not supported

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -693                          |
| Constant          | SQLE_UNSUPPORTED_JDBC_FEATURE |
| SQLSTATE          | WJ007                         |
| Sybase error code | 13602                         |
| ODBC 2 State      | ERROR                         |
| ODBC 3 State      | ERROR                         |
| Parameter 1       | Name of the attempted feature |

**Probable cause** An attempt was made to use a feature of JDBC that is not supported.

| Item              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -742                              |
| Constant          | SQLE_JDBC_BATCH_EXECUTE_ABANDONED |
| SQLSTATE          | WJ015                             |
| Sybase error code | 13755                             |
| ODBC 2 State      | ERROR                             |
| ODBC 3 State      | ERROR                             |
|                   |                                   |

#### JDBC SAStatement batch execute abandoned

## **Probable cause** An error occurred when executing a statement in the batch. The rest of the statements in the batch will be abandoned.

#### JDK '%1' is not a supported JDK

| ltem              | Value                |
|-------------------|----------------------|
| SQLCODE           | -842                 |
| Constant          | SQLE_UNSUPPORTED_JDK |
| SQLSTATE          | WJ025                |
| Sybase error code | 13848                |
| ODBC 2 State      | ERROR                |
| ODBC 3 State      | ERROR                |
| Parameter 1       | A JDK version string |

# **Probable cause** Either the JDK version specified in the 'create database' statement is unsupported or the version in the manifest file of the JDK jar file is unsupported.

# Key constraint between temporary tables requires a primary key (not unique constraint)

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -865                           |
| Constant          | SQLE_INVALID_FOREIGN_KEY_INDEX |
| SQLSTATE          | 42R03                          |
| Sybase error code | 1709                           |
| ODBC 2 State      | 42000                          |
| ODBC 3 State      | 42000                          |

# Probable causeKey constraint between temporary tables requires a primary key (not unique<br/>constraint) if the database uses combined indexes. Change the definition of<br/>the primary table using ALTER TABLE or rebuild the database.

#### Label '%1' not found

| ltem              | Value                                      |
|-------------------|--|
| SQLCODE           | -262                                       |
| Constant          | SQLE_LABEL_NOT_FOUND                       |
| SQLSTATE          | 42W24                                      |
| Sybase error code | 133  |
| ODBC 2 State      | 37000                                      |
| ODBC 3 State      | 42000                                      |
| Parameter 1       | Name of the label that could not be found. |
|                   |  |

### **Probable cause** You reference a label in a LEAVE statement, but the label could not be found.

| Language '%1' is | not supported, | '%2' will k | be used |
|------------------|----------------|-------------|---------|
|------------------|----------------|-------------|---------|

| Item              | Value  |
|-------------------|--|
| SQLCODE           | 116  |
| Constant          | SQLE_UNSUPPORTED_LANGUAGE  |
| SQLSTATE          | 01W14  |
| Sybase error code | 13615  |
| ODBC 2 State      | 01000  |
| ODBC 3 State      | 01000  |
| Parameter 1       | Name of the language that was requested by the client.                 |
| Parameter 2       | Name of the language that the server will use to send message strings. |

**Probable cause** The language that the application requested is not supported by the server to which the application is connecting. Instead, the server will send message strings in the language stated.

#### Language extension

| Item  | Value                   |
|---|-------------------------|
| SQLCODE                                       | -135                    |
| Constant                                      | SQLE_LANGUAGE_EXTENSION |
| SQLSTATE                                      | 0AW01                   |
| Sybase error code                             | 401                     |
| ODBC 2 State                                  | 37000                   |
| ODBC 3 State                                  | ERROR                   |
| SQLSTATE<br>Sybase error code<br>ODBC 2 State | 0AW01<br>401<br>37000   |

**Probable cause** You used a SQL statement that may be valid in some versions of SQL, but not in Adaptive Server Anywhere.

#### Language extension detected in syntax

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | 107                           |
| Constant          | SQLE_SYNTAX_EXTENSION_WARNING |
| SQLSTATE          | 01W07                         |
| Sybase error code | 5703                          |
| ODBC 2 State      | 01000                         |
| ODBC 3 State      | 01000                         |

#### Probable cause

The statement you are executing contains extensions to ANSI 1992 Entry level SQL.

#### Memory error -- transaction rolled back

| ltem              | Value             |
|-------------------|-------------------|
| SQLCODE           | -309              |
| Constant          | SQLE_MEMORY_ERROR |
| SQLSTATE          | 40W08             |
| Sybase error code | 3013              |
| ODBC 2 State      | ERROR             |
| ODBC 3 State      | ERROR             |
|                   | •                 |

**Probable cause** The UltraLite runtime has received an unexpected error from the system calls being used to store the UltraLite database. For example, a write to persistent memory failed. This is an internal error and indicates faulty or corrupt persistent storage on the device. A ROLLBACK WORK statement has been automatically executed.

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -669                         |
| Constant          | SQLE_METHOD_CANNOT_BE_CALLED |
| SQLSTATE          | WJ001                        |
| Sybase error code | 13711                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
| Parameter 1       | The name of the method       |

#### Method '%1' cannot be called at this time

**Probable cause** The method cannot be called at this time. Check that the method is not being called out of order.

# Mismatch between external function platform specifier and current operating system

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -618                           |
| Constant          | SQLE_EXTERNAL_PLATFORM_FAILURE |
| SQLSTATE          | WW004                          |
| Sybase error code | 13675                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |

# **Probable cause** A call to an external entry point in a dynamically loaded module was qualified by an operating system which was not the operating system on which the server is currently executing.

#### Modifications not permitted for read-only database

| Value                   |
|-------------------------|
| -757                    |
| SQLE_READ_ONLY_DATABASE |
| 55W08                   |
| 13768                   |
| 42000                   |
| 42000                   |
|                         |

#### **Probable cause** You attempted an update operation on a database that was declared as readonly.

#### More columns are being dropped from table '%1' than are defined

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -124                          |
| Constant          | SQLE_TOO_MANY_COLUMNS_DELETED |
| SQLSTATE          | 42W44                         |
| Sybase error code | 207                           |
| ODBC 2 State      | 37000                         |
| ODBC 3 State      | 42000                         |
|                   |                               |

Probable causeThe number of columns in a table can never fall below one. Your ALTER<br/>TABLE has more drop/delete column clauses than the current number of<br/>columns in the table.

#### More information required

| Item              | Value          |
|-------------------|----------------|
| SQLCODE           | 112            |
| Constant          | SQLE_MORE_INFO |
| SQLSTATE          | 01W09          |
| Sybase error code | 13686          |
| ODBC 2 State      | 37000          |
| ODBC 3 State      | ОК             |

**Probable cause** More information is required to complete the request. This is used internally in the database interface library to process a unified login. It should not be returned to an application.

#### More than one table is identified as '%1'

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -139                            |
| Constant          | SQLE_CORRELATION_NAME_AMBIGUOUS |
| SQLSTATE          | 52012                           |
| Sybase error code | 7364                            |
| ODBC 2 State      | 37000                           |
| ODBC 3 State      | 42000                           |
| Parameter 1       | Ambiguous correlation name.     |
|                   | •                               |

## **Probable cause** You identified two tables in the same FROM clause with the same correlation name.

#### Must include primary key for table '%1' in the synchronization

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -778                        |
| Constant          | SQLE_PK_NOT_IN_SYNC_ARTICLE |
| SQLSTATE          | 5RW17                       |
| Sybase error code | 13788                       |
| ODBC 2 State      | 42000                       |
| ODBC 3 State      | 42S02                       |
| Parameter 1       | Name of the table           |

**Probable cause** The primary key of the table must be included in the synchronization entry.

#### Namespace heap exhausted at internal function: %1

|                | ltem   | Value  |
|----------------|--|--|
|                | SQLCODE  | -164   |
|                | Constant   | SQLE_NAMESPACE_HEAP_EXHAUSTED                    |
|                | SQLSTATE   | WP007  |
|                | Sybase error code  | 13739  |
|                | ODBC 2 State   | ERROR  |
|                | ODBC 3 State   | ERROR  |
|                | Parameter 1  | The internal function is for debugging purposes. |
|                |  |  |
| Probable cause | The amount of space allocated for the Java Namespace is insufficient to continue loading Java classes etc. Increase the size by using: set option public.java_namespace_size = nnnnnnn |  |

#### Need a dynamic library name

| Value                 |
|-----------------------|
| -619                  |
| SQLE_REQUIRE_DLL_NAME |
| WW005                 |
| 13676                 |
| ERROR                 |
| ERROR                 |
|                       |

**Probable cause** You must provide a library name specifier in the name of the external function to call.

#### No current row of cursor

| Item              | Value               |
|-------------------|---------------------|
| SQLCODE           | -197                |
| Constant          | SQLE_NO_CURRENT_ROW |
| SQLSTATE          | 24503               |
| Sybase error code | 560                 |
| ODBC 2 State      | 24000               |
| ODBC 3 State      | 24000               |
|                   | •                   |

**Probable cause** You attempted to perform an operation on the current row of a cursor, but the cursor is not positioned on a row. The cursor is before the first row of the cursor, after the last row, or is on a row that has since been deleted.

#### No database file specified

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -72  |
| Constant          | SQLE_NO_DATABASE_FILE  |
| SQLSTATE          | 08W39  |
| Sybase error code | 4001   |
| ODBC 2 State      | 08001  |
| ODBC 3 State      | 08001  |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |

#### Probable cause

The database server was started but there was no specified database file. The server is stopped.

#### No indicator variable provided for NULL result

| _ | Item              | Value             |
|---|-------------------|-------------------|
|   | SQLCODE           | -181              |
|   | Constant          | SQLE_NO_INDICATOR |
|   | SQLSTATE          | 22002             |
|   | Sybase error code | 13635             |
|   | ODBC 2 State      | ERROR             |
|   | ODBC 3 State      | ERROR             |
|   |                   |                   |

## **Probable cause** You tried to retrieve a value from the database that was NULL, but you did not provide an indicator variable for that value.

| ltem              | Value                                   |
|-------------------|---|
| SQLCODE           | -194                                    |
| Constant          | SQLE_INVALID_FOREIGN_KEY                |
| SQLSTATE          | 23503                                   |
| Sybase error code | 546                                     |
| ODBC 2 State      | 23000                                   |
| ODBC 3 State      | 23000                                   |
| Parameter 1       | Name of the foreign key.                |
| Parameter 2       | Name of the table with the foreign key. |
|                   | I                                       |

# Probable causeYou attempted to insert or update a row that has a foreign key for another<br/>table. The value for the foreign key is not NULL and there is not a<br/>corresponding value in the primary key

#### Not allowed while '%1' is using the database

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -211                         |
| Constant          | SQLE_MUST_BE_ONLY_CONNECTION |
| SQLSTATE          | 42W19                        |
| Sybase error code | 13652                        |
| ODBC 2 State      | 40001                        |
| ODBC 3 State      | 40001                        |

## **Probable cause** You attempted a data definition language operation that cannot be completed while another user is connected.

#### Not connected to a database

| Item              | Value              |
|-------------------|--------------------|
| SQLCODE           | -101               |
| Constant          | SQLE_NOT_CONNECTED |
| SQLSTATE          | 08003              |
| Sybase error code | 13622              |
| ODBC 2 State      | 08003              |
| ODBC 3 State      | 08003              |
|                   |                    |

#### Probable cause

You are not connected to a database, or you executed the DISCONNECT statement and have not connected to a database again.

#### Not enough fields allocated in SQLDA

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -182                 |
| Constant          | SQLE_SQLDA_TOO_SMALL |
| SQLSTATE          | 07002                |
| Sybase error code | 13636                |
| ODBC 2 State      | 07001                |
| ODBC 3 State      | 07002                |
|                   |                      |

**Probable cause** There are not enough fields in the SQLDA to retrieve all of the values requested.

# Not enough memory is allocated to the Java virtual machine for remote access

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -679                    |
| Constant          | SQLE_OMNI_MEMORY_CONFIG |
| SQLSTATE          | WO009                   |
| Sybase error code | 708                     |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
|                   | •                       |

**Probable cause** The Java heap size and Java name space configuration values in sysoptions must be increased to allow the loading of the Java classes used for remote access.

#### Not enough memory to start

| ltem              | Value          |
|-------------------|----------------|
| SQLCODE           | -86            |
| Constant          | SQLE_NO_MEMORY |
| SQLSTATE          | 08W13          |
| Sybase error code | 708            |
| ODBC 2 State      | S1001          |
| ODBC 3 State      | HY001          |

Probable cause The database server started, but stopped because there was not enough memory.

#### Not enough values for host variables

| Value                     |
|---------------------------|
| -188                      |
| SQLE_NOT_ENOUGH_HOST_VARS |
| 07001                     |
| 13638                     |
| 07002                     |
| 07002                     |
|                           |

#### Probable cause

You have not provided enough host variables for either the number of bind variables, or the statement, or the number of select list items.

#### Null attribute mismatch for column '%1'

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -724                    |
| Constant          | SQLE_OMNI_NULL_MISMATCH |
| SQLSTATE          | WO018                   |
| Sybase error code | 11211                   |
| ODBC 2 State      | ОК                      |
| ODBC 3 State      | ОК                      |
| Parameter 1       | The name of the column. |
|                   |                         |

**Probable cause** The null attribute of the column specified in the 'CREATE EXISTING' statement differs from the null attribute of the actual column.

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | 109                        |
| Constant          | SQLE_NULL_VALUE_ELIMINATED |
| SQLSTATE          | 01003                      |
| Sybase error code | 409                        |
| ODBC 2 State      | 01000                      |
| ODBC 3 State      | 01000                      |
|                   |                            |

## **Probable cause** The expression argument of the aggregate function evaluated to NULL for one or more rows.

#### Number of columns allowing NULLs exceeds limit

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -733                       |
| Constant          | SQLE_TOO_MANY_NULL_COLUMNS |
| SQLSTATE          | 23504                      |
| Sybase error code | 233                        |
| ODBC 2 State      | 23000                      |
| ODBC 3 State      | 23000                      |
|                   |                            |

**Probable cause** You attempted to create or modify a table definition such that the number of columns that allow nulls is now more than the limit on such columns. The limit is a function of database page size and is approximately 8\*(page\_size - 30).

# Number of columns defined for the view does not match SELECT statement

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -114                       |
| Constant          | SQLE_VIEW_DEFINITION_ERROR |
| SQLSTATE          | 53011                      |
| Sybase error code | 4409                       |
| ODBC 2 State      | 21S02                      |
| ODBC 3 State      | 21S02                      |

**Probable cause** You attempted to create a view, but the column list specified as part of the CREATE VIEW statement does not correspond to the list of items in the view's SELECT statement.

# OMNI cannot handle expressions involving remote tables inside stored procedures

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -823                         |
| Constant          | SQLE_OMNI_EXPRESSION_IN_PROC |
| SQLSTATE          | WO023                        |
| Sybase error code | 13829                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |

**Probable cause** OMNI encountered a complicated expression involving remote tables inside a stored procedure. OMNI cannot always deal with such expressions.

| Only PUBLIC settings are allowed for optio | n '%1' |
|--|--------|
|--|--------|

| Item              | Value               |
|-------------------|---------------------|
| SQLCODE           | -202                |
| Constant          | SQLE_NOT_PUBLIC_ID  |
| SQLSTATE          | 42W43               |
| Sybase error code | 13685               |
| ODBC 2 State      | 42000               |
| ODBC 3 State      | 42000               |
| Parameter 1       | Name of the option. |

**Probable cause** The option specified in the SET OPTION statement is PUBLIC only. You cannot define this option for any other user.

#### Only the DBA can set the option '%1'

\_

\_

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -204                     |
| Constant          | SQLE_OPTION_REQUIRES_DBA |
| SQLSTATE          | 42W46                    |
| Sybase error code | 5878                     |
| ODBC 2 State      | 42000                    |
| ODBC 3 State      | 42000                    |

**Probable cause** The option specified in the SET OPTION statement can only be set by a user having DBA authority.

#### Operation would cause a group cycle

| ltem              | Value            |
|-------------------|------------------|
| SQLCODE           | -122             |
| Constant          | SQLE_GROUP_CYCLE |
| SQLSTATE          | 42W02            |
| Sybase error code | 314              |
| ODBC 2 State      | 37000            |
| ODBC 3 State      | 42000            |

#### Probable cause

You attempted to add a member to group that would result in a member belonging to itself. The membership may be direct or indirect.

# Owner '%1' used in a qualified column reference does not match correlation name '%2'

|                | Item                  | Value  |
|----------------|-----------------------|--|
|                | SQLCODE               | -845   |
|                | Constant              | SQLE_INVALID_COLUMN_QUALIFICATION                      |
|                | SQLSTATE              | 42U02  |
|                | Sybase error code     | 13851  |
|                | ODBC 2 State          | S0002  |
|                | ODBC 3 State          | 42S02  |
|                | Parameter 1           | The owner name specified in the column reference.      |
|                | Parameter 2           | The correlation name which is incorrectly referenced.  |
| Probable cause | Vour quart containe a | qualified column reference to a table name, but either |

Probable causeYour query contains a qualified column reference to a table name, but either<br/>a correlation name has been used for that table, or the owner of the table does<br/>not match the owner name specified in the column reference. Remove the<br/>owner qualification, and qualify column references only by correlation name.

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -615                        |
| Constant          | SQLE_INVALID_PARAMETER_NAME |
| SQLSTATE          | 42W47                       |
| Sybase error code | 201                         |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |
|                   |                             |

#### Parameter '%1' not found in procedure '%2'

**Probable cause** You supplied a procedure parameter name that does not match a parameter for this procedure. Check the spelling of the parameter name.

#### Parameter name missing in call to procedure '%1'

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -639                        |
| Constant          | SQLE_PARAMETER_NAME_MISSING |
| SQLSTATE          | 42W42                       |
| Sybase error code | 201                         |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |
| Parameter 1       | The name of the procedure   |

**Probable cause** Positional arguments were specified after keyword arguments in a call to this procedure.

#### Parameter not registered as output parameter

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -671                      |
| Constant          | SQLE_PARAM_NOT_REGISTERED |
| SQLSTATE          | WJ002                     |
| Sybase error code | 13712                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
|                   | •                         |

## **Probable cause** The parameter must be registered as an output parameter before the value of the parameter can be obtained.

#### Parse error: %1

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -95                          |
| Constant          | SQLE_INVALID_PARSE_PARAMETER |
| SQLSTATE          | 08W49                        |
| Sybase error code | 5864                         |
| ODBC 2 State      | 08004                        |
| ODBC 3 State      | 08004                        |

**Probable cause** An error occurred while parsing a connection string.

#### Parse error: %1

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -754                  |
| Constant          | SQLE_INVALID_DSN_NAME |
| SQLSTATE          | 08W54                 |
| Sybase error code | 5864                  |
| ODBC 2 State      | 08004                 |
| ODBC 3 State      | 08004                 |

Probable cause An invalid data source name was used in the connection string.

#### Passthrough statement inconsistent with current passthrough

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -287                          |
| Constant          | SQLE_PASSTHROUGH_INCONSISTENT |
| SQLSTATE          | 5RW08                         |
| Sybase error code | 13649                         |
| ODBC 2 State      | S0002                         |
| ODBC 3 State      | 42S02                         |

Probable causePassthrough is additive, in that subsequent passthrough statements add to the<br/>list of users receiving passthrough. The passthrough statements must all be<br/>PASSTHROUGH ONLY or none should be PASSTHROUGH ONLY.

#### Password must be at least %1 characters

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -738                    |
| Constant          | SQLE_PASSWORD_TOO_SHORT |
| SQLSTATE          | 28000                   |
| Sybase error code | 573                     |
| ODBC 2 State      | 28000                   |
| ODBC 3 State      | 28000                   |
|                   |                         |

 
 Probable cause
 The password is shorter than that allowed by the current MIN\_PASSWORD\_LENGTH option setting. :EN

#### Plan can not be generated for this type of statement

| Value                         |
|-------------------------------|
| -894                          |
| SQLE_STMT_NOT_ALLOWED_IN_PLAN |
| 0AW14                         |
| 13589                         |
| ERROR                         |
| ERROR                         |
|                               |

Probable cause You tried to get the

You tried to get the execution plan for a statement type that is not supported.

#### Previous error lost prior to RESIGNAL

| <br>Item          | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -825                     |
| Constant          | SQLE_PREVIOUS_ERROR_LOST |
| SQLSTATE          | WP011                    |
| Sybase error code | 13831                    |
| ODBC 2 State      | ERROR                    |
| ODBC 3 State      | ERROR                    |
|                   |                          |

**Probable cause** A RESIGNAL statement in an exception handler of a stored procedure was executed but the context of the previous error was unavailable. A possible cause of this error is a SELECT statement which returns a result set in the exception handler.

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -119   |
| Constant          | SQLE_PRIMARY_KEY_COLUMN_DEFINED                        |
| SQLSTATE          | 52009  |
| Sybase error code | 1909   |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Name of the column that is already in the primary key. |
|                   | 1  |

#### Primary key column '%1' already defined

**Probable cause** You listed the same column name twice in the definition of a primary key.

# Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'

|                | ltem                                       | Value   |
|----------------|--|---|
|                | SQLCODE                                    | -198  |
|                | Constant                                   | SQLE_PRIMARY_KEY_VALUE_REF  |
|                | SQLSTATE                                   | 23W05   |
|                | Sybase error code                          | 547   |
|                | ODBC 2 State                               | 23000   |
|                | ODBC 3 State                               | 23000   |
|                | Parameter 1                                | The name of the table containing the row being modified.          |
|                | Parameter 2                                | The name of the foreign index (or role) of the referencing table. |
|                | Parameter 3                                | The name of the foreign table referencing the primary row.        |
| Probable cause | You attempted to dele referenced elsewhere | te or modify a row whose primary key value is in the database.    |

#### Primary key for table '%1' is not unique

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -193  |
| Constant          | SQLE_PRIMARY_KEY_NOT_UNIQUE                       |
| SQLSTATE          | 23W01   |
| Sybase error code | 2601  |
| ODBC 2 State      | 23000   |
| ODBC 3 State      | 23000   |
| Parameter 1       | Name of the table where the problem was detected. |
|                   |   |

# Probable causeYou attempted to add a new row to a table, but the new row has the same<br/>primary key as an existing row. The database has not added the incorrect row<br/>to the database. For example, you might have added a student with student<br/>number 86004 and there is already a row for a student with that number.

#### Procedure '%1' is no longer valid

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -836                           |
| Constant          | SQLE_PROCEDURE_NO_LONGER_VALID |
| SQLSTATE          | 42W63                          |
| Sybase error code | 13842                          |
| ODBC 2 State      | 37000                          |
| ODBC 3 State      | 42000                          |
| Parameter 1       | Name of the procedure.         |

## **Probable cause** A procedure definition cannot be loaded from the catalog. Check for tables or columns which have been renamed or which may be reserved words.

#### Procedure '%1' not found

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -265   |
| Constant          | SQLE_PROCEDURE_NOT_FOUND                       |
| SQLSTATE          | 52W09  |
| Sybase error code | 504  |
| ODBC 2 State      | S0002  |
| ODBC 3 State      | 42S02  |
| Parameter 1       | Name of the procedure that could not be found. |
|                   | •  |

**Probable cause** You misspelled the name of a procedure, or you did not qualify a procedure name with a user name.

#### Procedure '%1' terminated with unhandled exception '%2'

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -91   |
| Constant          | SQLE_UNHANDLED_JAVA_EXCEPTION                                     |
| SQLSTATE          | WP001   |
| Sybase error code | 13735   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | The name of the procedure which returned the unhandled exception. |
| Parameter 2       | The fully qualified Java class name of the unhandled exception.   |

## **Probable cause** A Java procedure terminated with an active exception, and this exception is reflected in SQL as an error status.

#### **Procedure has completed**

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | 105  |
| Constant          | SQLE_PROCEDURE_COMPLETE  |
| SQLSTATE          | 01W05  |
| Sybase error code | 13618  |
| ODBC 2 State      | ОК   |
| ODBC 3 State      | ОК   |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |

# Probable causeThere are no more result sets available for this procedure. An OPEN or a<br/>RESUME statement may have caused the procedure to execute to<br/>completion. You may have attempted to RESUME a cursor on a SELECT<br/>statement.

#### Procedure in use by '%1'

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -215                  |
| Constant          | SQLE_PROCEDURE_IN_USE |
| SQLSTATE          | 42W23                 |
| Sybase error code | 3702                  |
| ODBC 2 State      | 40001                 |
| ODBC 3 State      | 40001                 |
| Parameter 1       | Name of user.         |

### **Probable cause** You attempted to DROP a procedure that is being used by other active users of the database.

#### Procedure or trigger calls have nested too deeply

| E_NESTING_TOO_DEEP |
|--------------------|
| 29                 |
|                    |
| DR                 |
| DR                 |
|                    |

**Probable cause** You may have defined a procedure or trigger that causes unlimited recursion.

#### Publication '%1' not found

| Value  |
|--|
| -280   |
| SQLE_PUBLICATION_NOT_FOUND                       |
| 5RW01  |
| 13642  |
| S0002  |
| 42S02  |
| Name of the publication that could not be found. |
|  |

**Probable cause** You misspelled the name of a publication, or you did not qualify a publication name with a user name.

#### **RAISERROR executed: %1**

Probable cause A RAISERROR statement has been executed.

#### **READTEXT or WRITETEXT statement cannot refer to a view**

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -708                        |
| Constant          | SQLE_TEXT_OPERATION_ON_VIEW |
| SQLSTATE          | 42W50                       |
| Sybase error code | 285                         |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |
|                   | 1                           |

**Probable cause** A Transact-SQL READTEXT or WRITETEXT statement cannot refer to text columns in a view. Replace the view reference with the name of a base table.

# Referential integrity actions other than RESTRICT not allowed for temporary tables

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -849                            |
| Constant          | SQLE_INVALID_FOREIGN_KEY_ACTION |
| SQLSTATE          | 42R01                           |
| Sybase error code | 1709                            |
| ODBC 2 State      | 42000                           |
| ODBC 3 State      | 42000                           |

**Probable cause** You attempted to specify an unsupported referential integrity action for a temporary table.

#### Remote message type '%1' not found

| Value                        |
|------------------------------|
| -286                         |
| SQLE_NOT_REMOTE_TYPE         |
| 5RW07                        |
| 13648                        |
| S0002                        |
| 42S02                        |
| Name of remote message type. |
|                              |

## Probable causeYou referred to a remote message type that is not defined in this database.<br/>Use CREATE REMOTE TYPE to define remote message types.

# Remote server '%1' could not be found; Add the server using CREATE SERVER

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -659                           |
| Constant          | SQLE_OMNI_SERVER_NOT_FOUND     |
| SQLSTATE          | WO004                          |
| Sybase error code | 11214                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
| Parameter 1       | The name of the remote server. |
|                   | •                              |

## Probable causeYou attempted to define an object on a server that has not been added. Use<br/>CREATE SERVER to add the remote server definition.

#### Remote server '%1' is currently configured as read only

| ltem  | Value                            |
|---|----------------------------------|
| SQLCODE   | -658                             |
| Constant  | SQLE_OMNI_READONLY               |
| SQLSTATE  | WO003                            |
| Sybase error code                                 | 11248                            |
| ODBC 2 State                                      | ERROR                            |
| ODBC 3 State                                      | ERROR                            |
| Parameter 1                                       | The name of the remote server.   |
| Sybase error code<br>ODBC 2 State<br>ODBC 3 State | WO003<br>11248<br>ERROR<br>ERROR |

**Probable cause** You attempted to perform an update on an object located on a server that is configured as read only. Use ALTER SERVER to reconfigure the remote server to be updatable.

#### Remote server does not have the ability to support this statement

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -706                         |
| Constant          | SQLE_OMNI_SERVER_NOT_CAPABLE |
| SQLSTATE          | WO012                        |
| Sybase error code | 11227                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
|                   | •                            |

## **Probable cause** You attempted to execute a statement that requires a capability that is not supported by a remote server.

#### **Remote statement failed**

| Item                                  | Value                        |
|---------------------------------------|------------------------------|
| SQLCODE                               | -288                         |
| Constant                              | SQLE_REMOTE_STATEMENT_FAILED |
| SQLSTATE                              | 5RW09                        |
| Sybase error code                     | 13650                        |
| ODBC 2 State                          | S0002                        |
| ODBC 3 State                          | 42S02                        |
| · · · · · · · · · · · · · · · · · · · |                              |

Probable causeThis SQLSTATE can be signaled within a trigger to prevent DBREMOTE<br/>from displaying an error message in the output. This exception will only<br/>occur when a trigger or procedure SIGNALS it. This is useful for ignoring<br/>replication errors that are permitted by design.

#### Request denied -- no active databases

| - | Item              | Value                            |
|---|-------------------|----------------------------------|
| - | SQLCODE           | -76                              |
|   | Constant          | SQLE_REQUEST_DENIED_NO_DATABASES |
|   | SQLSTATE          | 08W28                            |
|   | Sybase error code | 950                              |
|   | ODBC 2 State      | 08004                            |
|   | ODBC 3 State      | 08004                            |
|   |                   |                                  |

#### Probable cause

The server has denied your request as there are currently no running databases.

#### Request to start/stop database denied

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -75                             |
| Constant          | SQLE_START_STOP_DATABASE_DENIED |
| SQLSTATE          | 08W29                           |
| Sybase error code | 6004                            |
| ODBC 2 State      | 42000                           |
| ODBC 3 State      | 42000                           |
|                   |                                 |
| <br>              |                                 |

## **Probable cause** You do not have permission to start or stop a database. The required permission is determined on the server command line.

| ltem              | Value                                      |
|-------------------|--|
| SQLCODE           | -685                                       |
| Constant          | SQLE_RESOURCE_GOVERNOR_EXCEEDED            |
| SQLSTATE          | WP009                                      |
| Sybase error code | 13715                                      |
| ODBC 2 State      | ERROR                                      |
| ODBC 3 State      | ERROR                                      |
| Parameter 1       | The resource whose limit has been exceeded |
|                   | •  |

#### Resource governor for '%1' exceeded

**Probable cause** The resource governor for the stated resource has determined that the usage of the resource has exceeded its limit.

#### **RESTORE** unable to open file '%1'

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -717                        |
| Constant          | SQLE_RESTORE_UNABLE_TO_OPEN |
| SQLSTATE          | WB008                       |
| Sybase error code | 13726                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
| Parameter 1       | File name of database file. |
|                   |                             |

Probable cause RESTORE was unable to open one of the database files.

#### **RESTORE** unable to start database '%1'

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -719                         |
| Constant          | SQLE_RESTORE_UNABLE_TO_START |
| SQLSTATE          | WB010                        |
| Sybase error code | 13728                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
| Parameter 1       | File name of database file.  |
|                   |                              |

Probable cause After a RESTORE, the resulting database could not be started.

#### **RESTORE** unable to write to file '%1'

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -718                         |
| Constant          | SQLE_RESTORE_UNABLE_TO_WRITE |
| SQLSTATE          | WB009                        |
| Sybase error code | 13727                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
| Parameter 1       | File name of database file.  |
|                   | •                            |

**Probable cause** RESTORE was unable to write to one of the database files.

#### Result set not allowed from within an atomic compound statement

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -222                    |
| Constant          | SQLE_RESULT_NOT_ALLOWED |
| SQLSTATE          | 3BW02                   |
| Sybase error code | 13655                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
|                   |                         |

| Probable cause | You used a SELECT statement with no INTO clause or a RESULT |
|----------------|---|
|                | CURSOR statement within an atomic compound statement.       |

## Return type of void from procedure '%1' cannot be used in any expression

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -705                        |
| Constant          | SQLE_PROCEDURE_RETURNS_VOID |
| SQLSTATE          | 53019                       |
| Sybase error code | 257                         |
| ODBC 2 State      | 07006                       |
| ODBC 3 State      | 07006                       |
| Parameter 1       | Name of the procedure.      |
|                   |                             |

## **Probable cause** The Java type void does not map onto any SQL type, hence a procedure returning void cannot be used in any SQL expression.

#### Return value cannot be set

#### Probable cause

Setting a value for the return parameter of a callable statement is not allowed.

#### Right truncation of string data

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -638                         |
| Constant          | SQLE_STRING_RIGHT_TRUNCATION |
| SQLSTATE          | 22001                        |
| Sybase error code | 9502                         |
| ODBC 2 State      | 22001                        |
| ODBC 3 State      | 22001                        |

Probable cause Non-space characters were truncated upon the assignment of string data.

#### Rollback occurred due to deadlock during prefetch

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -684                      |
| Constant          | SQLE_ROLLBACK_ON_PREFETCH |
| SQLSTATE          | WW019                     |
| Sybase error code | 1205                      |
| ODBC 2 State      | 40001                     |
| ODBC 3 State      | 40001                     |

Probable cause One of the cursors that was opened with prefetch enabled was performing fetch operations, and a deadlock occurred during a prefetch. This is a deadlock situation and your transaction has been chosen as the one to rollback. The request which received this error was not executed, unless the request was a close cursor, in which case the cursor was closed.

### **ROLLBACK TO SAVEPOINT not allowed**

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -221                      |
| Constant          | SQLE_ROLLBACK_NOT_ALLOWED |
| SQLSTATE          | 3B002                     |
| Sybase error code | 13654                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
|                   |                           |

### **Probable cause** You attempted a ROLLBACK TO SAVEPOINT within an atomic operation to a savepoint established before the atomic operation.

### Row has been updated since last time read

|                | ltem  | Value                    |
|----------------|---|--------------------------|
|                | SQLCODE   | 104                      |
|                | Constant  | SQLE_ROW_UPDATED_WARNING |
|                | SQLSTATE  | 01W04                    |
|                | Sybase error code   | 532                      |
|                | ODBC 2 State  | OK                       |
|                | ODBC 3 State  | OK                       |
| Probable cause | You fetched a row from a SCROLL cursor. The row was previously fetched<br>from the same cursor, and one or more columns in the row has been updated<br>since the previous fetch. The column(s) updated may or may not be fetched<br>by the cursor; this warning just indicates that the row from the table has been<br>updated. If the cursor involves more than one table, a row from one or more<br>of the tables has been updated. |                          |

#### Row has changed since last read -- operation cancelled

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -208                        |
| Constant          | SQLE_ROW_UPDATED_SINCE_READ |
| SQLSTATE          | 22W02                       |
| Sybase error code | 554                         |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
|                   |                             |

Probable causeYou attempted an UPDATE (positioned) or DELETE (positioned) operation<br/>on a cursor declared as a SCROLL cursor, and the row you are changing has<br/>been updated since you read it. This error prevents the 'lost update' problem.

### Row in table '%1' was modified or deleted in BEFORE trigger

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -833                           |
| Constant          | SQLE_ROW_REMODIFIED_OR_DELETED |
| SQLSTATE          | 42W62                          |
| Sybase error code | 13839                          |
| ODBC 2 State      | 37000                          |
| ODBC 3 State      | ERROR                          |
| Parameter 1       | Name of the table.             |

**Probable cause** A BEFORE trigger has updated or deleted the row which caused the trigger to fire, preventing the original operation from completing. The trigger must be re-written so that it does not attempt to change the row via UPDATE or DELETE statements.

### Row not found

| ltem              | Value         |
|-------------------|---------------|
| SQLCODE           | 100           |
| Constant          | SQLE_NOTFOUND |
| SQLSTATE          | 02000         |
| Sybase error code | 560           |
| ODBC 2 State      | ОК            |
| ODBC 3 State      | ОК            |

**Probable cause** You positioned a cursor beyond the beginning or past the end of the query. There is no row at that position.

### Run time SQL error -- %1

\_

| ltem              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -300                         |
| Constant          | SQLE_ERROR                   |
| SQLSTATE          | 40000                        |
| Sybase error code | 13664                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
| Parameter 1       | Identification of the error. |
|                   | •                            |

**Probable cause** An internal database error occurred. If it can be reproduced, it should be reported to iAnywhere Solutions.

### Savepoint '%1' not found

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -220                    |
| Constant          | SQLE_SAVEPOINT_NOTFOUND |
| SQLSTATE          | 3B001                   |
| Sybase error code | 6401                    |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
| Parameter 1       | Name of savepoint.      |
|                   | -                       |

**Probable cause** You attempted to rollback to a savepoint that does not exist.

### Savepoints require a rollback log

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -213                         |
| Constant          | SQLE_SAVEPOINTS_REQUIRE_UNDO |
| SQLSTATE          | 3BW01                        |
| Sybase error code | 13656                        |
| ODBC 2 State      | ERROR                        |
| ODBC 3 State      | ERROR                        |
|                   |                              |

**Probable cause** You cannot use savepoints when the database server is running in bulk mode without a rollback log.

| Item              | Value                                     |
|-------------------|---|
| SQLCODE           | -774                                      |
| Constant          | SQLE_SCHEDULE_ALREADY_EXISTS              |
| SQLSTATE          | WE004                                     |
| Sybase error code | 13784                                     |
| ODBC 2 State      | ERROR                                     |
| ODBC 3 State      | ERROR                                     |
| Parameter 1       | Name of the schedule that already exists. |
| Parameter 2       | Name of the event being scheduled.        |

#### Schedule '%1' for event '%2' already exists

Probable causeYou have attempted to create a schedule with a name that already exists in<br/>SYS.SYSSCHEDULE for the named event.

### Schedule '%1' for event '%2' not found

| Value   |
|---|
| -773  |
| SQLE_SCHEDULE_NOT_FOUND                       |
| WE003   |
| 13783   |
| ERROR   |
| ERROR   |
| Name of the schedule that could not be found. |
| Name of the event being scheduled.            |
|   |

## **Probable cause** You have attempted to reference a schedule with a name that does not exist in SYS.SYSSCHEDULE for the named event.

### Seek absolute 0 was attempted on a JDBC SAResultSet

| Item              | Value                                      |
|-------------------|--|
| SQLCODE           | -743                                       |
| Constant          | SQLE_JDBC_RESULTSET_SEEK_ABSOLUTE_ZER<br>O |
| SQLSTATE          | WJ016                                      |
| Sybase error code | 13756                                      |
| ODBC 2 State      | ERROR                                      |
| ODBC 3 State      | ERROR                                      |

Probable cause

There is no row zero on JDBC resultSets. The valid row numbers are 1, 2, ..., -2, -1.

### SELECT lists in UNION do not match in length

| Item              | Value              |
|-------------------|--------------------|
| SQLCODE           | -153               |
| Constant          | SQLE_INVALID_UNION |
| SQLSTATE          | 53026              |
| Sybase error code | 205                |
| ODBC 2 State      | 37000              |
| ODBC 3 State      | 42000              |
|                   |                    |

Probable causeYou specified a UNION but the SELECT statements involved in the union<br/>do not have the same number of columns in the select list.

### SELECT returns more than one row

| ltem              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -185                  |
| Constant          | SQLE_TOO_MANY_RECORDS |
| SQLSTATE          | 21000                 |
| Sybase error code | 13637                 |
| ODBC 2 State      | ERROR                 |
| ODBC 3 State      | ERROR                 |
|                   |                       |

Probable causeYou tried to use a SELECT statement without a cursor, but the statement<br/>cursor returns more than one row. Only a single row SELECT statement can<br/>be used in this context.

### Server '%1': %2

| Item Value   |                   | Value                               |
|--------------|-------------------|-------------------------------------|
| SQLCODE -660 |                   | -660                                |
|              | Constant          | SQLE_OMNI_REMOTE_ERROR              |
|              | SQLSTATE          | WO005                               |
|              | Sybase error code | 13732                               |
|              | ODBC 2 State      | ERROR                               |
|              | ODBC 3 State      | ERROR                               |
|              | Parameter 1       | The name of the remote server.      |
|              | Parameter 2       | The message from the remote server. |
|              |                   |                                     |

Probable cause A message was generated by a remote server. The message text is included."

# Server capability name '%1' could not be found in the SYS.SYSCAPABILITYNAME table.

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -761                           |
| Constant          | SQLE_CAPABILITY_NOT_FOUND      |
| SQLSTATE          | WO014                          |
| Sybase error code | 13723                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
| Parameter 1       | The name of server capability. |
|                   |                                |

## Probable cause An ALTER SERVER statement was attempted on a capability that was not defined.

### Server not found and unable to autostart

| Value                           |
|---------------------------------|
| -764                            |
| SQLE_UNABLE_TO_CONNECT_OR_START |
| 08W55                           |
| 13774                           |
| 08001                           |
| 08001                           |
|                                 |

### **Probable cause** Could not connect to a server, and was unable to autostart a server. Autostart may have failed because no database file was supplied.

| ltem              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -846                    |
| Constant          | SQLE_INVALID_SET_CLAUSE |
| SQLSTATE          | 42U03                   |
| Sybase error code | 13852                   |
| ODBC 2 State      | S0002                   |
| ODBC 3 State      | 42S03                   |
|                   |                         |

#### Set clause for column '%1' used incorrectly

### **Probable cause** Your update statement contains an invalid set clause, e.g., there are multiple set clauses for the same column.

### SETUSER not allowed in procedures, triggers, events or batches

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -877                           |
| Constant          | SQLE_SETUSER_NOT_IN_PROCEDURES |
| SQLSTATE          | 42W09                          |
| Sybase error code | 13888                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
|                   | •                              |

**Probable cause** The SETUSER statement is not allowed in stored procedures, triggers, event handlers or batches. It cannot be executed via EXECUTE IMMEDIATE.

### Signature '%1' does not match procedure parameters

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -737                       |
| Constant          | SQLE_SIGNATURE_MISMATCH    |
| SQLSTATE          | 42W54                      |
| Sybase error code | 201                        |
| ODBC 2 State      | 37000                      |
| ODBC 3 State      | 42000                      |
| Parameter 1       | The value of the signature |

**Probable cause**The number of types in the signature must match the number of procedure<br/>parameters. If a 'dynamic result sets' clause was specified, the number of<br/>dynamic result sets must match the quantity found in the signature.

### Specified database file already in use.

| Item              | Value            |
|-------------------|------------------|
| SQLCODE           | -816             |
| Constant          | SQLE_FILE_IN_USE |
| SQLSTATE          | 08W56            |
| Sybase error code | 924              |
| ODBC 2 State      | 08001            |
| ODBC 3 State      | 08001            |

**Probable cause** The database server could not start the specified database because the file is already in use.

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -84                   |
| Constant          | SQLE_INVALID_DATABASE |
| SQLSTATE          | 08W11                 |
| Sybase error code | 4001                  |
| ODBC 2 State      | 08001                 |
| ODBC 3 State      | 08001                 |
|                   |                       |

### Specified database is invalid

### Specified database not found

|         | ltem                  | Value   |
|---------|-----------------------|---|
|         | SQLCODE               | -83   |
|         | Constant              | SQLE_DATABASE_NOT_FOUND                         |
|         | SQLSTATE              | 08W10   |
|         | Sybase error code     | 911   |
|         | ODBC 2 State          | 08001   |
|         | ODBC 3 State          | 08001   |
|         |                       |   |
| e cause | The database server w | as started but was unable to find the specified |

Probable cause The database server was started but was unable to find the specified database. The database server may be attempting to start a database file that cannot be opened or that cannot be found on the network. You may be attempting to connect to a database name that is not running. The database server is stopped.

### SQL statement error

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -132                 |
| Constant          | SQLE_STATEMENT_ERROR |
| SQLSTATE          | 26501                |
| Sybase error code | 13629                |
| ODBC 2 State      | ERROR                |
| ODBC 3 State      | ERROR                |

#### Probable cause

The statement identifier (generated by PREPARE) passed to the database for a further operation is invalid.

### SQLDA data type invalid

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -759                        |
| Constant          | SQLE_SQLDA_INVALID_DATATYPE |
| SQLSTATE          | 07W05                       |
| Sybase error code | 13770                       |
| ODBC 2 State      | 07001                       |
| ODBC 3 State      | 07W05                       |

**Probable cause** The data type specified for a SQLDA variable is invalid.

### SQLDA fields inconsistent for a multi-row SQLDA

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -700                    |
| Constant          | SQLE_SQLDA_INCONSISTENT |
| SQLSTATE          | 07W04                   |
| Sybase error code | 13721                   |
| ODBC 2 State      | 07001                   |
| ODBC 3 State      | 07W04                   |

**Probable cause** Not all of the rows in a multi-rows SQLDA have been defined identically for an array operation (insert, fetch, or execute). A given column must be defined the same (type and length) in each row.

#### Sqlpp/dblib version mismatch

| ltem              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -230                   |
| Constant          | SQLE_PP_DBLIB_MISMATCH |
| SQLSTATE          | 08W18                  |
| Sybase error code | 13657                  |
| ODBC 2 State      | 08001                  |
| ODBC 3 State      | 08001                  |

# Probable cause Your executable has source files with Embedded SQL that were preprocessed with a preprocessor that does not match the database interface library.

#### Statement cannot be executed

| _ | ltem              | Value                    |
|---|-------------------|--------------------------|
| _ | SQLCODE           | 111                      |
|   | Constant          | SQLE_CANNOT_EXECUTE_STMT |
|   | SQLSTATE          | 01W08                    |
|   | Sybase error code | 590                      |
|   | ODBC 2 State      | ОК                       |
|   | ODBC 3 State      | ОК                       |
|   |                   |                          |

# Probable cause You specified a statement for the PREPARE..WITH EXECUTE statement that cannot be executed. If you specified an output SQLDA, it may contain a DESCRIBE of the prepared statement.

# Statement contains an illegal usage of the non-deterministic function '%1'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -889   |
| Constant          | SQLE_NONDETERMINISTIC_FUNCTION   |
| SQLSTATE          | 42W79  |
| Sybase error code | 13594  |
| ODBC 2 State      | 37000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | The name of the non-deterministic user-defined function used in error. |

**Probable cause** Non-deterministic functions cannot appear in a CHECK constraint, or any other type of integrity constraint. They may appear anywhere within a query, view, or derived table. However, if an aliased SELECT list expression contains a non-deterministic function, that alias cannot be referred to elsewhere in the query.

### Statement contains an illegal usage of the NUMBER(\*) function

|                | Item   | Value               |
|----------------|--|---------------------|
|                | SQLCODE  | -864                |
|                | Constant   | SQLE_INVALID_NUMBER |
|                | SQLSTATE   | 42W71               |
|                | Sybase error code  | 13869               |
|                | ODBC 2 State   | 37000               |
|                | ODBC 3 State   | 42000               |
|                |  |                     |
| Probable cause | The NUMBER(*) and IDENTITY() functions can only appear in the SELECT list of the outer-most SELECT block. It cannot be used in any subquery or in a predicate. |                     |

| ltem              | Value            |
|-------------------|------------------|
| SQLCODE           | -299             |
| Constant          | SQLE_INTERRUPTED |
| SQLSTATE          | 57014            |
| Sybase error code | 3621             |
| ODBC 2 State      | ERROR            |
| ODBC 3 State      | ERROR            |
|                   | -                |

### Statement interrupted by user

# Probable causeYou canceled a statement during its execution. The database was able to stop<br/>the operation without doing a rollback. If the statement is INSERT,<br/>UPDATE, or DELETE, any changes made by the statement will be canceled.<br/>If the statement is a data definition statement (for example CREATE<br/>TABLE), the statement will be canceled, but the COMMIT that was done as<br/>a side effect will not be canceled.

### Statement is not allowed in passthrough mode

| ltem              | Value                                    |
|-------------------|--|
| SQLCODE           | -707                                     |
| Constant          | SQLE_STMT_NOT_ALLOWED_IN_PASSTHROUG<br>H |
| SQLSTATE          | 0AW05                                    |
| Sybase error code | 13631                                    |
| ODBC 2 State      | 37000                                    |
| ODBC 3 State      | 42000                                    |
|                   |  |

### **Probable cause** You tried to execute a statement that cannot be executed while in passthrough mode. For example, you may have executed a batch statement.

### statement's size limit is invalid.

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -674                      |
| Constant          | SQLE_INVALID_CURSOR_RANGE |
| SQLSTATE          | 09W07                     |
| Sybase error code | 13713                     |
| ODBC 2 State      | 42000                     |
| ODBC 3 State      | 42000                     |
|                   | '                         |

Probable causeFIRST or TOP n are used in a SELECT statement to limit the size of a result.<br/>The size limit 'n' must be a constant integer greater than 0 and less than<br/>32767.

# Strongly-encrypted database files are not supported in the runtime server

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -688                          |
| Constant          | SQLE_NO_ENCRYPTION_IN_RUNTIME |
| SQLSTATE          | 55W13                         |
| Sybase error code | 13879                         |
| ODBC 2 State      | 42000                         |
| ODBC 3 State      | 42000                         |

### **Probable cause** You attempted to start a strongly-encrypted database with the runtime server. Use the full server.

| Value                     |
|---------------------------|
| -151                      |
| SQLE_SUBQUERY_SELECT_LIST |
| 53023                     |
| 102                       |
| 37000                     |
| 42000                     |
|                           |

### Subquery allowed only one select list item

## Probable cause You entered a subquery which has more than one column in the select list. Change the select list to have only one column.

#### Subquery cannot return more than one row

| Item              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -186                            |
| Constant          | SQLE_SUBQUERY_RESULT_NOT_UNIQUE |
| SQLSTATE          | 21W01                           |
| Sybase error code | 512                             |
| ODBC 2 State      | 37000                           |
| ODBC 3 State      | 42000                           |
|                   | •                               |

**Probable cause** You used a subquery that returns more than one row, in a context where only a single row can be used. If the subquery is in the WHERE clause, you might be able to use the IN keyword.

### Subscription to '%1' for '%2' already exists

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -282                         |
| Constant          | SQLE_SUBSCRIPTION_NOT_UNIQUE |
| SQLSTATE          | 5RW03                        |
| Sybase error code | 13644                        |
| ODBC 2 State      | S0002                        |
| ODBC 3 State      | 42S02                        |
| Parameter 1       | Name of the publication.     |
| Parameter 2       | Name of the user.            |

#### **Probable cause** You attempted to create a subscription that already exists.

### Subscription to '%1' for '%2' not found

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -283                        |
| Constant          | SQLE_SUBSCRIPTION_NOT_FOUND |
| SQLSTATE          | 5RW04                       |
| Sybase error code | 13645                       |
| ODBC 2 State      | S0002                       |
| ODBC 3 State      | 42S02                       |
| Parameter 1       | Name of the publication.    |
| Parameter 2       | Name of the user.           |
|                   |                             |

### **Probable cause** You attempted to drop, start, or synchronize a subscription that does not exist.

### Synchronization failed due to an unspecified error on the server.

| Value                             |
|-----------------------------------|
| -857                              |
| SQLE_SERVER_SYNCHRONIZATION_ERROR |
| 0AW12                             |
| 13860                             |
| 37000                             |
| 42000                             |
|                                   |

## **Probable cause** Synchronization failed at the server. More details can be found in the synchronization log file.

### Synchronization message type '%1' not found

\_

| Item              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -765                                  |
| Constant          | SQLE_NOT_SYNC_TYPE                    |
| SQLSTATE          | 5RW11                                 |
| Sybase error code | 13775                                 |
| ODBC 2 State      | S0002                                 |
| ODBC 3 State      | 42S02                                 |
| Parameter 1       | Name of synchronization message type. |

### **Probable cause** You referred to a synchronization message type that is not defined in this database.

# Synchronization option '%1' contains semi-colon, equal sign or curly brace

| ltem              | Value                                  |
|-------------------|--|
| SQLCODE           | -797                                   |
| Constant          | SQLE_BAD_SYNC_OPTION_VALUE             |
| SQLSTATE          | 5RW32                                  |
| Sybase error code | 13807                                  |
| ODBC 2 State      | 42000                                  |
| ODBC 3 State      | 42802                                  |
| Parameter 1       | The name of the synchronization option |
|                   |  |

### **Probable cause**You attempted to set a synchronization option with an invalid value.

### Synchronization option '%1' not found

| Item              | Value                                  |
|-------------------|--|
| SQLCODE           | -805                                   |
| Constant          | SQLE_SYNC_OPTION_NOT_FOUND             |
| SQLSTATE          | 5RW33                                  |
| Sybase error code | 13815                                  |
| ODBC 2 State      | 42000                                  |
| ODBC 3 State      | 42S02                                  |
| Parameter 1       | The name of the synchronization option |
|                   |  |

**Probable cause** You attempted to delete a undefined synchronization option.

| Value                     |
|---------------------------|
| -809                      |
| SQLE_SYNC_OPTION_TOO_LONG |
| 5RW34                     |
| 13819                     |
| 42000                     |
| 42S02                     |
| -                         |

| Probable cause | Synchronization optior | list cannot be longer than | database page size. |
|----------------|------------------------|----------------------------|---------------------|
|----------------|------------------------|----------------------------|---------------------|

### Synchronization server failed to commit the upload

|                | Item   | Value                        |
|----------------|--|------------------------------|
|                | SQLCODE  | -794                         |
|                | Constant   | SQLE_UPLOAD_FAILED_AT_SERVER |
|                | SQLSTATE   | 0AW09                        |
|                | Sybase error code  | 13804                        |
|                | ODBC 2 State   | 37000                        |
|                | ODBC 3 State   | 42000                        |
|                |  |                              |
| Probable cause | You attempted to synchronize an UltraLite database and during the<br>synchronization session, a complete upload stream was sent that could not be<br>committed to the consolidated database. The reason for the upload failure |                              |

can be found in the synchronization log file.

### Synchronization site '%1' is already defined

| ltem              | Value                                |
|-------------------|--------------------------------------|
| SQLCODE           | -796                                 |
| Constant          | SQLE_SYNC_SITE_NOT_UNIQUE            |
| SQLSTATE          | 5RW31                                |
| Sybase error code | 13806                                |
| ODBC 2 State      | 42000                                |
| ODBC 3 State      | 42S02                                |
| Parameter 1       | The name of the synchronization site |
|                   | •                                    |

**Probable cause** 

You attempted to create a synchronization site with a non-unique site name.

### Syntax error near '%1' %2

| lte | em              | Value  |
|-----|-----------------|--|
| SÇ  | QLCODE          | -131   |
| Co  | onstant         | SQLE_SYNTAX_ERROR  |
| SÇ  | QLSTATE         | 42W04  |
| Sy  | base error code | 102  |
| OI  | DBC 2 State     | 37000  |
| OI  | DBC 3 State     | 42000  |
| Pa  | rameter 1       | The word or symbol where the syntax error has been detected. |
| Pa  | rameter 2       | Line number.   |

**Probable cause** The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE").

# Syntax error, cannot specify IQ specific options without specifying IQ PATH

| Value                     |
|---------------------------|
| -687                      |
| SQLE_IQ_PATH_SYNTAX_ERROR |
| 42W48                     |
| 102                       |
| 37000                     |
| 42000                     |
|                           |

Probable cause The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE").

### System event type '%1' not found

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -806   |
| Constant          | SQLE_EVENT_TYPE_NOT_FOUND                              |
| SQLSTATE          | WE008  |
| Sybase error code | 13816  |
| ODBC 2 State      | ERROR  |
| ODBC 3 State      | ERROR  |
| Parameter 1       | Name of the system event type that could not be found. |

### **Probable cause** You have attempted to create an event with a system event type name that does not exist in SYS.SYSEVENTTYPE.

### Table '%1' has a foreign key with a referential action

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -677  |
| Constant          | SQLE_TABLE_HAS_REFACTION                      |
| SQLSTATE          | 56001   |
| Sybase error code | 547   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | Name of the table with the referential action |

**Probable cause** The table could not be renamed as it has a foreign key with a referential action. To rename the table, first drop the foreign key constraints.

### Table '%1' has no primary key

|                | ltem                 | Value   |
|----------------|----------------------|---|
|                | SQLCODE              | -118  |
|                | Constant             | SQLE_NO_PRIMARY_KEY                                     |
|                | SQLSTATE             | 55008   |
|                | Sybase error code    | 1719  |
|                | ODBC 2 State         | 42000   |
|                | ODBC 3 State         | 42000   |
|                | Parameter 1          | Name of the table that does not have a primary key.     |
|                |                      |   |
| Probable cause | You attempted to add | a foreign key referring to a table that does not have a |

primary key. You must add a primary key to the referenced table.

### Table '%1' has publications

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -281   |
| Constant          | SQLE_TABLE_HAS_PUBLICATIONS                    |
| SQLSTATE          | 5RW02  |
| Sybase error code | 13643  |
| ODBC 2 State      | S0002  |
| ODBC 3 State      | 42S02  |
| Parameter 1       | Name of the publication that has publications. |
|                   |  |

**Probable cause** You attempted to drop a table that has publications defined.

### Table '%1' is already included

\_

| ltem  | Value                       |
|---|-----------------------------|
| SQLCODE   | -822                        |
| Constant  | SQLE_TABLE_ALREADY_INCLUDED |
| SQLSTATE  | 5RW36                       |
| Sybase error code                                 | 13828                       |
| ODBC 2 State                                      | 42000                       |
| ODBC 3 State                                      | 42S02                       |
| Parameter 1                                       | The name of the table       |
| Sybase error code<br>ODBC 2 State<br>ODBC 3 State | 13828<br>42000<br>42802     |

# **Probable cause** You attempted to add or modify a publication or synchronization definition such that the same table is included twice.

### Table '%1' is in an outer join cycle

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -136                          |
| Constant          | SQLE_OUTER_JOIN_CYCLE         |
| SQLSTATE          | 52W14                         |
| Sybase error code | 315                           |
| ODBC 2 State      | 37000                         |
| ODBC 3 State      | 42000                         |
| Parameter 1       | Name of a table in the cycle. |
|                   |                               |

**Probable cause** You specified outer joins that create a cycle of tables.

### Table '%1' is part of a synchronization definition

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -819                     |
| Constant          | SQLE_SYNC_CONTAINS_TABLE |
| SQLSTATE          | 5RW35                    |
| Sybase error code | 13825                    |
| ODBC 2 State      | 42000                    |
| ODBC 3 State      | 42S02                    |
| Parameter 1       | The name of the table    |
|                   |                          |

**Probable cause** A table belonging to a synchronization definition cannot be dropped or altered except using DBMLSync.

### Table '%1' not found

| Item              | Value                                      |
|-------------------|--|
| SQLCODE           | -141                                       |
| Constant          | SQLE_TABLE_NOT_FOUND                       |
| SQLSTATE          | 42W33                                      |
| Sybase error code | 2706                                       |
| ODBC 2 State      | S0002                                      |
| ODBC 3 State      | 42S02                                      |
| Parameter 1       | Name of the table that could not be found. |

**Probable cause** You misspelled the name of a table, or you did not qualify a table name with a user name. For example, you might have referred to employee instead of "DBA".employee,

### Table '%1' requires a unique correlation name

| ltem              | Value   |
|-------------------|---|
| SQLCODE           | -137  |
| Constant          | SQLE_CORRELATION_NAME_NEEDED                            |
| SQLSTATE          | 52W15   |
| Sybase error code | 315   |
| ODBC 2 State      | 37000   |
| ODBC 3 State      | 42000   |
| Parameter 1       | Name of the table that needs a unique correlation name. |
|                   |   |

### **Probable cause** You specified a join that joins a table to itself. You need to use unique correlation names in order to have multiple instances of a table.

### Table already has a primary key

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -112                      |
| Constant          | SQLE_EXISTING_PRIMARY_KEY |
| SQLSTATE          | 55013                     |
| Sybase error code | 1923                      |
| ODBC 2 State      | 42000                     |
| ODBC 3 State      | 42000                     |

#### Probable cause

You attempted to add a primary key on a table that already has a primary key defined. You must delete the current primary key before adding a new one.

### Table cannot have two primary keys

| ltem              | Value  |
|-------------------|--|
| SQLCODE           | -126   |
| Constant          | SQLE_PRIMARY_KEY_TWICE   |
| SQLSTATE          | 52W05  |
| Sybase error code | 1923   |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 42000  |
|                   | SQLCODE<br>Constant<br>SQLSTATE<br>Sybase error code<br>ODBC 2 State |

**Probable cause** You specified the primary key twice in a CREATE TABLE statement.

### Table in use

| Item              | Value             |
|-------------------|-------------------|
| SQLCODE           | -214              |
| Constant          | SQLE_TABLE_IN_USE |
| SQLSTATE          | 42W21             |
| Sybase error code | 3702              |
| ODBC 2 State      | 40001             |
| ODBC 3 State      | 40001             |

**Probable cause** You attempted to ALTER or DROP a table that is being used by other active users of the database.

#### Table must be empty

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -116                     |
| Constant          | SQLE_TABLE_MUST_BE_EMPTY |
| SQLSTATE          | 55W02                    |
| Sybase error code | 4901                     |
| ODBC 2 State      | ERROR                    |
| ODBC 3 State      | ERROR                    |
|                   |                          |

**Probable cause** You attempted to modify a table, and the database server can only perform the change if there are no rows in the table.

#### Table name '%1' is ambiguous

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -852                        |
| Constant          | SQLE_AMBIGUOUS_TABLE_NAME   |
| SQLSTATE          | 52W42                       |
| Sybase error code | 13856                       |
| ODBC 2 State      | S0013                       |
| ODBC 3 State      | 42S13                       |
| Parameter 1       | Name of an ambiguous table. |
|                   |                             |

# **Probable cause** A statement has referred to a table name which is not unique. Preface the table name by an owner name.

# Tables related by key constraint must both be permanent or both be temporary created with ON COMMIT PRESERVE ROWS

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -850                           |
| Constant          | SQLE_INVALID_FOREIGN_KEY_TABLE |
| SQLSTATE          | 42R02                          |
| Sybase error code | 1709                           |
| ODBC 2 State      | 42000                          |
| ODBC 3 State      | 42000                          |

# Probable causeTables involved in a key constraint relationship must both be permanent user<br/>tables or both be temporary tables created with ON COMMIT PRESERVE<br/>ROWS. Change the definition of one or both tables using ALTER TABLE.

### Terminated by user -- transaction rolled back

| ERMINATED_BY_USER |
|-------------------|
|                   |
|                   |
|                   |
|                   |
|                   |

### **Probable cause** You canceled a statement while the database was executing. A ROLLBACK WORK statement has been automatically executed.

### The aggregate expression '%1' must appear in either the select list or a HAVING clause subquery

| ltem              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -862                                |
| Constant          | SQLE_INVALID_AGGREGATE_PLACEMENT    |
| SQLSTATE          | 42W69                               |
| Sybase error code | 13866                               |
| ODBC 2 State      | 37000                               |
| ODBC 3 State      | 42000                               |
| Parameter 1       | The aggregated expression in error. |

**Probable cause** An aggregated expression containing an outer reference must either appear in a select list expression (a subselect), or in a HAVING clause subquery in the query whose FROM clause contains the table with the column being aggregated.

### The column '%1' does not exist in the remote table

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -722                    |
| Constant          | SQLE_OMNI_NOSUCH_COLUMN |
| SQLSTATE          | WO016                   |
| Sybase error code | 11208                   |
| ODBC 2 State      | ERROR                   |
| ODBC 3 State      | ERROR                   |
| Parameter 1       | The name of the column. |
|                   |                         |

# **Probable cause** The column specified in the 'CREATE EXISTING' statement does not exist in the remote table.

### The communications environment could not be created

| Item                              | Value                             |
|-----------------------------------|-----------------------------------|
| SQLCODE                           | -740                              |
| Constant                          | SQLE_FAILED_TO_CREATE_STREAMS_ENV |
| SQLSTATE                          | WW024                             |
| Sybase error code                 | 13753                             |
| ODBC 2 State                      | ERROR                             |
| ODBC 3 State                      | ERROR                             |
| Sybase error code<br>ODBC 2 State | 13753<br>ERROR                    |

# **Probable cause** The communications environment could not be created. Either there are insufficient resources to create the environment or the language resource file cannot be found.

### The connection parameters file could not be found

| ltem              | Value                |
|-------------------|----------------------|
| SQLCODE           | -654                 |
| Constant          | SQLE_NO_PROFILE_FILE |
| SQLSTATE          | 08W37                |
| Sybase error code | 13706                |
| ODBC 2 State      | 08001                |
| ODBC 3 State      | 08001                |
|                   |                      |

**Probable cause** An attempt was made to parse a connection string containing a connection profile but the connection parameters file could not be found.

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -683                       |
| Constant          | SQLE_DUPLICATE_CURSOR_NAME |
| SQLSTATE          | WJ004                      |
| Sybase error code | 13714                      |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |
| Parameter 1       | The name of the cursor     |
|                   | •                          |

### The cursor name '%1' already exists

**Probable cause** You attempted to declare a cursor with a name that already exists. Cursor names must be unique within a connection.

### The data type of column '%1' is not supported

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -736                           |
| Constant          | SQLE_OMNI_UNSUPPORTED_DATATYPE |
| SQLSTATE          | WO022                          |
| Sybase error code | 11205                          |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
| Parameter 1       | The name of the column.        |
|                   | •                              |

## **Probable cause** The column is defined with a data type that is not supported for remote tables.

# The data type specified for column '%1' is not compatible with the actual data type

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -721                        |
| Constant          | SQLE_OMNI_DATATYPE_MISMATCH |
| SQLSTATE          | WO015                       |
| Sybase error code | 11209                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |
| Parameter 1       | The name of the column.     |

**Probable cause** The data type of the column specified in the 'CREATE EXISTING' statement is not compatible with the actual data type of the column in the remote table.

### The database does not support the Java virtual machine

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -758                 |
| Constant          | SQLE_NO_JAVA_SUPPORT |
| SQLSTATE          | WJ022                |
| Sybase error code | 13769                |
| ODBC 2 State      | ERROR                |
| ODBC 3 State      | ERROR                |

Probable cause The Java virtual machine could not be started because the database does not have the proper support. It may be that the database was created with an older version of the software, or was created with the Java support disabled. If the database was created with an older version of the software the database should be upgraded to the most recent version. If the database was created with Java support disabled, then the instjava.sql script should be run against the database to enable Java support.

### The database needs to be restarted for this Java related command

| ltem              | Value                       |  |
|-------------------|-----------------------------|--|
| SQLCODE           | -871                        |  |
| Constant          | SQLE_JAVA_DB_RESTART_NEEDED |  |
| SQLSTATE          | WJ029                       |  |
| Sybase error code | 13875                       |  |
| ODBC 2 State      | ERROR                       |  |
| ODBC 3 State      | ERROR                       |  |

# Probable causeJava support in the database requires a database restart after some Java<br/>related commands are performed, e.g. some Java commands like Alter<br/>Database Upgrade Java On require a restart before one performs any Java<br/>related commands that load a Java class into the database.

### The external function call is incompatible

| Item              | Value                           |  |
|-------------------|---------------------------------|--|
| SQLCODE           | -818                            |  |
| Constant          | SQLE_INCOMPATIBLE_EXTERNAL_CALL |  |
| SQLSTATE          | WW026                           |  |
| Sybase error code | 13824                           |  |
| ODBC 2 State      | ERROR                           |  |
| ODBC 3 State      | ERROR                           |  |

# **Probable cause** You attempted to call an external function. An attempt to load the attempted library failed because of incompatibility with the server. Incompatibility may arise because the dynamic library is using an external function API that is either not supported by the server or is newer than the one supported by the server.

# The integrated login ID guest can only be mapped to the guest database user ID

| ltem              | Value                          |  |
|-------------------|--------------------------------|--|
| SQLCODE           | -247                           |  |
| Constant          | SQLE_INTEGRATED_LOGON_GUESTMAP |  |
| SQLSTATE          | 28W06                          |  |
| Sybase error code | 13695                          |  |
| ODBC 2 State      | 28000                          |  |
| ODBC 3 State      | 28000                          |  |

Probable cause

You attempted to map the guest login ID to something other than guest

# The JDBC resultset must be positioned on an insert row in order to use the '%1' function

|                | Item   | Value                                       |
|----------------|--|---|
| SQLCODE        |  | -753  |
|                | Constant   | SQLE_JDBC_MUST_OPER_ON_INSERT_ROW           |
|                | SQLSTATE   | WJ020                                       |
|                | Sybase error code  | 13764                                       |
|                | ODBC 2 State   | ERROR                                       |
|                | ODBC 3 State   | ERROR                                       |
|                | Parameter 1  | Name of the resultset function being called |
|                |  |   |
| Probable cause | Resultset functions such as 'insertRow' can only be called when the resist positioned on the insert row. |   |

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -841                      |
| Constant          | SQLE_JDK_VERSION_MISMATCH |
| SQLSTATE          | WJ026                     |
| Sybase error code | 13847                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
| Parameter 1       | A JDK jar file name       |
| Parameter 2       | A JDK version string      |
|                   |                           |
| <br>              |                           |

#### The JDK version in '%1' does not match '%2'

Probable causeThe JDK version specified in the 'create database' statement does not match<br/>the JDK version in the JDK jar file.

## The length specified for column '%1' is different than the actual length

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -723                      |
| Constant          | SQLE_OMNI_LENGTH_MISMATCH |
| SQLSTATE          | WO017                     |
| Sybase error code | 11210                     |
| ODBC 2 State      | ОК                        |
| ODBC 3 State      | ОК                        |
| Parameter 1       | The name of the column.   |

## **Probable cause** The length of the column specified in the 'CREATE EXISTING' statement is different than the length of the column in the remote table.

#### The login ID '%1' has not been mapped to any database user ID

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -313                           |
| Constant          | SQLE_INTEGRATED_LOGON_UNMAPPED |
| SQLSTATE          | 28W09                          |
| Sybase error code | 13698                          |
| ODBC 2 State      | 28000                          |
| ODBC 3 State      | 28000                          |

**Probable cause** You attempted to drop a login ID that had not been mapped yet

#### The login ID '%1' is already mapped to user ID '%2'

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -249                         |
| Constant          | SQLE_INTEGRATED_LOGON_MAPPED |
| SQLSTATE          | 28W08                        |
| Sybase error code | 13697                        |
| ODBC 2 State      | 28000                        |
| ODBC 3 State      | 28000                        |
|                   |                              |

Probable cause You attempted to map a login ID twice

#### The optimizer was unable to construct a valid access plan

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -727                       |
| Constant          | SQLE_CANNOT_OPTIMIZE_QUERY |
| SQLSTATE          | WI010                      |
| Sybase error code | 13730                      |
| ODBC 2 State      | ERROR                      |
| ODBC 3 State      | ERROR                      |

## Probable cause The database server was unable to construct a valid access plan for the given request. This is an Adaptive Server Anywhere internal error. If it can be reproduced, it should be reported by iAnywhere Solutions. You may be able to work around this problem by modifying the query statement.

#### The option '%1' can only be set as a temporary option

| Item              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -216                     |
| Constant          | SQLE_OPTION_IS_TEMP_ONLY |
| SQLSTATE          | 42W52                    |
| Sybase error code | 5878                     |
| ODBC 2 State      | 42000                    |
| ODBC 3 State      | 42000                    |
|                   | •                        |

## **Probable cause** The option specified in the SET OPTION statement can only be set as a temporary option.

#### The option '%1' cannot be set from within a procedure

| ltem       | V          | alue                    |
|------------|------------|-------------------------|
| SQLCOD     | E -2       | 17                      |
| Constant   | S          | QLE_OPTION_IN_PROCEDURE |
| SQLSTAT    | TE 42      | 2W53                    |
| Sybase err | or code 58 | 378                     |
| ODBC 2 S   | State 42   | 2000                    |
| ODBC 3 S   | State 42   | 2000                    |
|            |            |                         |

## **Probable cause** The option specified in the SET OPTION statement cannot be set from within a procedure.

#### The pattern is too long

| Item              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -606                  |
| Constant          | SQLE_PATTERN_TOO_LONG |
| SQLSTATE          | WW001                 |
| Sybase error code | 7706                  |
| ODBC 2 State      | ERROR                 |
| ODBC 3 State      | ERROR                 |
|                   |                       |

Probable causeThe pattern for the LIKE operator is too long. All patterns of 126 characters<br/>or less are supported. Some patterns as long as 254 characters are supported,<br/>depending on their contents. Patterns longer than 254 characters are not<br/>supported.

## The remote server does not support an auto-incrementing data type

| ltem              | Value                           |
|-------------------|---------------------------------|
| SQLCODE           | -698                            |
| Constant          | SQLE_OMNI_AUTOINC_NOT_SUPPORTED |
| SQLSTATE          | WO011                           |
| Sybase error code | 11205                           |
| ODBC 2 State      | ERROR                           |
| ODBC 3 State      | ERROR                           |

### **Probable cause** Auto-incrementing data types can only be supported in a proxy table when the backend server supports this feature.

| Item              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -666                                  |
| Constant          | SQLE_OMNI_RMT_TABLE_NOTFOUND          |
| SQLSTATE          | WO007                                 |
| Sybase error code | 11214                                 |
| ODBC 2 State      | ERROR                                 |
| ODBC 3 State      | ERROR                                 |
| Parameter 1       | The complete name of the remote table |

#### The remote table '%1' could not be found

**Probable cause** The table could not be found on the remote server. Check the remote table name and the user privileges on that table.

## The Select list for the derived table '%1' has no expression to match '%2'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -812   |
| Constant          | SQLE_NO_MATCHING_SELECT_ITEM                                 |
| SQLSTATE          | 42W59  |
| Sybase error code | 13822  |
| ODBC 2 State      | 37000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Name of the derived table.                                   |
| Parameter 2       | Name of the alias for which there is no matching expression. |

Probable cause The specified alias from the derived table's AS clause has no matching expression from the Select statement for that derived table. Ensure that each Select list item has a matching alias in the derived table's AS clause, and vice-versa.

#### The selected database is currently inactive

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -74                      |
| Constant          | SQLE_DATABASE_NOT_ACTIVE |
| SQLSTATE          | 08W30                    |
| Sybase error code | 950                      |
| ODBC 2 State      | 08001                    |
| ODBC 3 State      | 08001                    |
|                   | •                        |

#### Probable cause

The selected database is in an inactive state. The database may be in the process of being started or of being shut down.

## The server attempted to access a page beyond the end of the maximum allowable dbspace file size

| ltem              | Value                                     |
|-------------------|---|
| SQLCODE           | -605                                      |
| Constant          | SQLE_ACCESS_BEYOND_END_OF_MAX_DBSPA<br>CE |
| SQLSTATE          | 04W08                                     |
| Sybase error code | 5006                                      |
| ODBC 2 State      | ERROR                                     |
| ODBC 3 State      | ERROR                                     |
|                   |   |

**Probable cause** The database attempted to access a page whose page number is beyond the maximum possible number of disk pages. This is a fatal internal error.

| Value                          |
|--------------------------------|
| -729                           |
| SQLE_UNENFORCEABLE_FOREIGN_KEY |
| 23507                          |
| 549                            |
| 23000                          |
| 23000                          |
| Name of the foreign key.       |
|                                |

**Probable cause** You attempted to create a foreign key that can not be enforced. In order to enforceable, the primary and foreign table for the specified key must exist on the same server. You can use the 'unenforced' keyword to create a foreign key specification that is not to be enforced.

#### The specified transaction isolation is invalid

| ltem              | Value                              |
|-------------------|------------------------------------|
| SQLCODE           | -676                               |
| Constant          | SQLE_INVALID_TRANSACTION_ISOLATION |
| SQLSTATE          | WJ003                              |
| Sybase error code | 7374                               |
| ODBC 2 State      | ERROR                              |
| ODBC 3 State      | ERROR                              |

**Probable cause** The specified transaction isolation is invalid.

#### The table specification '%1' identifies more than one remote table

| Item              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -726                                  |
| Constant          | SQLE_OMNI_RMT_TABLE_NOTUNIQUE         |
| SQLSTATE          | WO020                                 |
| Sybase error code | 11215                                 |
| ODBC 2 State      | ERROR                                 |
| ODBC 3 State      | ERROR                                 |
| Parameter 1       | The complete name of the remote table |

**Probable cause** More than one table was found on the remote server for the given table specification. Add a database or owner name to the specification.

#### There are still active database connections

| _ | Item              | Value                         |
|---|-------------------|-------------------------------|
|   | SQLCODE           | -109                          |
|   | Constant          | SQLE_STILL_ACTIVE_CONNECTIONS |
|   | SQLSTATE          | 08W06                         |
|   | Sybase error code | 6001                          |
|   | ODBC 2 State      | ERROR                         |
|   | ODBC 3 State      | ERROR                         |
|   |                   |                               |

**Probable cause** You attempted to shut down a database which still has active connections.

#### There is already a variable named '%1'

| Item              | Value                |
|-------------------|----------------------|
| SQLCODE           | -261                 |
| Constant          | SQLE_VARIABLE_EXISTS |
| SQLSTATE          | 42W15                |
| Sybase error code | 134                  |
| ODBC 2 State      | 37000                |
| ODBC 3 State      | 42000                |
|                   |                      |

**Probable cause** You attempted to CREATE a variable with the name of another variable that already exists.

#### There is more than one way to join '%1' to '%2'

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | -147  |
| Constant          | SQLE_AMBIGUOUS_JOIN                         |
| SQLSTATE          | 52W08                                       |
| Sybase error code | 301   |
| ODBC 2 State      | 37000                                       |
| ODBC 3 State      | 42000                                       |
| Parameter 1       | Name of first table that cannot be joined.  |
| Parameter 2       | Name of second table that cannot be joined. |

# Probable cause You are attempting to KEY JOIN two tables, and there are two or more foreign keys relating the two tables. There may be two foreign keys from the first table to the second table It may be that each table has a foreign key to the other table. You must use a correlation name for the primary key table which is the same as the role name of the desired foreign key relationship.

#### There is no way to join '%1' to '%2'

| Item              | Value                                       |
|-------------------|---|
| SQLCODE           | -146  |
| Constant          | SQLE_CANNOT_JOIN                            |
| SQLSTATE          | 53W04                                       |
| Sybase error code | 301   |
| ODBC 2 State      | 37000                                       |
| ODBC 3 State      | 42000                                       |
| Parameter 1       | Name of first table that cannot be joined.  |
| Parameter 2       | Name of second table that cannot be joined. |
|                   |   |

## Probable cause You may have attempted a KEY JOIN between two tables and there is no foreign key on one of the tables that references the primary key of the other table. You may have attempted a NATURAL JOIN between two tables that have no common column names.

#### There is no way to join to '%1'

| lt | em               | Value  |
|----|------------------|--|
| S  | QLCODE           | -875   |
| С  | onstant          | SQLE_CANNOT_JOIN_TABEXPR                     |
| S  | QLSTATE          | 42W73  |
| S  | ybase error code | 102  |
| 0  | DBC 2 State      | 37000  |
| 0  | DBC 3 State      | 42000  |
| P  | arameter 1       | Name of table or view that cannot be joined. |

Probable cause The server cannot discover a valid join condition involving this table. If the join is an outer join, you may be missing an ON clause. If the join is a KEY JOIN, the server cannot discover a foreign key-primary key relationship with this table that can be used to generate the join condition. If the join is a NATURAL JOIN, the table has no common column names with the table expression it is being joined to.

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -616                           |
| Constant          | SQLE_TOO_MANY_COLUMNS_IN_TABLE |
| SQLSTATE          | 52W20                          |
| Sybase error code | 1702                           |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |
|                   | -                              |

#### Too many columns in table

## **Probable cause** You executed a CREATE TABLE or ALTER TABLE statement, which attempted to add a column to a table. The resulting number of columns in the table would exceed the limit for the current database page size.

#### Too many parameters to this external procedure call

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -625                     |
| Constant          | SQLE_TOO_MANY_PARAMETERS |
| SQLSTATE          | WW010                    |
| Sybase error code | 13680                    |
| ODBC 2 State      | ERROR                    |
| ODBC 3 State      | ERROR                    |
|                   |                          |

Probable cause There is a maximum of 256 parameters to an external function call in 32-bit Windows.

#### too many temporary tables in connection

|   | Item              | Value                     |
|---|-------------------|---------------------------|
| - | SQLCODE           | -817                      |
|   | Constant          | SQLE_TOO_MANY_TEMP_TABLES |
|   | SQLSTATE          | 52W41                     |
|   | Sybase error code | 13823                     |
|   | ODBC 2 State      | ERROR                     |
|   | ODBC 3 State      | ERROR                     |
|   |                   |                           |

 Probable cause
 A CREATE TABLE or DECLARE TABLE statement attempted to create a temporary table, but the resulting number of distinct table ids used for temporary tables in the current connection would exceed the limit.

#### Transact-SQL feature not supported

| ltem              | Value                           |
|-------------------|---------------------------------|
| <br>SQLCODE       | -611                            |
| Constant          | SQLE_TSQL_FEATURE_NOT_SUPPORTED |
| SQLSTATE          | 0AW02                           |
| Sybase error code | 176                             |
| ODBC 2 State      | 37000                           |
| ODBC 3 State      | 42000                           |
|                   |                                 |

Probable cause You attempted to use a Transact-SQL feature that is not supported in Adaptive Server Anywhere.

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | 110                         |
| Constant          | SQLE_BACKUP_PAGE_INCOMPLETE |
| SQLSTATE          | 01W10                       |
| Sybase error code | 13683                       |
| ODBC 2 State      | ОК                          |
| ODBC 3 State      | ОК                          |

#### Transaction log backup page only partially full

**Probable cause** A DB\_LOG\_BACKUP\_READ\_WAIT was issued against the transaction log and the page returned was not full. The application should reissue the request for the same page.

#### Transaction log was truncated

| Item              | Value              |
|-------------------|--------------------|
| SQLCODE           | -244               |
| Constant          | SQLE_LOG_TRUNCATED |
| SQLSTATE          | WB005              |
| Sybase error code | 13661              |
| ODBC 2 State      | ERROR              |
| ODBC 3 State      | ERROR              |
|                   | •                  |

Probable causeAn operation was being performed on the transaction log such as SQL<br/>Remote or Replication Agent processing and the transaction log was<br/>truncated by an independent backup during that operation.

#### Trigger '%1' not found

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -268   |
| Constant          | SQLE_TRIGGER_NOT_FOUND                       |
| SQLSTATE          | 52W10  |
| Sybase error code | 9819   |
| ODBC 2 State      | S0002  |
| ODBC 3 State      | 42S02  |
| Parameter 1       | Name of the trigger that could not be found. |
|                   |  |

Probable cause

You misspelled the name of a trigger, or you did not qualify a trigger name with a user name.

#### Trigger definition conflicts with existing triggers

|   | ltem              | Value                      |
|---|-------------------|----------------------------|
| _ | SQLCODE           | -271                       |
|   | Constant          | SQLE_TRIGGER_DEFN_CONFLICT |
|   | SQLSTATE          | 52W11                      |
|   | Sybase error code | 102                        |
|   | ODBC 2 State      | S0002                      |
|   | ODBC 3 State      | 42S01                      |
|   |                   |                            |

**Probable cause** You attempted to create a trigger, but a trigger with the same name already exists.

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -855                           |
| Constant          | SQLE_AMBIGUOUS_TRIGGER_NAME    |
| SQLSTATE          | 42W66                          |
| Sybase error code | 13858                          |
| ODBC 2 State      | 37000                          |
| ODBC 3 State      | 42000                          |
| Parameter 1       | Name of the ambiguous trigger. |
|                   |                                |

#### Trigger name '%1' is ambiguous

**Probable cause** A statement has referred to a trigger name which is not unique. Preface the trigger name by a table and/or owner name.

#### Trigger or foreign key for table '%1' is no longer valid

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -837                         |
| Constant          | SQLE_TRIGGER_NO_LONGER_VALID |
| SQLSTATE          | 42W64                        |
| Sybase error code | 13843                        |
| ODBC 2 State      | 37000                        |
| ODBC 3 State      | 42000                        |
| Parameter 1       | Name of the table.           |

## **Probable cause** A trigger definition cannot be loaded from the catalog. Check for tables or columns which have been renamed or which may be reserved words. The trigger may be a system-generated trigger to enforce the referential actions of a foreign key.

#### Triggers and procedures not supported in runtime server

| ltem              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -275                           |
| Constant          | SQLE_PROCEDURES_NOT_IN_DESKTOP |
| SQLSTATE          | 0AW04                          |
| Sybase error code | 102                            |
| ODBC 2 State      | ERROR                          |
| ODBC 3 State      | ERROR                          |

**Probable cause** You attempted to call a stored procedure or have modified a row in a table on which a trigger is defined and you are using the runtime server. Triggers and stored procedures are not supported in the runtime server. You must be running the full server to use these features.

#### TRUNCATE TABLE statement cannot refer to a view

| Item              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -702                      |
| Constant          | SQLE_CANNOT_TRUNCATE_VIEW |
| SQLSTATE          | 42W49                     |
| Sybase error code | 4708                      |
| ODBC 2 State      | 37000                     |
| ODBC 3 State      | 42000                     |

Probable causeYou attempted to use TRUNCATE TABLE on a view. The TRUNCATE<br/>TABLE statement deletes every row from a table and cannot be used to<br/>delete rows from a view. Replace the view reference with the name of a base<br/>table.

| Unable to connect to server '%1': %2 | Unable | to | connect to | server | '%1': %2 |
|--------------------------------------|--------|----|------------|--------|----------|
|--------------------------------------|--------|----|------------|--------|----------|

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -656  |
| Constant          | SQLE_OMNI_CONNECT_ERROR                                       |
| SQLSTATE          | WO001   |
| Sybase error code | 11206   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | The name of the server that could not be connected to         |
| Parameter 2       | A more specific reason returned from the server class driver. |

**Probable cause** You attempted to connect to a remote server. Check that the remote server is running.

#### Unable to connect to server '%1': server definition is circular

| Item              | Value   |
|-------------------|---|
| SQLCODE           | -657  |
| Constant          | SQLE_OMNI_CIRCULAR_CONNECT                            |
| SQLSTATE          | WO002   |
| Sybase error code | 13593   |
| ODBC 2 State      | ERROR   |
| ODBC 3 State      | ERROR   |
| Parameter 1       | The name of the server that could not be connected to |
|                   |   |

## **Probable cause** You attempted to connect to a remote server which maps to the local database.

#### Unable to delete database file

| ltem              | Value                             |  |
|-------------------|-----------------------------------|--|
| SQLCODE           | -243                              |  |
| Constant          | SQLE_BACKUP_UNABLE_TO_DELETE_FILE |  |
| SQLSTATE          | WB004                             |  |
| Sybase error code | 13660                             |  |
| ODBC 2 State      | ERROR                             |  |
| ODBC 3 State      | ERROR                             |  |
|                   |                                   |  |

#### Probable cause

You attempted to delete a database file, but it could not be deleted. The filename should not be the same as any database file that is currently in use.

#### Unable to enlist transaction; DTC may be down

| _ | Item              | Value                 |
|---|-------------------|-----------------------|
|   | SQLCODE           | -803                  |
|   | Constant          | SQLE_FAILED_TO_ENLIST |
|   | SQLSTATE          | WL005                 |
|   | Sybase error code | 13813                 |
|   | ODBC 2 State      | ERROR                 |
|   | ODBC 3 State      | ERROR                 |
|   |                   |                       |

**Probable cause** You tried to enlist a transaction but DTC does not seem to be available at this time.

| Item     |            | Value                                       |
|----------|------------|---|
| SQLCO    | DE         | -189  |
| Constant | t          | SQLE_NOT_FOUND_IN_INDEX                     |
| SQLSTA   | ATE        | WI005                                       |
| Sybase e | error code | 2727  |
| ODBC 2   | 2 State    | ERROR                                       |
| ODBC 3   | 3 State    | ERROR                                       |
| Paramete | er 1       | Name of invalid index.                      |
| Paramete | er 2       | Name of table containing the invalid index. |
|          |            |   |

#### Unable to find in index '%1' for table '%2'

**Probable cause** This is an internal error. If it can be reproduced, it should be reported to iAnywhere Solutions. You should be able to work around the error by dropping and recreating the index.

#### Unable to open backup log '%1'

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | 119                            |
| Constant          | SQLE_UNABLE_TO_OPEN_BACKUP_LOG |
| SQLSTATE          | WB011                          |
| Sybase error code | 13776                          |
| ODBC 2 State      | ОК                             |
| ODBC 3 State      | ОК                             |
| Parameter 1       | backup log filename            |
|                   | •                              |

Probable causeThe server was unable to open the backup log to record the execution of a<br/>BACKUP or RESTORE statement. Check the settings of the environment<br/>variables used to locate the backup log file. The directory to contain the log<br/>must already exist.

#### Unable to reenlist transaction; DTC may be down

| ltem              | Value                   |  |
|-------------------|-------------------------|--|
| SQLCODE           | -804                    |  |
| Constant          | SQLE_FAILED_TO_REENLIST |  |
| SQLSTATE          | WL006                   |  |
| Sybase error code | 13814                   |  |
| ODBC 2 State      | ERROR                   |  |
| ODBC 3 State      | ERROR                   |  |

#### Probable cause

You tried to recover a transaction but DTC does not seem to be available at this time.

#### Unable to start database server

|                | Item  | Value                       |
|----------------|---|-----------------------------|
|                | SQLCODE   | -80                         |
|                | Constant  | SQLE_UNABLE_TO_START_ENGINE |
|                | SQLSTATE  | 08W07                       |
|                | Sybase error code   | 708                         |
|                | ODBC 2 State  | 08001                       |
|                | ODBC 3 State  | 08001                       |
|                |   | •                           |
| Probable cause | It was not possible to start the database server. There may not be enough |                             |

**Probable cause** It was not possible to start the database server. There may not be enough memory to run the database server. It may be that the executable cannot be found.

#### Unable to start specified database: %1

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -82                           |
| Constant          | SQLE_UNABLE_TO_START_DATABASE |
| SQLSTATE          | 08W09                         |
| Sybase error code | 840                           |
| ODBC 2 State      | 08001                         |
| ODBC 3 State      | 08001                         |
|                   | •                             |

## **Probable cause** The database server was started but was unable to find the specified database. No specific reason is known.

#### Undefined synchronization template '%1'

| ltem              | Value                                    |  |
|-------------------|--|--|
| SQLCODE           | -795                                     |  |
| Constant          | SQLE_SYNC_TEMPLATE_NOT_FOUND             |  |
| SQLSTATE          | 5RW30                                    |  |
| Sybase error code | 13805                                    |  |
| ODBC 2 State      | 42000                                    |  |
| ODBC 3 State      | 42S02                                    |  |
| Parameter 1       | The name of the synchronization template |  |

## **Probable cause** You attempted to define a remote synchronization site using an undefined synchronization template.

#### Unknown backup operation

| Item              | Value                         |  |
|-------------------|-------------------------------|--|
| SQLCODE           | -240                          |  |
| Constant          | SQLE_UNKNOWN_BACKUP_OPERATION |  |
| SQLSTATE          | WB001                         |  |
| Sybase error code | 3206                          |  |
| ODBC 2 State      | ERROR                         |  |
| ODBC 3 State      | ERROR                         |  |
|                   |                               |  |

#### Probable cause You specified an invalid backup statement operation in a call to db\_backup.

#### Unknown function '%1'

|                | Item   | Value  |  |
|----------------|--|--|--|
|                | SQLCODE  | -148   |  |
|                | Constant   | SQLE_UNKNOWN_FUNC                              |  |
|                | SQLSTATE   | 42W05  |  |
|                | Sybase error code  | 176  |  |
|                | ODBC 2 State   | 37000  |  |
|                | ODBC 3 State   | 42000  |  |
|                | Parameter 1  | Function name that is not a database function. |  |
|                |  |  |  |
| Probable cause | You misspelled the name of a database function (such as MAXIMUM instead of MAX) in a query definition or in a query column name. |  |  |

| ltem              | Value                     |
|-------------------|---------------------------|
| SQLCODE           | -643                      |
| Constant          | SQLE_CANNOT_UNLOAD_A_VIEW |
| SQLSTATE          | WL004                     |
| Sybase error code | 13672                     |
| ODBC 2 State      | ERROR                     |
| ODBC 3 State      | ERROR                     |
|                   |                           |

Probable causeUNLOAD TABLE was specified with the name of a view. UNLOAD<br/>TABLE may only be used to unload tables.

## Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead

| ltem              | Value   |
|-------------------|---|
| <br>SQLCODE       | 117   |
| Constant          | SQLE_UNSUPPORTED_CHARSET_AND_LANGUA<br>GE                               |
| SQLSTATE          | 01W15   |
| Sybase error code | 13616   |
| ODBC 2 State      | 01000   |
| ODBC 3 State      | 01000   |
| Parameter 1       | Name of the character set that could not be supported.                  |
| Parameter 2       | Name of the language that could not be supported.                       |
| Parameter 3       | Name of the language that the server will use to send language strings. |
|                   |   |

**Probable cause** The character set that the application requested is not supported by the server to which the application is connecting. The language that the application requested is not supported either. Language strings will be sent in the language specified.

#### **Unterminated C string**

| lt | em               | Value                   |
|----|------------------|-------------------------|
| S  | QLCODE           | -634                    |
| С  | Constant         | SQLE_UNTERMINATED_C_STR |
| S  | QLSTATE          | 22024                   |
| S  | ybase error code | 13682                   |
| 0  | DDBC 2 State     | 22024                   |
| C  | DDBC 3 State     | 22024                   |

#### Probable cause

The least significant character of a C string host variable must contain the null character.

#### Update operation attempted on a read-only cursor

| ltem              | Value                 |
|-------------------|-----------------------|
| SQLCODE           | -633                  |
| Constant          | SQLE_READ_ONLY_CURSOR |
| SQLSTATE          | 42W30                 |
| Sybase error code | 7732                  |
| ODBC 2 State      | S1009                 |
| ODBC 3 State      | HY092                 |
|                   |                       |

**Probable cause** You attempted an update operation on a cursor that was explicitly declared as read-only.

| ltem              | Value                    |
|-------------------|--------------------------|
| SQLCODE           | -192                     |
| Constant          | SQLE_NON_UPDATEABLE_VIEW |
| SQLSTATE          | 42W31                    |
| Sybase error code | 7301                     |
| ODBC 2 State      | 42000                    |
| ODBC 3 State      | 42000                    |
|                   | •                        |

#### Update operation attempted on non-updatable query

Probable cause You attempted an insert, update, or delete operation on a query that is implicitly read-only. Queries that contain DISTINCT, GROUP BY, HAVING, or UNION, or that contain aggregate functions, or that involve a join, are implicitly read only. If the query references a view then the view may be non-updatable.

#### Update operation attempted on non-updatable remote query

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -728                        |
| Constant          | SQLE_NON_UPDATEABLE_EXT_TAB |
| SQLSTATE          | 42W35                       |
| Sybase error code | 7338                        |
| ODBC 2 State      | 42000                       |
| ODBC 3 State      | 42000                       |

## **Probable cause** You attempted an update, or delete operation on a remote table that is currently not implemented. Examples of such operations include positioned updates and updates that require building of work tables.

#### User '%1' already has GRANT permission

| Value  |
|--|
| -120   |
| SQLE_ALREADY_HAS_GRANT_PERMS                           |
| 42W01  |
| 13625  |
| 42000  |
| 42000  |
| Name of the user ID that already has GRANT permission. |
|  |

### **Probable cause** You attempted to give a user GRANT OPTION and that user already has GRANT OPTION.

#### User '%1' already has membership in group '%2'

| Item              | Value  |
|-------------------|--|
| SQLCODE           | -312   |
| Constant          | SQLE_ALREADY_HAS_GROUP_MEMBERSHIP                |
| SQLSTATE          | 42W34  |
| Sybase error code | 13627  |
| ODBC 2 State      | 42000  |
| ODBC 3 State      | 42000  |
| Parameter 1       | Name of the user ID that already has membership. |
| Parameter 2       | Name of the group.                               |
|                   |  |

## **Probable cause** You attempted to give a membership in a group to a user that already has such membership.

#### User '%1' has the row in '%2' locked

| ltem              | Value                            |
|-------------------|----------------------------------|
| SQLCODE           | -210                             |
| Constant          | SQLE_LOCKED                      |
| SQLSTATE          | 42W18                            |
| Sybase error code | 8405                             |
| ODBC 2 State      | 40001                            |
| ODBC 3 State      | 40001                            |
| Parameter 1       | Name of another user.            |
| Parameter 2       | Table which generates the error. |
|                   |                                  |

Probable causeYou attempted to read or write a row and it is locked by another user, while<br/>the BLOCKING database option is set to OFF.

#### User '%1' is already the publisher for this database

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -284                    |
| Constant          | SQLE_ONLY_ONE_PUBLISHER |
| SQLSTATE          | 5RW05                   |
| Sybase error code | 13646                   |
| ODBC 2 State      | S0002                   |
| ODBC 3 State      | 42S02                   |
| Parameter 1       | Name of the publisher.  |
|                   |                         |

## **Probable cause** You attempted to GRANT PUBLISH to a user ID, when a publisher already exists.

#### User '%1' is not a remote user for this database

| ltem              | Value                |
|-------------------|----------------------|
| SQLCODE           | -285                 |
| Constant          | SQLE_NOT_REMOTE_USER |
| SQLSTATE          | 5RW06                |
| Sybase error code | 13647                |
| ODBC 2 State      | S0002                |
| ODBC 3 State      | 42S02                |
| Parameter 1       | Name of user.        |
|                   | ·                    |

## Probable causeYou attempted to CREATE a subscription for a user, or PASSTHROUGH<br/>for a user that is not a remote user of this database. You must GRANT<br/>REMOTE or GRANT CONSOLIDATE.

#### User '%1' is not a user group

| ltem              | Value                                 |
|-------------------|---------------------------------------|
| SQLCODE           | -123                                  |
| Constant          | SQLE_NOT_A_GROUP                      |
| SQLSTATE          | 42W03                                 |
| Sybase error code | 13626                                 |
| ODBC 2 State      | 42000                                 |
| ODBC 3 State      | 42000                                 |
| Parameter 1       | Name of user you thought was a group. |

### **Probable cause** You attempted to add a member to group, but the user ID specified as a group has not been granted the GROUP special privilege.

#### User ID '%1' does not exist

| Value  |
|--|
| -140   |
| SQLE_UNKNOWN_USERID                          |
| 08004  |
| 509  |
| 28000  |
| 28000  |
| Name of the user ID that could not be found. |
|  |

Probable cause You used a user ID that does not exist.

#### User message %1 already exists

| Item              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -610                        |
| Constant          | SQLE_MESSAGE_ALREADY_EXISTS |
| SQLSTATE          | 52W16                       |
| Sybase error code | 13624                       |
| ODBC 2 State      | 42000                       |
| ODBC 3 State      | 42000                       |
|                   | •                           |

**Probable cause** The message with this error number already exists in the SYSUSERMESSAGES system table.

**Probable cause** 

#### User message %1 not found

| Item              | Value                  |
|-------------------|------------------------|
| SQLCODE           | -612                   |
| Constant          | SQLE_MESSAGE_NOT_FOUND |
| SQLSTATE          | 52W17                  |
| Sybase error code | 2748                   |
| ODBC 2 State      | 42000                  |
| ODBC 3 State      | 42000                  |
| Parameter 1       | Message number.        |

## User owns procedures in use

SYSUSERMESSAGES.

|                | Item  | Value                            |
|----------------|---|----------------------------------|
|                | SQLCODE   | -750                             |
|                | Constant  | SQLE_USER_OWNS_PROCEDURES_IN_USE |
|                | SQLSTATE  | 42W55                            |
|                | Sybase error code   | 3702                             |
|                | ODBC 2 State  | 40001                            |
|                | ODBC 3 State  | 40001                            |
|                |   |                                  |
| Probable cause | You attempted to REVOKE CONNECT from a user that owns a procedure being used by other active users of the database. |                                  |

The message with this error number does not exist in

#### User owns tables in use

| Item              | Value                        |
|-------------------|------------------------------|
| SQLCODE           | -751                         |
| Constant          | SQLE_USER_OWNS_TABLES_IN_USE |
| SQLSTATE          | 42W56                        |
| Sybase error code | 3702                         |
| ODBC 2 State      | 40001                        |
| ODBC 3 State      | 40001                        |
|                   | 1                            |

**Probable cause** You attempted to REVOKE CONNECT from a user that owns a table being used by other active users of the database.

#### **User-defined exception signaled**

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -297                        |
| Constant          | SQLE_USER_DEFINED_EXCEPTION |
| SQLSTATE          | 99999                       |
| Sybase error code | 13662                       |
| ODBC 2 State      | ERROR                       |
| ODBC 3 State      | ERROR                       |

Probable cause A stored procedure or trigger signaled a user-defined exception. This error state is reserved for use within stored procedures or triggers which contain exception handlers, as a way of signaling an exception which can be guaranteed to not have been caused by the database server. Valid SQLSTATE values range from 99000 to 99999 and are set by the user when executing the signal SQL statement.

#### User-defined type '%1' not found

| Item              | Value                          |
|-------------------|--------------------------------|
| SQLCODE           | -613                           |
| Constant          | SQLE_USER_TYPE_NOT_FOUND       |
| SQLSTATE          | 52W18                          |
| Sybase error code | 2715                           |
| ODBC 2 State      | 42000                          |
| ODBC 3 State      | 42000                          |
| Parameter 1       | Name of the user-defined type. |
|                   |                                |

**Probable cause** The user-defined type with this name does not exist in SYSUSERTYPE.

#### Using temporary table

|                | Item                | Value   |
|----------------|---------------------|---|
|                | SQLCODE             | 102   |
|                | Constant            | SQLE_TEMPORARY_TABLE                                |
|                | SQLSTATE            | 01W02   |
|                | Sybase error code   | 13075   |
|                | ODBC 2 State        | 01000   |
|                | ODBC 3 State        | 01000   |
|                |                     |   |
| Probable cause | A temporary table h | as been created in order to satisfy the query. This |

A temporary table has been created in order to satisfy the query. This warning can only occur on an OPEN statement.

#### VALIDATE TABLE statement must refer to a base table

| ltem              | Value                       |
|-------------------|-----------------------------|
| SQLCODE           | -720                        |
| Constant          | SQLE_CANNOT_VALIDATE_OBJECT |
| SQLSTATE          | 42W51                       |
| Sybase error code | 13729                       |
| ODBC 2 State      | 37000                       |
| ODBC 3 State      | 42000                       |

**Probable cause** The VALIDATE TABLE statement must refer to a local base table; it cannot refer to a view, an IQ table, or an object on a remote server.

#### Value %1 out of range for destination

| Item              | Value                               |
|-------------------|-------------------------------------|
| SQLCODE           | -158                                |
| Constant          | SQLE_OVERFLOW_ERROR                 |
| SQLSTATE          | 22003                               |
| Sybase error code | 220                                 |
| ODBC 2 State      | 22003                               |
| ODBC 3 State      | 22003                               |
| Parameter 1       | The value that caused the overflow. |

**Probable cause** You supplied to or fetched from the database a value that is out of range for the destination column or host variable. For example, the value 10 may have been supplied for a DECIMAL(3,2) field.

#### Value for column '%1' in table '%2' has changed

| Item                                    | Value                                       |
|---|---|
| SQLCODE                                 | 106   |
| Constant                                | SQLE_COLUMN_VALUE_CHANGED                   |
| SQLSTATE                                | 01W06                                       |
| Sybase error code                       | 532   |
| ODBC 2 State                            | ОК  |
| ODBC 3 State                            | ОК  |
| Parameter 1                             | Name of the column whose value has changed. |
| Parameter 2                             | Name of the table containing the column.    |
| , i i i i i i i i i i i i i i i i i i i |   |

**Probable cause** A replicated UPDATE has found a value in an updated column that does not match the value when the original UPDATE was made.

#### Value truncated

| _ | Item              | Value          |
|---|-------------------|----------------|
|   | SQLCODE           | 101            |
|   | Constant          | SQLE_TRUNCATED |
|   | SQLSTATE          | 01004          |
|   | Sybase error code | 7337           |
|   | ODBC 2 State      | 01004          |
|   | ODBC 3 State      | 01004          |

**Probable cause** You may have tried to insert, update, or select a value in the database that is too large to fit in the destination. You may have fetched data into a host variable or SQLDA variable not large enough to receive the value.

#### Variable '%1' not found

| Item              | Value                   |
|-------------------|-------------------------|
| SQLCODE           | -260                    |
| Constant          | SQLE_VARIABLE_NOT_FOUND |
| SQLSTATE          | 42W14                   |
| Sybase error code | 137                     |
| ODBC 2 State      | 37000                   |
| ODBC 3 State      | 42000                   |
|                   |                         |

## **Probable cause** You attempted to DROP or SET the value of a SQL variable that was not created or was previously dropped.

## View references '%1', which is a temporary object. Views can only refer to permanent objects.

| ltem              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -766                       |
| Constant          | SQLE_VIEW_OVER_TEMP_OBJECT |
| SQLSTATE          | 42U00                      |
| Sybase error code | 4412                       |
| ODBC 2 State      | 42000                      |
| ODBC 3 State      | 42000                      |
| Parameter 1       | Temporary object name      |
|                   | •                          |

### **Probable cause** Views must refer only to permanent objects, not to temporary objects such as local temporary tables.

#### Warning

| ltem              | Value        |
|-------------------|--------------|
| SQLCODE           | 200          |
| Constant          | SQLE_WARNING |
| SQLSTATE          | 01000        |
| Sybase error code | 13619        |
| ODBC 2 State      | ОК           |
| ODBC 3 State      | ОК           |

### **Probable cause** A warning has occurred. The message indicates the condition that caused the warning.

#### WITH CHECK OPTION violated for insert/update on base table '%1'

|                | ltem   | Value                                 |
|----------------|--|---------------------------------------|
|                | SQLCODE  | -632                                  |
|                | Constant   | SQLE_WITH_CHECK_OPTION_VIOLATION      |
|                | SQLSTATE   | 44000                                 |
|                | Sybase error code  | 550                                   |
|                | ODBC 2 State   | S1000                                 |
|                | ODBC 3 State   | 44000                                 |
|                | Parameter 1  | Name of the base table being updated. |
|                |  |                                       |
| Probable cause | You attempted an insert or update operation on the indicated base table<br>through a view (possibly nested). However, one or more values in the<br>modified row(s) triggered a WITH CHECK OPTION violation. This<br>violation occurs when a modified value causes one or more rows to fall |                                       |

to FALSE or UNKNOWN for that row.

outside the range of the view by making the view's WHERE clause evaluate

| Wrong number of parameters to function '%1' |
|---|
|---|

| Item              | Value                      |
|-------------------|----------------------------|
| SQLCODE           | -154                       |
| Constant          | SQLE_WRONG_PARAMETER_COUNT |
| SQLSTATE          | 37505                      |
| Sybase error code | 174                        |
| ODBC 2 State      | 37000                      |
| ODBC 3 State      | 42000                      |
| Parameter 1       | Name of the function.      |
|                   | •                          |

Probable cause You supplied an incorrect number of parameters to a database function.

#### Wrong number of values for INSERT

| Item              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -207                          |
| Constant          | SQLE_WRONG_NUM_OF_INSERT_COLS |
| SQLSTATE          | 53002                         |
| Sybase error code | 213                           |
| ODBC 2 State      | 21S01                         |
| ODBC 3 State      | 21S01                         |
|                   | ·                             |

**Probable cause** The number of values you are trying to insert does not match the number of columns specified in the INSERT statement, or the number of columns in the table if no columns are specified.

#### Wrong number of variables in FETCH

| Item              | Value                             |
|-------------------|-----------------------------------|
| SQLCODE           | -264                              |
| Constant          | SQLE_WRONG_NUM_OF_FETCH_VARIABLES |
| SQLSTATE          | 42W26                             |
| Sybase error code | 553                               |
| ODBC 2 State      | S1002                             |
| ODBC 3 State      | 07009                             |
|                   |                                   |

## **Probable cause** You specified a number of variables in a FETCH statement that does not match the number of select list items.

#### You cannot synchronize with uncommitted transactions

| ltem              | Value                         |
|-------------------|-------------------------------|
| SQLCODE           | -755                          |
| Constant          | SQLE_UNCOMMITTED_TRANSACTIONS |
| SQLSTATE          | 0AW08                         |
| Sybase error code | 13765                         |
| ODBC 2 State      | 37000                         |
| ODBC 3 State      | 42000                         |
|                   | •                             |

### **Probable cause** You attempted to synchronize an UltraLite database and there are changes in the UltraLite database that have not been committed.

### Internal errors (assertion failed)

Adaptive Server Anywhere has many internal checks that have been designed to detect possible database corruption as soon as possible. If the database server prints an Assertion Failed message, you should not continue to use it before attempting to determine the cause. You should record the assertion number displayed on the screen and report the error to Adaptive Server Anywhere technical support.

The *dbvalid* utility is useful for determining if your database file is corrupt. You may find it necessary to reconstruct your data from backups and transaction logs (see "Backup and Data Recovery" on page 299 of the book *ASA Database Administration Guide*).

### Index

#### Α

assertion failed error, 317

#### D

documentation SQL Anywhere Studio, vi

#### Ε

errors alphabetical list of messages, 72 codes, 1, 2, 24 error messages, 72 indexed by SQLCODE, 2, 24 indexed by Sybase error code, 45 messages, 1 SQLCODE values, 2 SQLSTATE values, 24

#### F

feedback documentation, ix providing, ix

#### Ν

newsgroups technical support, ix

#### S

SQL Anywhere Studio documentation, vi

SQLCODE values, 1, 2

SQLSTATE values, 24

support newsgroups, ix

#### Т

technical support newsgroups, ix

#### W

warnings error messages, 72 SQLCODE values, 2 SQLSTATE values, 24 W–W